View NSN Online: https://aerobasegroup.co.il/nsn/8010-00-598-5730

FARWEST PAINT MFG CO -- WONDERGLO 900 FLAT LATEX INTERIOR, 37875, WHITE 8010-00-598-5730

Product ID:WONDERGLO 900 FLAT LATEX INTERIOR, 37875, WHITE MSDS Date:12/01/1993 FSC:8010 NIIN:00-598-5730 MSDS Number: BWGYY === Responsible Party === Company Name: FARWEST PAINT MFG CO Address:4522 S 133 ST City:TUKWILA State:WA ZIP:98168 Country:US Info Phone Num:206-2 44-8844 Emergency Phone Num:206-941-1619 Preparer's Name: CARWIN BEARDALL CAGE:6F266 === Contractor Identification === Company Name: FARWEST PAINT MANUFACTURING CO Address:4522 SOUTH 133RD ST Box:City:TUKWILA State:WA ZIP:98168 Country:US Phone:206-244-8844 CAGE:6F266

Ingred Name:ETHYLENE GLYCOL (SARA 313) CAS:107-21-1 RTECS #:KW2975000 Fraction by Wt: 1.51% Other REC Limits:NONE RECOMMENDED OSHA PEL:100 PPM ACGIH TLV:50 PPM EP A Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:TEXANOL (ESTER ALCOHOL) CAS:25265-77-4 RTECS #:UF6000000 Fraction by Wt: 0.09% Other REC Limits:NONE RECOMMENDED OSHA PEL:100 PPM ACGIH TLV:100 PPM

Ingred Name:VOC: 62 GRAMS/LITER (LESS WATER) RTECS #:9999999VO Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chr onic:INHAL: PROLONGED INHAL IN CONFINED AREAS, MAY LEAD TO MUCOUS MEMBRANE IRRITATION, DIZZINESS, HEADACHE. SKIN CONTACT: IRRITATION. EYE CONTACT: IRRITATION. INGESTION: AMOUNTS INGESTED INCIDENTAL TO CONS UMER & INDUSTRIAL HANDLING NOT LIKELY TO CAUSE INJURY, HOWEVER, INGESTION OF LARGER AMOUNTS COULD CAUSE SERIOUS INJURY. Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH SAFE HANDLING INSTRUCTIONS.

====== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS DEVELOP, SEEK MEDICAL ATTENTION AT ONCE. SKIN: WASH OFF QUICKLY WITH PLENTY OF WATER, THEN SOAP & WATER. REMOVE & WASH CONTAM CLOTHING BEFORE REUSE. EYE: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS, FOR AT LEAST 15 MINUTES. OBTAIN EMERGENCY MEDICAL TREATMENT. INGESTION: IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

=================== Fire Fighting Measure

Flash Point Method:TCC

Extinguishing Media: FOAM, DRY CHEMICAL, WATER, OR WATER FOG Fire Fighting Procedures:WATER MAY BE USED TO COOL AND PROTECT ADJACENT CONTAINERS. Unusual Fire/Explosion Hazard: WILL NOT BURN. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT OR FIRE. Spill Release Procedures: COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILL MAY BE COLLECTED WITH ABSORBENT MATERIALS. Handling and Storage Precautions: AVOID TEMPERATURES BELOW 40F. KEEP FROM FREEZING. STORE CONTAINERS WITH LIDS TIGHTLY CLOSED AND APPROPRIATELY LABELED. Other Precautions: THIS PRODUCT CONTAINS NO MERCURY IN REPORTABLE QUANTITIES AS DEFINED BY OSHA AND EPA. Respiratory Protection: IF PERSONAL EXPOSURE C ANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/OSHA FOR PROTECTION AGAINST MATERIALS LI STED IN INGREDIENT SECTION. Ventilation:LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF EXPOSURE TO MATERIALS IN INGREDIENTS IS MAINTAINED BELOW PEL/TLV Protective Gloves: SEE GLOVE SUPPLIER Eye Protection: SAFETY GLASSES W/UNPERFORATED SIDESHIELD Other Protective Equipment: EYE WASH, SAFETY SHOWERS , GOGGLES, SAFETY GLASSES, IMPERVIOUS GLOVES. Work Hygienic Practices: KEEP WORK AREA CLEAN & FREE FROM SPILLS & LEAKS. ALWAYS WASH HANDS W/SOAP & WATER BEFORE HANDLING FOOD, DRINK, SMOKING. Supplemental Safety and Health Boiling Pt:B.P. Text:212F,100C Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C Vapor Pres:23.8 @ 20C Vapor Density:> AIR Spec Gravity:1.3733 pH:7.0 Viscosity:93 KU

Evaporation Rate & amp; Reference: SLOWER T

HAN ETHER Solubility in Water:INFINITE Appearance and Odor:THIXOTROPIC LIQUID WITH SLIGHT ODOR, COLOR OF TINT. Percent Volatiles by Volume:3.95

Stability Indicator/Materials to Avoid:YES OXIDIZERS AND/OR HYDROFLUORIC ACID Stability Condition to Avoid:ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENTS Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE Conditions to Avoid Polymerization:ELEVATED TEMPERATUR ES, CONTACT WITH OXIDIZING AGENTS

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE, AND FEDERAL REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be a ccurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.