

GENERAL SEALANTS, INC -- GS #424 MIL-S-11030E, TYPE III -- 8030-00-965-2438

=====
Product Identification
=====

Product ID:GS #424 MIL-S-11030E, TYPE III

MSDS Date:10/22/1990

FSC:8030

NIIN:00-965-2438

MSDS Number: BWPZL

=== Responsible Party ===

Company Name:GENERAL SEALANTS, INC

Address:300 S TURNBULL CANYON RD

City:CITY OF INDUSTRY

State:CA

ZIP:91745

Country:US

Info Phone Num:818-961-0211

Emerge

ncy Phone Num:818-961-0211

CAGE:53992

=== Contractor Identification ===

Company Name:GENERAL SEALANTS INC

Address:300 S TURNBULL CANYON RD

Box:3855

City:CITY OF INDUSTRY

State:CA

ZIP:91744

Country:US

Phone:818-961-0211

CAGE:53992

=====
Composition/Information on Ingredients
=====

Ingred Name:CHLORINATED PARAFFINS (THIS PRODUCT HAS NOT BEEN SHOWN TO
HAVE ADVERSE HEALTH EFFECTS)

CAS:68920-70-7

Other REC Limits:NONE RECOMMENDED

Ingred Name:GS #424 IS CONSIDERED NON-HAZARDOU

S, NON-COMBUSTIBLE AND
NON-EXPLOSIVE.
RTECS #:9999999ZZ
Other REC Limits:NONE RECOMMENDED

===== Fire Fighting Measures =====

Flash Point:800F,427C
Extinguishing Media:WATER, CARBON DIOXIDE
Fire Fighting Procedures:USE WATER SPRAY TO COOL FIRE EXPOSED SURFACES
AND TO PROTECT PERSONNEL. RESPIRATORY AND EYE PROTECTION REQUIRED.
Unusual Fire/Explosion Hazard:NON-EXPLOSIVE, MAY PRODUCE CARBON
MONOXIDE AND IRRITATING SMOKE.

===== Exposure Contr
ols/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:SOLID
Melt/Freeze Pt:M.P/F.P Text:230F,110C
Vapor Pres:SOLID
Vapor Density: