

MARTIN ELECTRONICS INC -- MK 132 MARINE FLARE SIGNAL, 6263352 -- 1370-01-252-0317

=====
Product Identification
=====

Product ID:MK 132 MARINE FLARE SIGNAL, 6263352

MSDS Date:10/31/1994

FSC:1370

NIIN:01-252-0317

MSDS Number: BWRXY

=== Responsible Party ===

Company Name:MARTIN ELECTRONICS INC

Address:ROUTE 1 BOX 700

City:PERRY

State:FL

ZIP:32347

Country:US

Info Phone Num:904-584-2634

Emergency Ph

one Num:904-584-2634

CAGE:4A902

=== Contractor Identification ===

Company Name:MARTIN ELECTRONICS INC

Address:ROUTE 1 BOX 700

Box:City:PERRY

State:FL

ZIP:32347

Country:US

Phone:904-584-2634

CAGE:4A902

=====
Composition/Information on Ingredients
=====

Ingred Name:MAGNESIUM

CAS:7439-95-4

RTECS #:OM2100000

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:STRONTIUM NITRATE

CAS:10042-76-9

RTECS #:WK9800000

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:PERCHLORIC ACID, POTASSIUM SALT (1:1);

(POTASSIUM
PERCHLORATE)
CAS:7778-74-7
RTECS #:SC9700000
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:ETHYLENE, CHLORO-, POLYMER; (POLYVINYL CHLORIDE)
CAS:9002-86-2
RTECS #:KV0350000
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:ASPHALT; (ASPHALTUM)
CAS:8052-42-4
RTECS #:CI9900000
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:LEAD TRINITRORESORCINATE; (LEAD STYPHNATE) MFR CAS #
15245-44-0
CAS:15345-44-0
RTECS #:OG6425000
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:NAPHTHACENE; (TETRACENE)
CAS:92-24-0
RTECS #:QI7605000
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:ANTIMONY TRISULFIDE; (ANTIMONY SULFIDE)
CAS:1345-04-6
RTECS #:CC9450000
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:BARIUM (II) NITRATE (1:2); (BARIUM NITRATE) MFR CAS #
13465-94-6
CAS:1022-31-8
RTECS #:CQ9625000
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:ZIRCONIUM
CAS:7440-67-7
RTECS #:ZH7070000
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3; 10 STEL

Ingred Name:LEAD DIOXIDE; (LEAD OXIDE)
CAS:1309-60-0
RTECS #:OG0700000
OSHA PEL:N/K
ACGIH TLV:

N/K

Ingred Name:METHANE, DICHLORO-; (METHYLENE CHLORIDE) (SARA 313)
(CERCLA)
CAS:75-09-2
RTECS #:PA8050000
OSHA PEL:500 PPM
ACGIH TLV:50 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:POLY-2-METHYL-5-VINYL TETRAZOLI(PMVT)
OSHA PEL:500 PPM
ACGIH TLV:50 PPM

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES
OSHA:NO
Health Hazards Acute and Chronic:CHLOROCARBON MATLS HAVE PRDCED SENSIT
OF MYOCARDIUM TO EPINEPHRINE IN LAB ANIMALS & COULD HAVE SIMILAR
EFT IN HUMANS. ADRENOMIMETICS (EG, EPINEPHRINE) MAY BE
CONTRA-INDICATED EXCEPT FOR LIFE-SUSTAININ G USES IN HUMANS
ACUTELY/CHRONICALLY EXPOSED TO CHLOROCARBONS . INHAL/SKIN/EYES:
MINOR IRRIT. (EFTS OF OVEREXP)
Explanation of Carcinogenicity:METHYLENE CHLORIDE:IARC MONO SUPP, V7,
PG 194, 1987:GRP 2B. NTP 7TH ANNUAL RPT ON CARCINS,
1994:ANTIC
CARCIN. (SUPDAT)
Effects of Overexposure:HLTH HAZ: CHRONIC: LEAD APPEARS ON NAVY LIST OF
OCCUP CHEM REPRO HAZS. SEEK CONSULTATION FROM APPROP HLTH
PROFESSIONALS CONCERNING LATEST HAZ LIST INFO & SAFE HNDLG & EXPOS
INFO . INHAL: MAY CAU SE DAMAGE TO BLOOD & CENTRAL NERVOUS SYSTEM.
POSS CARCIN WHEN EXPOS TO DECOMP PRODS AT HIGH CONCS. SKIN: MINOR
IRRIT.
Medical Cond Aggravated by Exposure:NONE KNOWN OR REPORTED.

===== First Aid Measures =====

=====

First Aid:INGEST: CALL MD IMMEDIATELY . SKIN: FLUSH WITH COPIOUS AMOUNTS OF WATER. CALL MD . FOR BURNS USE STANDARD FIRST AID METHODS. EYES: IMMEDIATELY FLUSH W/LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES, OCCASIONALLY LIFTING UPPER &LOWER EYELIDS. IF EYE IRRITATION DEVELOPS, CALL MD. INHAL: REMOVE TO FRESH AIR. CONSULT MD IF IRRITATION OCCURS.

===== Fire Fighting Measures =====

Extinguishing Media:WATER SPRAY. APPLY BY MECH MEANS ONLY. FIGHT ALL FIRES FROM REMOTE & EXPLO RESISTANT SITE. EVACUATE ALL NON-ESSNTL PERS.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED PRESSURE DEMAND SCBA AND FULL PROTECTIVE EQUIPMENT . USE WATER TO COOL CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:THERMAL DECOMPOSITION PRODUCTS MAY INCLUDE HCL AND PHOSGENE .

===== Accidental Release Measures =====

Spill Release Procedures:CONSULT FED, STATE & LOC REGS FOR ANY

RPT/NOTIFICATION REQS. PROD MAY REPRESENT EXPLO HAZ. REMOVE ALL SOURCES OF IGNIT. STOP SOURCE AS SOON AS POSS & NOTIFY APPROP PERS. MATL SPILL SHOULD ONLY BE ADDR ESSED BY PERS EXPERIENCED IN HNDLG (SUPDAT)

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY PLACE AWAY FROM ALL SOURCES OF IGNITION. DO NOT STORE AT TEMPERATURE ABOVE 150F (65.5C). DO NOT SUBJECT TO MECHANICAL SHOCK.

Other Precautions:NO SMKNG IN AREA OF USE. DO NOT USE IN GEN VICIN OF ARC WELDING, OPEN FLAMES/HOT SURFS. HEAT &/OR UV RADIA MAY CAUSE FORM OF HCL &/OR PHOSGENE . SHELF LIFE INDEFINITE @ 50-90F & 35% RELATIVE HUM IDITY. PACKAGE ONLY IN DOT APPRVD CNTNR.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN . RESPIRATORY PROTECTION NOT NORMALLY NEEDED

AVOID PROLONGED BREATHING OF DECOMPOSITION PRODUCTS.
Ventilation:USE ONLY IN OPEN AREAS WITH ADEQUATE VENTILATION.
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:ANSI APPRVD CHEM WORKERS GOGGS .
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health

EXPLAN OF CARCIN:ANIMAL:LUNG, LIVER,SALIVARY, MAMMARY GLAND(TUMOR).

SPILL PROC:ENERGETIC MATL. USE NON-SPK TOOLS & AVOID SUBJECT MATL TO ME

CH SHOCK. IF ADDNL MATL MANAGEMENT INFO REQD, CNTCT MFR AT 90 4-584-2634. IN CASE OF FIRE, USE NORM FIRE-FIGHT EQUIP. USE NIOSH/MSHA APPRVD SCBA IF SMOKE FROM INCIDENT IS BRTHG HAZ.

===== Physical/Chemical Properties =====

Decomp Temp:Decomp Text:>180F,>82C

Appearance and Odor:6" LONG X 2" DIAMETER MOLDED PLASTIC HOUSING W/REMOVABLE PLASTIC CAP.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:Y

ES

NOT APPLICABLE.

Stability Condition to Avoid:TEMPERATURES ABOVE 82C. OPEN FLAMES.

Hazardous Decomposition Products:HCL, PHOSGENE . COMPOUNDS OF LEAD, BARIUM, CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL OF MATERIAL, DECOMPOSITION PRODUCTS AND EMPTY CONTAINERS IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information

is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.