

FUEL QUALITY SERVICES, INC. -- LTSA-15 -- 6850-01-167-4789

=====
===== Product Identification =====

Product ID:LTSA-15
MSDS Date:12/19/1990
FSC:6850
NIIN:01-167-4789
MSDS Number: BWSHK
=== Responsible Party ===
Company Name:FUEL QUALITY SERVICES, INC.
Address:1754 GREEN ROAD
Box:317
City:BUFORD
State:GA
ZIP:30518
Country:US
Info Phone Num:404-945-7139
Emergency Phone Num:404-945-7139
Preparer's Name:
R.V.DAUM
CAGE:40161
=== Contractor Identification ===
Company Name:FUEL QUALITY SERVICES, INC.
Address:4584 CANTRELL ROAD
Box:1380
City:FLOWERY BRANCH
State:GA
ZIP:30542
Country:US
Phone:(800) 827-9790 - (770) 967-9790
CAGE:40161

=====
===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC PETROLEUM SOLVENT
CAS:8008-20-6
RTECS #:OA5500000
Fraction by Wt: 50 - 58%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 AS OIL MIST
ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred N

ame:TRADE SECRET COMPONENT/NJ TRADE SECRET

Fraction by Wt: 12.6-21%

Other REC Limits:NONE RECOMMENDED

Ingred Name:STYRENE MONOMER (SARA 313)

CAS:100-42-5

RTECS #:WL3675000

Fraction by Wt: 0.84%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:S,50PPM/100STEL;9596

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:N,N-DIMETHYLCYCLOHEXYLAMINE

CAS:98-94-2

RTECS #:GX1198000

Fraction by Wt: 10.5-14%

Other REC Limits:NONE RECOMMENDED

Ingred Name:N,N'DISALYCYLIDENE-1,2 PROPANE DIAMINE

CAS:94-91-7

RTECS #:GP3130000

Fraction by Wt: 0.8-2.1%

Other REC Limits:NONE RECOMMENDED

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 0.2-.63%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL;9596

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA 313)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 0.084%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/125STEL;

9596
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingrid Name:3,5-XYLENOL/MIXED CRESOLS AND XYLENOLS

CAS:108-68-9

RTECS #:ZE6475000

Fraction by Wt: 200 MG/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NONSPECIFIC DISCOMFORT, SUCH AS
NAUSEA, HEADACHE, OR WEAKNESS; OR SKIN IRRITATION WITH DISCOMFORT
OR RASH, ABNORMAL KIDNEY AND LIVER FUNCTIONS, TEMPORARY LUNG
IRRITATION EFFECTS WITH COUGH,
DISCOMFORT , DIFFICULTY BREATHING,
OR SHORTNESS OFBREATH

Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure:SKIN BURNS OR ULCERATION. EVIDENCE SUGGESTS
THAT KEROSENE CAN PERMEATE THE SKIN.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING
DISEASES OF THE LIVER MAY HAVE INCREASED SUSCEPTIBILITY TO THE
TOXICITY OF EXCESSIVE EXPOSURE,

===== First Aid Measures =====

First Aid:EYE: IMMEDIATELY
FLUSH WITH PLENTY OF WATER FOR AT LEAST 15
MINUTES. CALL A PHYSICIAN. SKIN: IMMEDIATE FLUSH WITH PLENTY OF
WATER FOR 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING. CALL A
PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS
DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN. INGESTION: DO NOT INDUCE
VOMITING. IMMEDIATELY GIVE TWO GLASSES OF WATER IF CONSCIOUS. CALL
A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:109F,43C

Extinguishing Media:

WATER SPRAY, CHEMICAL FOAM, DRY CHEMICAL, CARBON
DIOXIDE

Fire Fighting Procedures:EVACUATE PERSONNEL TO A SAFE AREA. WEAR
SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID

===== Accidental Release Measures =====

Spill Release Procedures:USE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT
BEFORE PROCEEDING WITH CLEAN-UP. SOAK UP WITH SAWDUST, SAND, OIL
DRY OR OTHER ABSORBENT. THIS MATERIAL IS AN IGNITABLE,

CORROSIVE,
REACTIVE. A RELEASE OF 100 LBS MAY TRIGGER REPORTING OF
CERCLASECT. 103.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN WELL VENTILATED AREA. KEEP
CONTAINER TIGHTLY CLOSED. STORE IN ACCORDANCE WITH NATIONAL FIRE
PROTECTION ASSN. REGULATIONS.

Other Precautions:THIS PRODUCT CONTAINS TRACE QUANTITIES OF BENEZENE.
DO NOT BREATHE VAPOR OR MIST. DO NOT GET
IN EYES. DO NOT GET ON
SKIN. DO NOT GET ON CLOTHING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE THERE IS POTENTIAL FOR AIRBORNE EXPOSURES
IN EXCESS OF APPLICABLE LIMITS, WEAR NIOSH/MSHA APPROVED
RESPIRATORY PROTECTION.

Ventilation:USE ONLY WITH ADEQUATE VENTILATION.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:APRON, BOOTS, HOOD AND JACKET.

Work Hygienic Practices

:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

DO NOT CONSUME FOOD, DRINK OR TOBACCO IN THE AREA WHERE THEY BECOME
CONTAMINATED WITH THIS MATERIAL. KEEP CONTAINER TIGHTLY CLOSED.

=====
===== Physical/Chemical Properties =====

HCC:F6

Boiling Pt:B.P. Text:351F,177C

Spec Gravity:0.90

Solubility in Water:IMMISCIBLE

Appearance and Odor:AMINES ODOR, LIQUID FORM, AMBER COLOR.

=====
===== Stability and Reactivity Data =====

Stability Ind

icator/Materials to Avoid: YES

NONE REASONABLY FORESEEABLE

Stability Condition to Avoid: NONE REASONABLY FORESEEABLE

Hazardous Decomposition Products: DECOMPOSITION WILL NOT OCCUR

===== Disposal Considerations =====

Waste Disposal Methods: TREATMENT, STORAGE, TRANSPORTATION AND DISPOSAL
MUST BE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

THIS MATERIAL MAY BE A RCRA REGULATED HAZARDOUS WASTE UPON DISPOSAL
DUE TO THE IGNITABILITY CHARACTERIS
TIC.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular s
ituation.