View NSN Online: https://aerobasegroup.com/nsn/6850-01-159-4844

WACKER SILICONES CORP -- RTV SILICONE RUBBER T 330 -- 6850-01-159-4844

Product ID:RTV SILICONE RUBBER T 330 MSDS Date:09/11/1996 FSC:6850 NIIN:01-159-4844 MSDS Number: BWSWB === Responsible Party === Company Name: WACKER SILICONES CORP Address:3301 SUTTON RD City:ADRIAN State:MI ZIP:49221 Country:US Info Phone Num:517-264-8500 Emergency Phone Num:517-264-8500/800 -424-9300(CHEMTREC) CAGE:0DF77 === Contractor Identification === **Company Name: HUELSMAN JACK Box:UNKNOW** CAGE:0GH66 Company Name:NETEX INDUSTRIES(FORMER NORTHEAST TEXAS IND) Address:1700 NORTH EDWARDS STREET Box:City:MOUNT PLEASANT State:TX ZIP:75455 Country:US Phone:903-577-0388 CAGE:0WAG0 Company Name: PENN DETROIT DIESEL ALLISON INC Address:SIPE ROAD Box:RD 1 **City:YORK HAVEN** State:PA ZIP:17370-9785 Country:US Phone:717-938-5141 CAGE:62860 Company Name: TRIMAN INDUSTRIES INC Address:420 COMMERCE L

N SUITE 8 Box:City:WEST BERLIN State:NJ ZIP:08091 Country:US Phone:856-767-7945 /FAX: 856-767-7154 CAGE:0ZBE8 Company Name:WACKER SILICONES CORP Address:3301 SUTTON RD Box:City:ADRIAN State:MI ZIP:49221 Country:US Phone:517-264-8500 CAGE:0DF77

Ingred Name:POLY (DIMETHYLSILOXANE) CAS:63148-62-9 RTECS #:JJ6484500 Other REC Limits:NONE RECOMMENDED

Ingred Name:CATALYST Other REC Limits:NONE RECOMMENDED

Ingred Name:METHYL ETHYL KETOXIME (HYDROLYSIS BY-PRODUCT) CAS:96-29-7 RTECS #:EL9275000 Other REC Limits:NONE RECOMMENDED

Ingred Name:CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 Other REC Limits:NONE RECOMMENDED OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9596

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN. Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY

TRACT. ACUTE- CAUSES SEVERE EYE IRRITATION & BURNS. SKIN CONTACT CAUSES IRRITATION. MAY BE ABSORBED THROUGH SKIN & MAY CAUSE SENSITIZATION. INHALATION OF VAPOR/MIS T MAY CAUSE RESPIRATORY IRRITATION. INGESTION IS NOT EXPECTED IN INDUSTRIAL USE. CHRONIC-MAY CAUSE SKIN BURNS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SEVERE IRRITATION, DISCOMFORT, TEARING, REDNESS, BURNS, PAIN, SKIN SENSITIZATION

======= Fi

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:IF CONSCIOUS, RINSE MOUTH WITH COLD WAT ER & INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY. IF UNCONSCIOUS & VOMITING, TURN PERSON ON HIS SIDE TO AVOID CHOKING. ALLOW VICTIM TO DRINK AS MUCH COLD WATER AS DESIRED.

================== Fire Fighting Measures

Flash Point:NONE
Lower Limits:NOT RELEVANT
Upper Limits:NOT RELEVANT
Extinguishing Media:CARBON DIOXIDE, SAND, FOAM/DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL.
Fire Fighting Procedures:DO NOT ENTER ANY ENCLOSED OR CONFINED AREA WITHOUT PROPER PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:PRODUCT WILL BURN WITH A LAZY SMOLDERING TYPE FLAME. MAY FORM TOXIC VAPORS.

==

Spill Release Procedures:REMOVE SPILL WITH ABSORBENT MATERIAL SUCH AS SAND, CLAY, VERMICULITE. TRANSFER INTO CONTAINERS FOR DISPOSAL OR SALVAGE. FLOOR MAY BE SLIPPERY. WASH SPILL SITE WITH MINERAL SPIRITS TO REMOVE RESIDUAL C ONTAMINATION. PROVIDE VENTILATION. REMOVE FLAMES. Neutralizing Agent:NOT RELEVANT

Handling and Storage Precautions:STORE

IN DRY, CLEAN, VENTILATED PLACE

AWAY FROM INCOMPATIBLE MATERIALS. KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINER TIGHTLY CLOSED EVEN WHEN EMPTY.

Other Precautions: AVOID CONTACT WITH EYES AND SKIN. WASH THOROUGHLY AFTER HANDLING. LAUNDER CLOTHING BEFORE REUSE. DO NOT TAKE INTERNALLY. DO NOT EAT, DRINK OR SMOKE IN THE WORK AREA. CAUTION! THIS MATERIAL RELEASES ME THYLETHYLKETOXIME UPON HYDROLYSIS.

======= Exposure Controls/Personal Protection ==========

Respiratory

Protection:NONE REQUIRED WHERE ADEQUATE VENTILATION CONDITIONS EXIST. IF AIRBORNE CONCENTRATION IS HIGH, WEAR A NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR. Ventilation:ADEQUATE Protective Gloves:LATEX OR RUBBER Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED. Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. Supplemental S afety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PNI A, SAME NSN.

HCC:T6 NRC/State Lic Num:NOT RELEVANT Spec Gravity:1.33 Viscosity:NOT RELEVANT Evaporation Rate & amp; Reference:NOT RELEVANT Solubility in Water:NONE Appearance and Odor:BLACK PASTE - OXIME ODOR Percent Volatiles by Volume:4.2

Stability Indicator/Materials to Avoid:YES ACIDS, W

ATER, IRON Stability Condition to Avoid:AIR AND MOISTURE Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN, SILICON DIOXIDE, METHYL ETHYL KETONE, FORMALDEHYDE, POSSIBLY MEKO Conditions to Avoid Polymerization:STRONG ACIDS, HEAT IN PRESENCE OF

IRON

Waste Disposal Methods:DISPOSE OF IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO N

OT

FLUSH TO SEWER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to t heir

particular situation.