

CONOCO INC -- CONOSOL C-200 -- 6850-01-377-1808

=====
Product Identification
=====

Product ID:CONOSOL C-200

MSDS Date:03/03/1992

FSC:6850

NIIN:01-377-1808

MSDS Number: BWZJW

=== Responsible Party ===

Company Name:CONOCO INC

Address:600 N DAIRY ASHFORD RD RM 3012

Box:4784

City:HOUSTON

State:TX

ZIP:77210-4784

Country:US

Info Phone Num:713-293-5550/-1000

Emergency Phone Num:800-441-3637/800-424-9300

(CHEMTREC)

Preparer's Name:SAFETY, HEALTH & ENV.

CAGE:15445

=== Contractor Identification ===

Company Name:CONOCO INC

Address:600 N DAIRY ASHFORD RD RM 3012

Box:4784

City:HOUSTON

State:TX

ZIP:77210-4784

Country:US

Phone:800-441-3637/800-424-9300(CHEMTREC)

CAGE:15445

Company Name:EMULTEC INDUSTRIAL PRODUCTS INC

Address:1150 HAYDEN DR SUITE 100

Box:City:CHARROLLTON

State:TX

ZIP:75006

Country:US

Phone:972-417-1288

CAGE:0WA27

=====
Composition/Information on Ingredients
=====

Ing

red Name:HYDROTREATED MIDDLE PETROLEUM DISTILLATE

CAS:64742-46-7

RTECS #:JN9379645

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION- EXTREME EXPOSURE OR
ASPIRATION INTO THE LUNGS MAY CAUSE PNEUMONIA. SKIN- IRRITATION.
EYES- IRRITATION.

Effects of Overexposure:OV

EREXPOSURE MAY CAUSE WEAKNESS, HEADACHE,
NAUSEA, CONFUSION, BLURRED VISION, DROWSINESS AND OTHER NERVOUS
SYSTEM EFFECTS. GREATER EXPOSURE MAY CAUSE DIZZINESS, SLURRED
SPEECH, FLUSHED FACE, UNCONSCIOUSNESS OR CONVULSIONS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALATION- REMOVE TO FRESH AIR. ASSIST WITH BREATHING
SUPPORT MEASURES, IF NEEDED. SKIN- FLUSH WITH WATER AFTER
CONTACT.

WASH CONTAMINATED CLOTHING BEFORE REUSE. EYES- IMMEDIATELY FLUSH
WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. INGESTION- DO NOT
INDUCE VOMITING. IF CONSCIOUS, IMMEDIATELY GIVE TWO GLASSES OF
WATER. CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:200-210F

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:WATER SPRAY, FOAM, DRY CHEMICAL, CARBON DIOXIDE.

Fire Fighting Procedures:WATER OR FOAM

MAY CAUSE FROTHING. USE WATER TO
KEEP FIRE-EXPOSED CONTAINERS COOL. DO NOT ENTER ENCLOSED OR
CONFINED SPACE WITHOUT PROPER PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard:WATER SPRAY MAY BE USED TO FLUSH SPILLS
AWAY FROM EXPOSURES. PRODUCTS OF COMBUSTION MAY INCLUDE TOXIC
MATERIALS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCE OF HEAT, SPARKS, FLAME, IMPACT,
FRICTION OR ELECTRICITY. DIKE SPILL. PREVENT LIQUI

D FROM ENTERING

SEWERS, WATERWAYS OR LOW AREAS. RECOVER FREE LIQUID FOR REUSE OR RECLAMATION. SOAK UP WITH SAWDUST, SAND, OIL DRY OR OTHER ABSORBENT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN ACCORDANCE WITH NATIONAL FIRE PROTECTION ASSOCIATION REGULATIONS.

Other Precautions:NONE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELECT APPROPRIATE NIOSH-APPROVED RESPIRATORY

PROTECTION WHERE NECESSARY TO MAINTAIN EXPOSURES BELOW THE ACCEPTABLE LIMITS. PROPER RESPIRATORY SELECTION SHOULD BE DETERMINED BY ADEQUATE TRAINED PERSONNEL AND BASED ON THE CONTAMINANTS, ETC.

Ventilation:GENERAL MECHANICAL VENTILATION NORMALLY ADEQUATE.

Protective Gloves:IMPERVIOUS GLOVES SHOULD BE WORN.

Eye Protection:CHEMICAL SPLASH GOGGLES OR FACE SHIELD.

Other Protective Equipment:CLOTHING TO MINIMIZE SKIN EXPOSURE.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

WASH CLOTHING

AFTER USE.

Supplemental Safety and Health

NONE

=====
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:430-530F

Vapor Pres:0.4

Vapor Density:6.2

Spec Gravity:0.82-0.83

Solubility in Water:INSOLUBLE

Appearance and Odor:CLEAR, COLORLESS LIQUID.

Percent Volatiles by Volume:NIL

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS.

Stability Condition to Avo

id:EXCESSIVE HEAT AND FLAME.

Hazardous Decomposition Products:CARBON DIOXIDE AND POSSIBLY CARBON MONOXIDE.

Conditions to Avoid Polymerization:POLYMERIZATION WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:TREATMENT, STORAGE, TRANSPORTATION AND DISPOSAL MUST BE IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE/PROVINCIAL, AND LOCAL REGULATIONS. RECOVER NONUSABLE FREE LIQUID AND DISPOSE OF IN AN APPROVED AND PERMITTED INCINERATOR.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.