

ELF ATOCHEM NORTH AMERICA INC -- FORANE 134A -- 6830-01-370-6207

=====
Product Identification
=====

Product ID:FORANE 134A

MSDS Date:10/13/1992

FSC:6830

NIIN:01-370-6207

MSDS Number: BWZNV

=== Responsible Party ===

Company Name:ELF ATOCHEM NORTH AMERICA INC

Address:THREE PARKWAY 908

City:PHILADELPHIA

State:PA

ZIP:19102-1321

Country:US

Info Phone Num:215-587-7513/7779

Emergency Phone Num:215-587

-7513/7779

CAGE:86460

=== Contractor Identification ===

Company Name:ELF ATOCHEM NORTH AMERICA INC

Address:2000 MARKET STREET

Box:City:PHILADELPHIA

State:PA

ZIP:19103-3222

Country:US

Phone:800-245-5858

CAGE:86460

=====
Composition/Information on Ingredients
=====

Ingred Name:1,1,1,2-TETRAFLUOROETHANE (R134A)

CAS:811-97-2

Fraction by Wt: 100%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports o

f Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: VERY SLIGHT IRRITANT. RAPID VOLATILIZATION OF LIQUID MAY CAUSE FROSTBITE. SKIN: SLIGHT IRRITANT, CONTACT MAY CAUSE FROSTBITE. INHALATION: CONCENTRATED VAPORS CAN CAUSE RESPIRATORY DEPRESSION, INCREASES SENSITIVITY OF THE HEART TO ADRENALINE, DEPRESSION OF CARDIAC FUNCTION, DEATH DUE TO ASPHYXIATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITANT, DROWSINESS, UNCONSCIOUSNESS, RAPID HEATBEAT, IRREGULAR HEARTBEAT.

Medical Cond Aggravated by Exposure:PREEXISTING HEART DISEASE.

=====
===== First Aid Measures =====

First Aid:SKIN: IF FROSTBITTEN, WARM SLOWLY W/WATER. FLUSH W/PLENTY OF WATER. EYES: FLUSH W/PLENTY OF CLEAN WATER FOR 15 MINS. INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE CPR. IF BREATHING IS DIFFICULT, GIVE OXYGEN. INGESTION: NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE

Extinguishing Media:USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR SCBA. KEEP CONTAINERS COOL.

Unusual Fire/Explosion Hazard:CONTAINER MAY EXPLODE IF HEATED DUE TO RESULTING PRESSURE RISE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE/EXTINGUISH IGNITION/COMBUSTION SOURCES.

EVACUATE ENCLOSED SPACES UNTIL GAS IS DISPERSED. KEEP UPWIND. STOP LEAK IF POSSIBLE W/OUT RISK. DISPERSE GAS W/FLOOR-LEVEL FORCED-AIR VENTILATION. EXHAUST VAPORS OUTDOORS. REMOVE FLAMES/HEAT

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED. KEEP AWAY FROM IGNITION SOURCES. STORE IN TIGHTLY CLOSED CONTAINERS. EMPTY CONTAINERS CONTAIN HAZARDOUS RESIDUE.

Other Precautions:DON'T DROP, REUSE/REFILL CONTAINERS

TAINER. DON'T CUT, GRIND/
WELD ON/NEAR CONTAINER. DON'T GET IN EYES, ON SKIN/CLOTHING. DON'T
BREATHE VAPOR, MIST/GAS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN INADEQUATELY VENTILATED AREAS, A NIOSH/MSHA
APPROVED (TC-18C) SUPPLIED AIR RESPIRATOR/SCBA IS RESQUIRED.

Ventilation:CHECK AIR FOR CONTAMINANT & FOR OXYGEN DEFICIENCY. USE
LOCAL EXHAUST SYSTEM IF VENTILATION IS INADEQUATE.

Protective Gloves:SYNTHETIC RUBBER/NEOPRENE

Eye

Protection:GOGGLES

Other Protective Equipment:LIQUID GLOVES ARE RECOMMENDED FOR PROTECTION
FROM COLD.

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE
REUSE. DESTROY CONTAMINATED SHOES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-16F,-26C

Melt/Freeze Pt:M.P/F.P Text:-150F,-101C

Vapor Pres:96.16

Vapor Density:3.52

Spec Gravity:1.21

Solubility in Water:NEGLIGIBLE

Appearance and Odor:C

LEAR, COLORLESS LIQUIFIED GAS W/FAINT ETHEREAL
ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ALKALIE/ALKALINE EARTH METALS, ALUMINUM, MAGNESIUM/ZINC & STRONG
OXIDIZERS

Stability Condition to Avoid:FLAMES, HEATING ELEMENTS, TEMP >800F, HOT
METAL SURFACES, COMBUSTION ENGINES & OTHER IGNITION SOURCES

Hazardous Decomposition Products:HYDROGEN FLUORIDE, CO, CO2,
HYDROCHLORIC

ACID

===== Disposal Considerations =====

Waste Disposal Methods:RECYCLE/RECLAIM IF POSSIBLE. RECLAIMED MATERIAL MAY BE INCINERATED BUT TOXIC & CORROSIVE COMBUSTION PRODUCTS MUST BE HANDLED APPROPRIATELY. DISPOSE OF IAW/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.