View NSN Online: https://aerobasegroup.co.il/nsn/6750-01-318-9969

FUJI NDT SYSTEMS -- FUJI AUDEL INDUSTRIAL X DEVELOPER, ITEM PT-D #1806

6750-01-318-9969

============= Product Identification ================

Product ID:FUJI AUDEL INDUSTRIAL X DEVELOPER, ITEM PT-D #1806

MSDS Date:05/01/1996

FSC:6750

NIIN:01-318-9969

MSDS Number: BXFZH === Responsible Party ===

Company Name: FUJI NDT SYSTEMS

Address:1055 STEVENSON CRT

City:ROSELLE

State:IL

ZIP:60172-2300

Country:US

Info Phone N

um:770-448-0250

Emergency Phone Num:770-448-0250

CAGE:NO425

=== Contractor Identification ===

Company Name: ALLIED PHOTO PRODUCT CO, SUB OF ALLIED PRODUCT CORP

Address:5440-A OAKBROOK PKY

Box:City:NORCROSS

State:GA

ZIP:30093-2251

Country:US

Phone:770-448-0250

CAGE:1CG79

Company Name: FUJI MEDICAL SYSTEMS INC FUJI NDT SYSTEMS DIV

Address:90 VIADUCT RD

City:STAMFORD

State:CT ZIP:06907 Country:US

Phone:203-353-0300

CAGE:0CSD2

Company Name: FUJI NDT SYSTEMSDUCTS CO INC

Address: 1055 STEVENSON CRTY

City:R

OSELLE State:IL ZIP:60172-2300 Country:US Phone:770-448-0250 CAGE:NO425 ======= Composition/Information on Ingredients ======== Ingred Name: DIETHYLENE GLYCOL CAS:111-46-6 RTECS #: ID5950000 Fraction by Wt: >99% Other REC Limits: NONE RECOMMENDED LD50 LC50 Mixture:LD50 ORAL RAT HAS NOT BEEN ESTABLISHED Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Hea Ith Hazards Acute and Chronic:INHALATION: VAPOR MAY CAUSE IRRITATION TO NOSE AND THROAT. EYES: VAPOR MAY CAUSE IRRITATION. CONTACT CAUSES IRRITATION. SKIN: REPEATED AND PROLONGED CONTACT MAY CAUSE IRRITATION. INGESTION: DO NOT TAK E INTERNALLY. **Explanation of Carcinogenicity:NONE** Effects of Overexposure: INGESTION: SWALLOWING MAY CAUSE

GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA, CENTRAL NERVOUS DEPRESSION AND KIDNEY DAMAGE WHICH MAY BE FATAL.

Medical Cond Aggravat

ed by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:IF ON SKIN-THOROUGHLY WASH EXPOSED AREA WITH SOAP & WATER. IF IN EYE-IMMEDIATELY FLUSH WAITH WATER, LIFTING UPPER & LOWER LIDS, GET MEDICAL ATTENTION. IF SWALLOWED-IMMEDIATELY DRINK 2 GLASSES OF WATER AND INDUCE VOMITING BY GIVING IPECAC SYRUP OR STICKING FINGER AT BACK OF THROAT, GET MEDICAL ATTENTION IMMEDIATELY, IF BREATHED-REMOVE INDIVIDUAL TO F

RESH AIR.
======================================
Flash Point:NONE
Extinguishing Media: USE METHOD APPROPIATE FOR SURROUNDING FIRE.RBON DIOXIDE.
Fire Fighting Procedures: USE PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN & EYES.
Unusual Fire/Explosion Hazard:WHEN HEATED TO DECOMPOSITION, IT CAN EMIT ACRID SMOKE AND FUMES. WILL PRODUCE PHOSPHORUS, CARBON DIOXIDE AND POSSIBLY CARBON MONOXIDE.
======================================
Spill Release Procedures:WEAR PROTECTIVE CLOTHING. NEUTRALIZE WITH SODIUM BICARBONATE. IF FEDERAL, STATE AND LOCAL LAWS PERMIT, FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER. Neutralizing Agent:SODIUM BICARBONATE
======================================
Handling and Storage Precautions:DON'T STORE OR CONSUME FOOD, DRINK, TOBACCO IN SURROUNDING AREA. WASH THOROUGHLY AFTER USE. Other Precautions:WASH THOROUGHLY AFTER USE.
====== Exposure C
ontrols/Personal Protection ========
Respiratory Protection:SHOULD NOT BE NECESSARY UNDER NORMAL CONDITIONS. IF EXPOSED TO VAPORS THAT EXCEED TLV OR PEL, WEAR AN APPROVED VAPOR RESPIRATOR.
Ventilation: GOOD LOCAL MECHANICAL VENTILATION SHOULD BE SUFFICIENT. Protective Gloves: IMPERVIOUS GLOVES.
Eye Protection:WEAR PROTECTIVE GOGGLES. Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT. EYE WASH FACILITIES IN VINCINITY OF USE.
Work Hygienic Practices:WASH THOROUGHLY A FTER USE.
Supplemental Safety and Health KEY1;C3.
========== Physical/Chemical Properties ============
HCC:C2 Boiling Pt:>100.C, 212.F

Vapor Pres: