

FARWEST PAINT MFG CO -- ALKYD SPAR VARNISH -- 8010-00-160-5852

=====
Product Identification
=====

Product ID:ALKYD SPAR VARNISH

MSDS Date:02/09/1989

FSC:8010

NIIN:00-160-5852

MSDS Number: BXGXM

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Info Phone Num:206-244-8844

Emergency Phone Num:206-941-1619

CAGE:6F266

=== Cont

actor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====
Composition/Information on Ingredients
=====

Ingred Name:PARAFFINS (INC. NAPHTHENES)

CAS:64742-47-8

Fraction by Wt: 2.98%

Other REC Limits:NONE RECOMMENDED

ACGIH TLV:70 PPM

Ingred Name:AROMATICS

CAS:64742-95-6

Fraction by Wt: 5.79%

Other REC Limits:NONE RECOMMENDED

ACGIH TLV:70 PPM

Ingred Name:MI

NERAL SPIRITS 350
CAS:8032-32-4
RTECS #:OI6180000
Fraction by Wt: 35.37%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM

Ingred Name:VOC: 409 GRAMS/LITER (LESS WATER)
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:104F,40C
Lower Limits:0.9
Upper Limits:6.1
Extinguishing Media:FOAM,DRY CHEMICAL,CO2,WATER FOG. USE CLASS B
EXTINGUISHER. WATER UNSUITABLE EXTINGUISH
ING MEDIUM,USE TO COOL
CONTAINERS.
Fire Fighting Procedures:FIREFIGHTERS & OTHERS EXPOSED TO VAPORS OR
COMBUSTION PRODUCTS SHOULD WEAR SCBA. EVACUATE AREA OF UNPROTECTED
PERSONNEL. WEAR PROTECTIVE CLOTHING.
Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN
AIR & MAY BE IGNITED BY SPARKS, PILOT LIGHTS, ETC. CLOSED
CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:307 TO 394F
Vapor Pres:7 @ 20C
Vapor Density:> AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:NIL
Appearance and Odor:CLEAR LIQUID WITH MILD, SWEET AROMATIC ODOR
Percent Volatiles by Volume:50.69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH STRONG OXIDANTS, ACIDS, BASES AND EP

OXY HARDENERS

UNDER UNCONTROLLED CONDITIONS.

Stability Condition to Avoid: HEAT, SPARKS, & OPEN FLAMES. IF PRODUCT CONTAINS ALUMINUM, MOISTURE IN CLOSED CONTAINERS WILL GENERATE HYDROGEN GAS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all lia

bility for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.