

Product ID:0968500 GP-X WHITE MARKER MSDS Date:11/20/1993 FSC:7520 NIIN:00-558-1487 MSDS Number: BXNXJ === Responsible Party === Company Name: DIAGRAPH CORP Address: RT 148 AND OGDEN RD Box:520 **City:HERRIN** State:IL ZIP:62948-5000 Country:US Info Phone Num:618-997-3321 Emergency Phone Num:618-997-3321 Preparer's Name: PETER GIMSE CAGE:IO074 === Contractor Identification === Company Name: DIAGRAPH CORP Address:3401 RIDER TRAILS S Box:520 City:EARTH CITY State:MO ZIP:63045-1110 Country:US Phone:314-739-1221 CAGE:90316 Company Name: DIAGRAPH CORP Box:520 City:HERRIN State:IL ZIP:62948 Country:US Phone:618-997-3321 CAGE:IO074 Ingred Name:XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) *95-1* CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 20-40% Other REC Limits:100 PPM OSHA PEL:100 PPM ACGIH TLV:100 PPM, SKIN EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:PROPYLENE GLYCOL METHYL ETHER (1-METHOXY-2-PROPANOL) PROPYLENE GLYCOL MONO METHYL ETHER CAS:107-98-2 RTECS #:UB7700000 Fraction by Wt: 0-20% Other REC Limits:100 PPM ACGIH TLV:100 PPM

Ingred Name:ETHYL BENZENE *95-1* CAS:100-41-4 RTECS #:DA0700000 Fraction by Wt: 0-20% Other REC Limits:100 PPM OSHA PEL:435 MG/CUM ACGIH TLV:434 MG/CUM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE, TIO2 (SUSPECTED ANIMAL CARCINOGEN, IARC GROUP 3) *95-1* CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 20-40% OSHA PEL:15 MG/CUM ACGIH TLV:10 MG/CUM (DUST)

LD50 LC50 Mixture:ORAL LD50(RAT): 4300 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN: IRRITATI

 ON/DERMATITIS. EYES: IRRITATION. INHALATION: IRRITATION. INGESTION: LARGE CONCENTRATIONS, MAY BE FATAL. OVEREXPOSURE MAY CAUSE KIDNEY & LIVER DAMAGE. Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION, REDNESS, BLURRED VISION, DIZZINESS, FATIGUE, VOMITING, NAUSEA
======================================
First Aid:SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/WATER FOR 15 MINS. INHALATION: PROVIDE FRESH AIR & REST. INGESTION: DON'T INDUCE
VOMTING. OBTAIN MEDICAL ATTENTION IN ALL CASES.
======================================
Flash Point Method:CC Flash Point:70F Lower Limits:1 Extinguishing Media:DRY CHEMICAL, FOAM, CO2 Unusual Fire/Explosion Hazard:A STRAIGHT STREAM OF WATER COULD SPREAD FIRE. A VPOR ACCUMULATION WILL FLASH &/EXPLODE IF IGNITED.
======================================
Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. ABSORB ON
INERT MATERIAL.
======================================
Handling and Storage Precautions:STORE IN COOL, DRY PLACE AWAY FROM ALL SOURCES OF IGNITION.
======================================
Respiratory Protection:RECOMMENDED-ORGANIC VAPOR Ventilation:NEEDED TO KEEP VAPOR CONCENTRATION BELOW TLV LEVEL. Protective Gloves:NON-ABSORBENT Eye Protection:RECOMMENDED Other Protective Equipment:OIL RESISTANT FOOTWEAR, PROTECTIVE CLOTHING Sup

plemental Safety and Health

Boiling Pt:B.P. Text:230F Vapor Density:>1 Spec Gravity:1.272 Evaporation Rate & amp; Reference:SLOWER THAN BU ACETATE Appearance and Odor:WHITE LIQUID INK W/SOLVENT ODOR Percent Volatiles by Volume:42

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:STATIC DISCHARGE, OPEN SPARKS/FLAM ES & OTHER IGNITION SOURCES

Hazardous Decomposition Products:CO2, CO, HYDROCARBONS

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this infor mation to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.