

KRYLON INDUSTRIAL, SHERWIN-WILLIAMS CO. -- LUBE/KRI,1322 -- 9150-01-008-0954

=====
Product Identification
=====

Product ID:LUBE/KRI,1322

MSDS Date:07/20/1994

FSC:9150

NIIN:01-008-0954

MSDS Number: BXTHX

=== Responsible Party ===

Company Name:KRYLON INDUSTRIAL, SHERWIN-WILLIAMS CO.

Address:31500 SOLON RD (OLD COCHRAN RD)

City:SOLON

State:OH

ZIP:44139

Country:US

Info Phone Num:800-247-3266

Emergenc

y Phone Num:216-292-7400

CAGE:DO934

=== Contractor Identification ===

Company Name:KRYLON INDUSTRIAL

Address:6830 COCHRAN ROAD

City:SOLON

State:OH

ZIP:44139

Country:US

Phone:800-247-3266

CAGE:DO934

Company Name:KRYLON PRODUCTS

Address:31500 SOLON ROAD

Box:City:SOLON

State:OH

ZIP:44139

Country:US

Phone:800-832-2541/216-566-2917

CAGE:87187

Company Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FARGO AVENUE

Box:City:BEDFORD HEIGHTS

State:OH

ZIP:44146

Country:US

Phone:216-292-7400 OR 2

16-595-8634
CAGE:09800

=====
Composition/Information on Ingredients
=====

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9495

Ingred Name:ISOBUTANE
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 15%
Other REC Limits:NONE RECOMMENDED

Ingred Name:VM & P NAPHTHA/ALIPHATIC PETROLEUM DISTILLATES
CAS:64742-89-8
Fraction by Wt: 18%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 AS O
IL MIST
ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:PETROLEUM HYDROCARBON/MINERAL SPIRIT
CAS:64742-47-8
RTECS #:OA5504000
Fraction by Wt: 36%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:VOLITILE ORGANIC CONTENT AS LISTED ON MSDS: 84%.
RTECS #:9999999VC
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

=====
Hazards Identification
=====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS

UNKNOWN.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYES, CNS, SKIN, RESPIRATORY TRACT. ACUTE- MAY CAUSE EYES, SKIN AND RESPIRATORY TRACT IRRITATION. MAY CAUSE NERVOUS SYSTEM DEPRESSION, UNCONSCIOUSNESS, DEATH. ORAL:MAY BE HARMFUL IF INGESTED. ASPIRATION HAZARD. CHRONIC- MAY CAUSE DERMATITIS, CENTRAL NERVOUS SYSTEM AND BRAIN DAMAGE.

Explanation of Carcinogenicity:N

ONE

Effects of Overexposure:IRRITATION, DISCOMFORT, TEARING, BLURRED VISION, COUGHING, SHORTNESS OF BREATH, DROWSINESS, CONFUSION, COMA, DEFATTING, DEATH

Medical Cond Aggravated by Exposure:NONE KNOWN.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:NONE FOR AEROSOL

Lower Limits:0.7

Upper Limits:12.0

Extinguishing Media:CARBON DIOXIDE, FOAM/DRY CHEMICAL. WATER/FOAM MAY CAUSE FROTHING & CAN BE DANGEROUS IF SPRAYED INTO HOT, BURNING LIQUID.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE-EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:INTENSIVE HEAT CREATED BY FIRE OR SUNLIGHT WILL CAUSE AEROSOLS TO BURST. DO NOT INCINERATE OR STORE ABOVE 120F.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. AVOID INHALING VAPORS. PICK UP SPILLS WITH INERT ABSORBENT MATERIAL SUCH AS SAND, CLAY, EARTH. PLACE IN A CLOSED CONTAINER.

Neutr

alizing Agent:NOT RELEVANT

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL PLACE AWAY FROM DIRECT SUNLIGHT. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:CAUTION! FLAMMABLE. CONTAINER UNDER PRESSURE. DO NOT STORE WHERE TEMPERATURES MAY EXCEED 120F (48.8C). WASH THOROUGHLY AFTER EACH USE. DO NOT SPRAY NEAR FIRE. AVOID CONTACT WITH EYES AND SKIN. DO NOT BREATHE VAPORS OR MISTS.

=====
Exposure Control
s/Personal Protection
=====

Respiratory Protection:IF TLV IS EXCEEDED OR FOR SYMPTOMS OF OVER EXPOSURE, WEAR NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR OR AIR-PURIFYING RESPIRATOR. IN EMERGENCY, WEAR A NIOSH-APPROVED POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS.

Ventilation:LOCAL EXHAUST PREFERRED. MECHANICAL VENTILATION ACCEPTABLE AT POINT OF MIST OR SPRAY RELEASE.

Protective Gloves:NITRILE IF CONTACT POSSIBLE

Eye Protection:CHEMICAL GOGGLES/FACE SHIELDS

Other Pro

ective Equipment:PROTECTIVE CLOTHINGS, EYE-WASH FACILITIES, SAFETY SHOWER.

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING, DRINKING OR SMOKING. DO NOT EAT, DRINK OR SMOKE WHILE USING PRODUCT.

Supplemental Safety and Health

WARNING! CONTAINS PROPANE AND 2-METHYLPROPANE (FLAMMABLE GASES).

=====
Physical/Chemical Properties
=====

HCC:V3

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:1

Evaporation Rate & Reference:>1 (ETHER=1); GAS

Appearance an

d Odor:AEROSOL

Percent Volatiles by Volume:>60

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:TEMPERATURES ABOVE 120F.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, METAL OXIDES

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this i

nformation by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.