

PIONEER/ECLIPSE CORP. -- ILLUMINATE (#206) -- 7930-01-380-8401

=====
Product Identification
=====

Product ID:ILLUMINATE (#206)

MSDS Date:03/15/1995

FSC:7930

NIIN:01-380-8401

MSDS Number: BYCDW

=== Responsible Party ===

Company Name:PIONEER/ECLIPSE CORP.

City:SPARTA

State:NC

ZIP:28675

Country:US

Info Phone Num:910-372-8080

Emergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name:JAMES B. MC C

ORMICK

CAGE:ONLMO

=== Contractor Identification ===

Company Name:CLEANING SOLUTIONS, INC.

Box:UNKNOW

CAGE:0NY12

Company Name:PIONEER ECLIPSE CORPORATION

Address:CHEMICAL DIVISION

Box:City:SPARTA

State:NC

ZIP:28675

Country:US

Phone:919-372-8080

CAGE:0NLM0

Company Name:PIONEER/ECLIPSE CORP.

Address:ECLIPSE RD. & HWY. 21 S.

Box:1089

City:SPARTA

State:NC

ZIP:28675

Phone:(919) 372-8080

CAGE:ONLMO

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHANOL, 2-(2-METHOXYE

THOXY) (SARA III) (LD50: 9.2 G/KG
MALE RAT, ORAL)
CAS:111-90-0
RTECS #:KK8750000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: SLIGHTLY IRRITATING. SKIN:
IRRITATING UPON REPEATED/PROLONGED CONTACT. INHALATION: VAPOR/MIST
CAN CAUSE HEADACHE, NAUSEA, IRRITATION
OF EYES, NOSE & LUNGS.
INGESTION: IRRITATION TO MOUTH, ESOPHAGUS & STOMACH.
Explanation of Carcinogenicity:NONCARCINOGENIC
Effects of Overexposure:PROLONGED/REPEATED CONTACT CAN CAUSE DRYING,
DEFATTING & DERMATITIS TO SKIN.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH W/LARGE AMOUNT WATER AT LEAST 15 MINUTES. SEE
PHYSICIAN IF IRRITATION PERSISTS. SKIN: WASH AFFECTED AREAS W/SOAP
& WATER. INHALATION: MOVE TO FRESH AIR. INGESTION: DRINK
SEVERAL
GLASSES WATER AND INDUCE VOMITING. SEEK MEDICAL ATTN.

=====
===== Fire Fighting Measures =====

Flash Point:NONCOMBUSTIBLE
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:NA
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:MATERIALS CAN SPLATTER ABOVE 212F.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SM: ABSORB ON INERT MATERIAL (SAND/EARTH)
DISPOSE IN ACCORDANCE FED./STATE/LOCAL

