

NILES CHEMICAL PAINT CO. -- N-1488A 383 BROWN CAMO TYPE IV -- 8010-01-260-0916

=====
Product Identification
=====

Product ID:N-1488A 383 BROWN CAMO TYPE IV

MSDS Date:07/25/1995

FSC:8010

NIIN:01-260-0916

Kit Part:Y

MSDS Number: BYCPL

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO.

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-3377

Emergency Phone Num:219-236-5856

Preparer's Name:MIKE LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====
Composition/Information on Ingredients
=====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:

NO Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: ACUTE: EYES: SEVERE IRRITATION, LACRIMATION, REDNESS, BLURRED VISION. SKIN: REDNESS, IRRITATION, DEFATTING LEADING TO DERMATITIS. BREATHING: NASAL & RESPIRATORY IRRITATION, CNS DEPRESSION, ASPHYXIATION. INGESTION: GASTROINTESTINAL IRRITATION. CHRONIC: HISTOLOGIC FIBROSIS OF LUNGS, NARCOSIS, COMA.

Explanation of Carcinogenicity: NOT LISTED BY NTP, IARC OR OSHA.

Effects of Over

exposure: BREATHING: DIZZINESS, DROWSINESS, WEAKNESS, FATIGUE, CONFUSION, NAUSEA, HEADACHE, VERTIGO, POSSIBLE UNCONSCIOUSNESS. INGESTION: ABDOMINAL PAIN, NAUSEA, VOMITING, DIARRHEA.

Medical Condition Aggravated by Exposure: NK. TARGET ORGANS: RESPIRATORY SYSTEM, CNS, LUNGS, EYES, SKIN.

=====
===== First Aid Measures =====

First Aid: INHAL: GET FRESH AIR. IF BREATHING STOPPED, START ARTIF RESP. GET MED AID. SKIN: IMMEDIATELY FLUSH W/WATER. IF MAT'L PENETRATES CLOTHING, REMOVE CONTAM CLOTHING, FLUSH SKIN W/WATER. GET MED AID. EYES: IMMEDIATELY FLUSH W/LRG AMT WATER 15 MIN, LIFTING EYELIDS. GET MED AID IMMEDIATELY. INGESTION: DRINK 1-2 GLASSES WATER. DON'T INDUCE VOMITING. CONSULT PHYSICIAN/POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY

=====
===== Fire Fighting Measures =====

Flash Point Method: TCC

Flash Point: 20.0F, -6.7C

Lower Limits: 1.0

Upper Limits: 10.0

Extinguishing Media: DRY CHEMICAL, FOAM, CO
2.

Fire Fighting Procedures: WEAR POS PRESS SCBA W/FULL FACEPIECE & FULL PROTECTIVE CLOTHING. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESS BLD UP & AUTOIGNIT/EXPLOS.

Unusual Fire/Explosion Hazard: VAPOR HEAVIER THAN AIR, TRAVEL TO IGNIT SOURCE. ISOLATE FROM IGNIT SOURCE. CLSD CNTNR EXPLODE W/HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.*

=====
===== Accidental Release Measures =====

Spill Release Procedures: NO IGNIT SOURCES.

MINIMIZE BREATHING VAPORS.

AVOID SKIN CONTACT. SM: ABSORB W/INERT MAT'L (CLAY, SOIL, COMMERC ABSORB) SHOVEL RECLAIMED LIQ & ABSORB INTO RECOVERY/SALVAGE DRUMS. LG: DIKE (NO FURTHER MOVEMENT) & RECLAIM INTO SALVAGE DRUMS/TANK TRUCK.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORAGE IN HIGH TEMP AREAS OR NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. AVOID ROUGH HANDLING.

Other Precautions:

CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTY. DO NOT WELD OR FLAME CUT ON EMPTY DRUMS. DO NOT WEAR CONTACT LENSES WHEN WORKING W/THIS MATERIAL.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR APPROP (TC-23C-75) FITTED HALF-MASK FOR FULL FACEPIECE RESPIRATOR (NIOSH/MSHA) DURING/AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS BELOW TLV. FOLLOW RESPIRATOR MFR DIRECTIONS FOR USE.

Ventilation:

PROVIDE SUFFICIENT VENTILATION (VOLUME/PATTERN) TO KEEP AIR CONC BELOW TLV PEL. REMOVE DECOMP PROD. VENT VAPOR EMITTED.

Protective Gloves:CHEM RESISTANT, NITRILE OR VITON

Eye Protection:CHEM GOGGLES/SAFETY GLASSES/FACE SHIELDS

Work Hygienic Practices:WASH ANY CONTAM CLOTHING OR CLOTH THAT BECOMES WET BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING RESTROOM.

Supplemental Safety and Health
NK

=====
===== Physical/Chemical Properties =====

Boiling Pt

:B.P. Text:175 TO 302F

Vapor Density:>AIR

Spec Gravity:1.497

pH:NA

Viscosity:70-85 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:54.13

Corrosion Rate:MINIMAL

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS, NITRATES, ALKALIES, ACIDS.

Stability Condition to Avoid:NK *OVEREXPOS TO DECOMP PROD MAY CAUSE HEALTH

HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. GET MEDICAL AID.
Hazardous Decomposition Products: CAN PRODUCE CARBON MONOXIDE &/OR
CARBON DIOXIDE.
Conditions to Avoid Polymerization: HIGH TEMPERATURES

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, LOCAL
REGULATIONS. EPA HAZ WASTE CODE: D001 (IGNITABLE).

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.