

ADVANTAGE BATTERY CORP. SUBSID OF ACUMEX -- LEAD-ACID BATTERY -- 6140-01-360-6489

=====
Product Identification
=====

Product ID:LEAD-ACID BATTERY

MSDS Date:03/15/1996

FSC:6140

NIIN:01-360-6489

MSDS Number: BYHBQ

=== Responsible Party ===

Company Name:ADVANTAGE BATTERY CORP. SUBSID OF ACUMEX

Address:8701 BEDFORD-EULESS RD SUITE 501

City:HURST

State:TX

ZIP:76053

Country:US

Info Phone Num:817-589-

1225

Emergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:0VW59

=== Contractor Identification ===

Company Name:CELL ENERGY INC

Address:3190-B ORANGE GROVE AVE

Box:City:NORTH HIGHLANDS

State:CA

ZIP:95660-5706

Country:US

Phone:916-484-7974

CAGE:1U269

Company Name:GES AMERICA (FORMERLY) ADVANTAGE BATTERY CORP

Address:7001 GRAPEVINE HIGHWAY 500

Box:City:NORTH RICHLAND HILLS

State:TX

ZIP:76180

Country:US

Phone:817-589-1225

CAGE:0VW59

=====
Composition/Information on Ingredients
=====

Ingred Name:SULFURIC ACID (SARA III)
CAS:7664-93-9
RTECS #:WS5600000
Fraction by Wt: 11-23%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:LEAD (SARA III)
CAS:7439-92-1
RTECS #:OF7525000
Fraction by Wt: 64-80%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.05 MG/M3;1910.1025
ACGIH TLV:0.15 MG/M3;DUST 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:ANTIMONY (SARA 313) (CERCLA)
CAS:7440-36-0
RTECS #:CC4025000
Frac
tion by Wt: 1.5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.5 MG/M3
ACGIH TLV:0.5 MG (SB)/M3; 9495
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ARSENIC (SARA 313) (CERCLA)
CAS:7440-38-2
RTECS #:CG0525000
Fraction by Wt: 0.2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:SEE 1910.1018
ACGIH TLV:0.01 MG/M3, A1; 9495
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:CALCIUM, METAL
CAS:7440-70-2
RTECS #:EV8040000
Fraction by Wt: 0.2%
Other REC Limits:NONE RECOMMENDED

Ingred Name:TIN
CAS:7440-

31-5
RTECS #:XP7320000
Fraction by Wt: 0.2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9495

Ingred Name:POLYPROPYLENE (CASE MATERIAL)
CAS:9003-07-0
RTECS #:TR5000000
Fraction by Wt: 5-6%
Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYETHYLENE (SEPARATOR MATERIAL)
CAS:9002-88-4
RTECS #:TQ3325000
Fraction by Wt: 1-2%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 2140 MG/K
G (H2SO4)

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:ACID IS CORROSIVE TO ALL
TISSUES! MAY CAUSE IRRITATIONAND BURNS OF SKIN, EYES, OR GI TRACT.
MAY CAUSE CORNEAL DAMAGE OR BLINDNESS. MAY BE FATAL IF SWALLOWED.
CHRONIC: TOOTH EROSION, INFLAMMATION OF NOSE, THROAT AND BRONCHIAL
TUBES.

Explanation of Carcinogenicity:THE ELECTROLYTE IS NOT LISTED BY IARC,
NTP, OR OSHA AS A
CARCINOGEN.

Effects of Overexposure:INHALATION: BURNING SENSATION IN NOSE, THROAT
AND LUNGS, COUGHING, WHEEZING, SHORTNESS OF BREATH. EYES: REDNESS,
TEARING, BLURRED VISION, BURNS, SEVERE PAIN. SKIN: SEVERE PAIN,
BURNS, REDNESS, RASH, I TCHING. INGESTION: BURNS OF MOUTH, THROAT,
AND ESOPHAGUS, SEVERE STOMACH PAIN, NAUSEA, VOMITING.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS
OR WITH A PRE-EXISTING DISEASE INVOLVING THE RESPIRATORY TRACT OR
TEETH

MAY BE AT INCREASED RISK FROM EXPOSURE.

=====
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING.
GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER
FOR 15 MINUTES HOLDING EYELIDS OPEN. GET PROMPT MEDICAL ATTENTION.
SKIN :REMOVE CONTAMINATED CLOTHING. WASH WITHPLENTY OF WATER FOR 15
MINUTES. GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE VOMITING. GIVE
NOTHING BY MOUTH IF UNCONS
CIOUS. GET IMMEDIATE MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Extinguishing Media:USE DRY CHEMICAL, CARBON DIOXIDE, FOAM, HALOGEN.
Fire Fighting Procedures:USE OF WATER IN EXTINGUISHING BURNING
BATTERIES MAY CAUSE SPATTERING DUE TO THE PRESENCE OF MOLTEN LEAD.
WEAR SCBA AND FULL PROTECTIVE GEAR.
Unusual Fire/Explosion Hazard:WHEN BATTERY IS BEING CHARGED, HYDROGEN
GAS IS PRODUCED. BATTERY MAY EXPLODE IF HYDROGEN GAS TRAPPED INSIDE
THE CASE SHOULD IGNITE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SHOULD A BATTERY BREAK OPEN, ISOLATE AREA.
ELECTROLYTE SHOULD BE ABSORBED WITH A NON-ORGANIC TYPE ABSORBENT
SUCH AS DRY SAND OR EARTH. RESIDUE MAY BE NEUTRALIZED WITH BAKING
SODA AND RINSED WITH WATER .
Neutralizing Agent:USE SODA ASH OR BAKING SODA TO NEUTRALIZE THE
ELECTROLYTE.

=====
===== Handling and Storage =====

Handling and S
torage Precautions:AVOID THE USE OF UNINSULATED TOOLS. IF
THEY ARE REQUIRED, TAKE CARE NOT TO ELECTRICALLY SHORT THE
TERMINALS. REMOVE METAL JEWELRY BEFORE SERVICING.
Other Precautions:UNDER NORMAL CONDITIONS OF USE, EXPOSURE TO LEAD OR
LEAD CONTAINING COMPOUNDS DOES NOT OCCUR. SHOULD A BATTERY BREAK
OPEN AND A LEAD SPILL OCCUR, PRECAUTIONS SHOULD BE TAKEN TO PREVENT
LEAD DUST FROM BECOMING AIR BORNE.

=====
===== Exposure Controls/Personal Protection =====

Resp

iratory Protection:UNDER NORMAL CONDITIONS OF USE, RESPIRATORY PROTECTION IS NOT REQUIRED. HOWEVER, IF CONDITIONS ARISE THAT REQUIRE THEIR USE, USE ONLY NIOSH/MSHA RESPIRATORS APPROVED FOR DUST, FUME AND MIST.

Ventilation:BATTERY CHARGING AREAS MUST BE ADEQUATELY VENTILATED TO PREVENT HAZARDOUS CONCENTRATIONS OF FLAMMABLE GAS OR ACID MIST.

Protective Gloves:RUBBER GLOVES APPROVED FOR SULFURIC ACID

Eye Protection:CHEMICAL SPLASH GOGGLES AND FACE SHIELD

Other Protective Equipment:E

YE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE IMPERVIOUS WORK CLOTHING, BOOTS AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

MSDS FROM MANUFACTURER WAS STRICTLY FOR SULFURIC ACID; PHYSICAL CHARACTERISTICS IN MSDS ARE FOR SULFURIC ACID.

===== Physical/Chemical Properties =====

HCC:C1

Boiling Pt:B.P. Text:2

30F,110C

Vapor Pres:10 MMHG

Vapor Density:>1

Spec Gravity:1.24-1.28

Evaporation Rate & Reference: