

POWER-SONIC CORP, TECHNICAL DIV -- SEALED MAINTENANCE FREE LEAD ACID BATTERIES --
6140-01-237-8005

===== Product Identification =====

Product ID:SEALED MAINTENANCE FREE LEAD ACID BATTERIES

MSDS Date:10/01/1994

FSC:6140

NIIN:01-237-8005

MSDS Number: BYHKL

=== Responsible Party ===

Company Name:POWER-SONIC CORP, TECHNICAL DIV

Address:SIEMMPRE VIVA ROAD, SUITES A-F

City:SAN DIEGO

State:CA

ZIP:9217

3

Country:US

Info Phone Num:619-575-2275

Emergency Phone Num:619-575-2275

Preparer's Name:ENGINEERING

CAGE:0WJ05

=== Contractor Identification ===

Company Name:POWER-SONIC CORP

Address:9163 SIEMPRE VIVA ROAD

Box:City:SAN DIEGO

State:CA

ZIP:92173

Country:US

Phone:619-661-2030

CAGE:0WJ05

===== Composition/Information on Ingredients =====

Ingred Name:LEAD (SARA III) (PB, PBO2, PBSO)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 70%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:SE

E 1910.1025
ACGIH TLV:0.15 MG/M3,DUST;9394
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:SULFURIC ACID (SARA III)
CAS:7664-93-9
RTECS #:WS5600000
Fraction by Wt: 20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:FIBERGLASS (FIBROUS GLASS) SEPARATOR
CAS:65997-17-3
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 RESP DUST
ACGIH TLV:10 MG/M3 (300C(572F) MAY RELEASE COMBUSTIBLE GASES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:IF SULFURIC ACID IS SPILLED FROM BATTERY
NEUTRALIZE ACID W/SODIUM BICARBONATE (BAKING SODA), SODIUM CARBON
(SODA ASH), OR CALCIUM OXIDE (LIME).FLUSH AREA W/WATER & DISCARD TO
SEWAGE SYSTEM. DO NOT ALL OW UNNEUTRALIZED AICD INTO SEWAGE SYSTEM.
Neutralizing Agent:SODIUM BICARBONATE (BAKING SODA), SODIUM CARBON
(SODA ASH), CALICUM OXIDE (LIME)

===== Handling and Storage =====
=====

Handling and Storage Precautions:DO NOT REST TOOLS OR CABLES ON THE
BATTERY. USE INSULATED TOOLS ONLY. FOLLOW ALL INSTALLATION
INSTRUCTIONS & DIAGRAMS WHEN INSTALLING BATTERY SYSTEM.
Other Precautions:ELECTRICAL SAFETY-DUE TO THE BATTERY'S LOW INTERNAL
RESIST & HIGH POWER DENSITY, HIGH LEVELS OF SHORT CIRCUIT CURRENT
CAN DEVELOPED ACROSS THE BATTERY TERMINALS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR (F

OR LEAD). A RESPIRATOR SHOULD BE
WORN DURING RECLAIM, OPERATIONS IF THE TLV IS EXCEEDED.
Ventilation:NONE SPECIFIED BY MANUFACTURER.
Protective Gloves:RUBBER GLOVES, APRON.
Eye Protection:SAFETY GOGGLES, FACE SHIELD.
Other Protective Equipment:PROTECTIVE EQUIPMENT MUST BE WORN IF BATTERY
IS CRACKED OR OTHERWISE DAMAGED.
Work Hygienic Practices:WASH HANDS AFTER HANDLING.
Supplemental Safety and Health
PER CTDF:DRY CHARGED W/ELECTROLYTE PACKED SEPARATELY & SHIPPED
SIMULTANEOUSLY.

=====

===== Physical/Chemical Properties =====

HCC:C1
Melt/Freeze Pt:M.P/F.P Text:621F,327C
Spec Gravity:11.34 LEAD
Solubility in Water:NONE
Appearance and Odor:SILVER-GRAY METAL. NO ODOR. (LEAD).

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
REACTIVE METALS, STRONG BASES, MOST ORGANIC COMPOUNDS.
Stability Condition to Avoid:PROHIBIT SMOKING, APRKS, ETC. FROM BATTERY
CHARGING AREA. AVOID MIXING ACID W/OTHER
CHEMICAL.
Hazardous Decomposition Products:SULFURIC DIOXIDE, TRIOXIDE, HYDROGEN
SULFIDE, HYDROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:NEUTRALIZED ACID MAY BE FLUSHED DOEWN
SEWER.SPENT BATTERIES MUST BE TREATED AS HAZ WASTE & DISPOSED OF
ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS. A COPY OF MSDS
MUST BE SUPPLIED TO ANY SCRAP D EALER OR SECONDARY LEAD SMELLER
WITH BATTERY.

Disclaimer (provided with this informa

tion by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.