

EASTMAN KODAK COMPANY -- 848 7555 EA-5 PREHARDENER AND REPLENISHER, WORKING
SOLN -- 6750-00-001-9398

===== Product Identification =====

Product ID:848 7555 EA-5 PREHARDENER AND REPLENISHER, WORKING SOLN

MSDS Date:03/30/1995

FSC:6750

NIIN:00-001-9398

Kit Part:Y

MSDS Number: BYVTM

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:146

50

Country:US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 75-80%

Other REC Limits:NONE RECOMMENDED

In

gred Name:MAGNESIUM SULFATE HEPTAHYDRATE
CAS:10034-99-8
RTECS #:OM4508000
Fraction by Wt: 10-15%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM SULFATE
CAS:7757-82-6
RTECS #:WE1650000
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM ACETATE
CAS:127-09-3
RTECS #:AJ4300010
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SUCCINADEHYDE-BIS-BISULFITE
CAS:5450-96-4
RTECS #:EK3585000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NO
T ESTABLISHED.
ACGIH TLV:NOT ESTABLISHED.

Ingred Name:FORMALDEHYDE (SARA 302/313) (CERCLA)
CAS:50-00-0
RTECS #:LP8925000
Fraction by Wt: 0.7%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:SEE 1910.1048
ACGIH TLV:C 0.3 PPM, A2; 9495
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:INHAL:FORMA

LDEHYDE DETECTABLE BY MOST

PEOPLE @LEVELS 100C

Vapor Pres:18MM @20C

Vapor Density:0.6

Spec Gravity:1.18-120

pH:SUPPLE

Solubility in Water:COMPLETE.

Appearance and Odor:LIQUID, GREEN, STRONG ODOR.

Percent Volatiles by Volume:75-80

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE W/COMMON MATLS & CONTAMINANTS W/WHICH MATL MAY REASONABLY COME INTO CONTACT.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazard

ous Decomposition Products:HAZ COMBUST PROD:NONE (NON-COMBUSTIBLE).

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE/TREAT/DISPOSAL MAY BE SUBJECT TO NAT/STATE/LOC LAWS.FLUSH TO SEWER W/LG AMTS OF WATER.CHEM SUBJ TO SARA SEC 313 TITLE III & 40CFR PART 372:FORMALDEHYDE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The Uni

ted States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.