View NSN Online: https://aerobasegroup.co.il/nsn/8010-01-336-0526

DEL PAINT CORP. -- TT-E-2784 -- 8010-01-336-0526

Product ID:TT-E-2784 MSDS Date:08/01/1995

FSC:8010

NIIN:01-336-0526

MSDS Number: BYYNB === Responsible Party ===

Company Name: DEL PAINT CORP.

Address:3105 E. RENO City:OKLAHOMA CITY

State:OK ZIP:73117 Country:US

Info Phone Num:405-672-1431/FAX 405-672-0804 Emergency Phone Num:800-424-9300 24 HRS

Preparer's Name: ONEY FLEMING CAGE:JO954

=== Contractor Identification === Company Name: DEL PAINT CORP.

Address:3105 E. RENO City:OKLAHOMA CITY

State:OK ZIP:73117 Country:US

Phone: 405-672-1431/FAX 405-672-0804

CAGE:JO954

Company Name: DEL PAINT MFG

Address:3105 EAST RENO Box:City:OKLAHOMA CITY

State:OK ZIP:73117 Country:US

Phone: 405-672-1431

CAGE:39934

====== Composition/Information on Ingredients ========

Ingred Name:PROPYLENE GLYCOL

CAS:57-55-6

RTECS #:TY2000000 Fraction by Wt: 3.5%

Other REC Li

mits:NONE RECOMMENDED

Ingred Name:2,2,4-TRIMETHYL-1-3-PENTANEDIOL MONOISOBUTYRATE

CAS:25265-77-4 RTECS #:UF6000000 Fraction by Wt: 3.16%

Other REC Limits: NONE RECOMMENDED

Ingred Name: DIMETHYLAMINOETHANOL LOW VOC

CAS:108-01-0

RTECS #:KK6125000 Fraction by Wt: 0.2%

Other REC Limits: NONE RECOMMENDED

Ingred Name: 2-N-OCTYL-4-ISOTHIAZOLIN-3-ONE

CAS:26530-20-1 Fraction by Wt: 0.18%

Other REC Limits: NONE RECOMMENDED

Ingred Name: NON HAZARDOUS INGREDIENTS

Fraction by Wt: 92.96% Other REC Limits:NONE R

ECOMMENDED

OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

============ Hazards Identification ===============

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: CAN CAUSE IRRITATION OF RESPIRATORY PASSAGES.

Effects of Overexposure:INHALATION OF VAPOR/MIST CAN CAUSE HEADACHES, NAUSEA, IRRITATION OF NOSE/THROAT/LUNGS. EYES: CAN CAUSE SLIGHT IRRITATION. CHRONIC SKIN CONTACT CAN CAU

SE SLIGHT IRRITATION.

Medical Cond Aggravated by Exposure:PREEXISTING LUNG DISEASE MAY BE AGGRAVATED BY EXPOSURE.

First Aid:EYES: FLUSH W/LARGE AMTS WATER 15 MINUTES. CONSULT DR. IF IRRITATION PERSISTS. SKIN: WASH AFFECTED AREA THOROUGHLY W/SOAP & WATER. INGESTION: GIVE 2 GLASSES WATER. CONSULT DR.

========== Fire Fighting Measures ===============

Flash Point Method:SCC Flash Point:>212F,>100C

Lower Limits:NA Upper Limits:NA Extinguishing Media: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG. Fire Fighting Procedures: WEAR SCBA (PRESSURE DEMAND MSHA/NIOSH APPROVED OR EQUIVALENT) & FULL PROTECTIVE GEAR. Unusual Fire/Explosion Hazard: MATERIAL CAN SPLATTER ABOVE 212F/100C. POLYMER FILM CAN BURN. ========= Accidental Release Measures =============== Spill Release Procedures: KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY. USE CARE TO AVOID FALLING. CONTAIN W/INERT MAT'L (SAND/EARTH). TRANSFER LIQ/SOLID DIKING MAT'L TO SEPARATE SUITABLE CONTAINERS FOR RECOVERY/DISPOSAL. Neutralizing Agent:NONE ============= Handling and Storage ========================== Handling and Storage Precautions: KEEP FROM FREEZING. DO NOT TAKE INTERNALLY, KEEP AWAY FROM CHILDREN. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVER-SPRAY DURING SPRAY APPLICATION. Ventilation: NORMAL. SUCH AS FAN. Protective Gloves: RUBBER Eye Protection: SAFETY GLASSES OR GOGGLES. Other Protective Equipment: EYEWASH STATION. Supplemental Safety and Health

NK

======== Physical/Chemical Properties =========

Boiling Pt:B.P. Text:212 TO 644F
Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C
Decomp Temp:Decomp Text:350F,177C
Vapor Pres:NONE
Vapor Density:>AIR
Spec Gravity:1.14
VOC Pounds/Gallon:192

pH:9 MAX

VOC Grams/Liter: 1.6

Viscosity:77-95

KU
Evaporation Rate & Deference: SLOWER THAN ETHER
Solubility in Water: SLIGHT
Appearance and Odor: GRAY LIQUID, SLIGHT ODOR
Percent Volatiles by Volume: 60.6

======== Stability and Reactivity Data ===========

Stability Indicator/Materials to Avoid:YES NONE KNOWN Stability Condition to Avoid:NONE Hazardous Decomposition Products:ACRYLIC MONOMERS

======= Disposal Considerations ============

Waste Disposal Methods: KEEP SPILLS/CLEANING RUN-OFF OUT OF SEW ERS &

OPEN BODIES OF WATER. CONSULT FEDERAL/STATE/LOCAL AUTHORITIES FOR PROPER DISPOSAL PROCEDURES CONCERNING HEALTH & ENVIRONMENT.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.