View NSN Online: https://aerobasegroup.co.il/nsn/6520-01-224-9681

Product ID:VAC U EZ MSDS Date:05/12/1995 FSC:6520 NIIN:01-224-9681 MSDS Number: BZBSD === Responsible Party === Company Name: CONTINENTAL LABORATORIES Address:912 S STATE STREET City:MADRID State:IA ZIP:50156 Country:US Info Phone Num:515-795-2000 Emergency Phone Num:515-795-2000 CAGE:1V857 === Contractor Identification === **Company Name: CONTINENTAL LABORATORIES** Address:912 S STATE STREET Box:City:MADRID State:IA ZIP:50156 Country:US Phone:515-795-2000 CAGE:1V857

Ingred Name:ETHYL ALCOHOL CAS:64-17-5 RTECS #:KQ6300000 Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Ca

rcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NONE KNOWN.
Explanation of Carcinogenicity:NOT CARCINOGENIC. Effects of Overexposure:EYES-CONTACT WITH EYES IS PAINFUL AND IRRITATING. SKIN-PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION. INHALATION-VAPORS MAY IRRITATE NASAL PASSAGE.
Medical Cond Aggravated by Exposure:NOT ESTABLISHED.
======================================
First Aid:EYE-FLUSH IMMEDIATELY WITH WATER FOR AT LEAST 1 5 MIN.
SKIN-WASH OFF SKIN WITH WATER. REMOVE CONTAMINATED CLOTHING AND CLEAN BEFORE RESUE. INHALATION-REMOVE TO FRESH AIR. INGESTION-IF SWALLOWED CONSULT A PHYSICIAN IMMEDIATELY.
======================================
Flash Point Method:TCC Flash Point:104F,40C Autoignition Temp:Autoignition Temp Text:UNKNON Extinguishing Media:DRY CHEMICAL, ALL PURPOSE FOAM OR WATER FOG. Fire Fighting Procedures:SELF-CONTAINED POSITIVE PRESSURE BREATHING APPARATU
S AND PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard:VAPORS MAY TRAVEL BY AIR CURRENTS AND BE IGNITED BY PILOT LIGHTS OR OTHER FLAMES, SPARKS OR HEATERS.
======================================
Spill Release Procedures:SOAK UP WITH ABSORBENT MATERIAL. FLUSH AREA WITH WATER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
Handling and Storage Precautions:WEAR PROTECTIVE CLOTHING. AVO
OVERHEATING AND FREEZING. Other Precautions:NONE.
========= Exposure Controls/Personal Protection ====================================
Respiratory Protection:NONE SPECIFIED BY MANUFACTURER. Ventilation:LOCAL EHXAUST. Protective Gloves:LATEX OR NEOPRENE.
Eye Protection:SAFETY GLASSES OR GOGGLES. Other Protective Equipment:NOT REQUIRED. Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health NONE
======================================

oiling Pt:B.P. Text:183F,84C Melt/Freeze Pt:M.P/F.P Text:14F,-10C Vapor Density:1 (N-BUTYL ACETATE=1) Solubility in Water:COMPLETE Appearance and Odor:DARK GREEN, HERBAL.

==

Stability Indicator/Materials to Avoid:YES CONCENTRATED NITRIC OR SULFURIC ACID. STRONG OXIDIZING AGENTS. Stability Condition to Avoid:AVOID EXCESSIVE HEAT. (I.E. BOILING) Hazardous Decomposition Products:BURNING CAN PRODUCE TRACES OF CARBON MONOXIDE.

Waste Disposal Methods: DISPOSE OF ACCORDING TO LOCAL POLLUTION REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document

should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.