View NSN Online: https://aerobasegroup.co.il/nsn/9150-01-415-9114

Product ID:MILOTEC-1 OR MH 1204 MSDS Date:11/06/1996 FSC:9150 NIIN:01-415-9114 MSDS Number: BZRCM === Responsible Party === Company Name: MILITEC CORP Address:1911 NORTH FORT MYER DRIVE # 500 City:ARLINGTON State:VA ZIP:22209 Country:US Info Phone Num:703-528-8371/2614 Emergency Phone Num:703-528-8371 CAG E:MILI2 === Contractor Identification === Company Name: MILITEC CORP Address:1911 N FORT MYER DR #500 Box:City:ARLINGTON State:VA ZIP:22209 Country:US Phone:703-528-8371 CAGE:MILI2 Company Name: MILITEC INC Address:11828 PIKA DR Box:City:WALDORF State:MD ZIP:20602 Country:US Phone:301-893-3910 CAGE:0KXE0

Ingred Name:NON-HAZARDOUS INGREDIENTS Fraction by Wt: 100% Other REC Limits:NONE RECOMMENDED

====== Hazards

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: TARGET ORGANS: EYE, SKIN, RESPIRATORY TRACT. ACUTE- MAY CAUSE EYES & SKIN IRRITATION. PROLONGED/REPEATED SKIN CONTACT CAUSES DEFATTING. INHALATION OF VAPORS/OIL MIST MAY CAUSE IRRITATION. INGESTION MAY CAUSE NAUSEA. ASPIRATION HAZARD. CHRONIC- MAY CAUSE DERMATITIS. Explanation of Carcinogenicity:NONE Effects of Overexposure: IRRITATION, NAUSEA Medical Cond Aggravated by Exposure: PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT. First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED-REMOVE TO FRESH AIR. EYES-FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN-WIPE OFF EXCESS. WASH SKIN WITH SOAP & WATER. INGESTED -DO NOT INDUCE VO MITING. IF CONSCIOUS, RINSE MOUTH. SEEKMEDICAL ATTENTION. Flash Point Method:COC Flash Point:410F,210C Autoignition Temp: Autoignition Temp Text: 715F Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM/DRY CHEMICAL. Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/ Explosion Hazard:NONE.

Spill Release Procedures:CONTAIN LIQUIDS & CONTROL DISCHARGES TO STREAMS OR SEWER SYSTEMS UNDER CONDITIONS ACCEPTABLE TO LOCAL, STATE AND FEDERAL AUTHORITIES. APPLY ABSORBENT MATERIALS & SWEEP UP & PLACE WASTE IN A SUITABLE & PROPERLY LABELED CONTAINER FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Ha

ndling and Storage Precautions:TYPICAL FOR OTHER HYDROCARBON LUBRICANTS. KEEP AWAY FROM OPEN FLAME. KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINER CLOSED WHEN NOT IN USE. Other Precautions:STORE IN ORIGINAL CONTAINER. KEEP OFF FOOD STUFFS. AVOID EYE CONTACT. AVOID REPEATED/PROLONGED SKIN CONTACT. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING MIST.

Respiratory Protection:NONE NORMALLY REQUIRED. IF ENGINEERING C ONTROLS

FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR AN AIR-SUPPLIED RESPIRATOR OR SCB A, AS REQUIRED. USE IAW 29 CFR 1910.134.

Ventilation:NONE NORMALLY REQUIRED. DLA-HMIS: USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW PEL.

Protective Gloves: RUBBER, IF DESIRED.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:NO SPECIAL EQUIPMENT REQUIRED. HOWEVER, GOOD PERSONAL HYGIENE PRA

CTICES SHOULD ALWAYS BE FOLLOWED.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE. Supplemental Safety and Health NONE SPECIFIED BY MANUFACTURER.

HCC:V6 Boiling Pt:B.P. Text:528F,276C Melt/Freeze Pt:M.P/F.P Text:-45F,-43C Vapor Density:NONE@70F Spec Gravity:1.142 Viscosity:43.4CST @100F Evaporation Rate & amp; Reference:NEGLIGIBLE Solubili ty in Water:SLIGHT (