View NSN Online: https://aerobasegroup.co.il/nsn/6750-01-418-6293

EASTMAN KODAK COMPANY -- 838 0578 FLEXICOLOR BLEACH III REPLENISHER NR, WORK SOLUTION -- 6750-01-418-6293

============= Product Identification ==================

Product ID:838 0578 FLEXICOLOR BLEACH III REPLENISHER NR, WORK SOLUTION

MSDS Date: 10/23/1997

FSC:6750

NIIN:01-418-6293

Kit Part:Y

MSDS Number: CBSQJ === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650 Country:US

Info Phone Num:716-477-3194 MSDS:800-242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD Box:City:ROCHESTER

State:NY

ZIP:14650-3129 Country:US

Phone:800-828-6203

CAGE:5K871

==

====== Composition/Information on Ingredients ========

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 80 - 85%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Ingred Name: AMMONIUM FERRIC PROPYLENEDIAMINETETRAACETIC ACID

CAS:111687-36-6 Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

Ingred Name: ACETIC ACID (CERCLA)

CAS:64-19-7

RTECS #:AF1225000 Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 PPM

ACGIH

TLV:10 PPM/15 STEL; 9596 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: AMMONIUM ACETATE (CERCLA)

CAS:631-61-8

RTECS #:AF3675000 Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: AMMONIUM BROMIDE

CAS:12124-97-9 RTECS #:BO9170000 Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

Ingred Name: AMMONIUM NITRATE

CAS:6484-52-2

RTECS #:BR9050000 Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

======= H

azards Identification ===========
LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN. Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:TARGET ORGANS:EYE. ACUTE- EYE:NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION. SKIN:LOW HAZARD FOR RECOMMENDED HANDLING. INHALE:EXPECTED TO BE A LOW HAZARD. ORAL:EXPECTED TO BE A LOW INGESTIO N HAZARD. CHRONIC-UNKNOWN. Explanation of Carcinog enicity:NONE Effects of Overexposure:TRANSIENT EYE IRRITATION Medical Cond Aggravated by Exposure:NONE
======================================
First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:IF CONSCIOUS, DRINK 1-2 GLASSES OF WATE R. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
====== Fire Fighting Measures ====================================
Flash Point:NONE Lower Limits:NOT RELEVANT Upper Limits:NOT RELEVANT Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS. Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. HAZARDOUS DECOMPOSITION PRODUCTS MAY BE FORMED. Unusual Fire/Explosion Hazard:NONE
========= Accidental Release Measures ====================================
Spill Release Procedures:FLUSH TO SEWER WITH LARGE AMOUNT OF WATER IF PERMITTED. OTHERWISE, ABSORB SPILL WITH INERT MATERIAL SUCH AS VERMICULITE. PLACE IN A CONTAINER FOR DISPOSAL. CLEAN AREA THOROUGHLY TO REMOVE RESIDUAL CON TAMINATION. PREVENT RUNOFF FROM

Λ ENTERING SEWERS.

Neutralizing Agent:NOT RELEVANT

============== Handling and Storage =========================

Handling and Storage Precautions: STORE IN TIGHTLY CLOSED CONTAINER,

AWAY FROM INCOMPATIBLE MATERIALS. Other Precautions: DO NOT GET IN EYES. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. KEEP OUT OF REACH OF CHILDREN. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: NONE SHOULD BE NEEDED. Ventilation: GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES/HR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS Protective Gloves:LATEX RECOMMENDED Eye Protection: SAFETY GLASSES WITH SIDE SHIELD/GOGGLES Other Protective Equipment: EYE BATH, SAFETY SHOWER, WASH FACILITIES Work Hygienic Practices: OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. Supplemental Safety and Health KIT CONSISTS OF PART A (PNI A) AND PART B (PNI B). THIS IS WORK SOLUTION. THE PH RANGE: 4.1 - 4.3 ======== Physical/Chemical Properties ============ HCC:C3 NRC/State Lic Num: NOT RELEVANT Boiling Pt:B.P. Text:>212F,>100C Vapor Pres:18 @ 68F Vapor Density:0.6 Spec Gravity:1.10 pH:4.1 Solubility in Water: COMPLETE Appearance and Odor: COLORLESS LIQUID - SLIGHT VINEGAR ODOR Percent Volatiles by Volume:75-80 ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YES BASES, SODIUM HYPOCHLORITE (BLEACH), STRONG OXIDIZING AGENTS Stability Condition to Avoid:NONE Hazardous Decomposition Products: AMMONIA, CHLORAMINE, NITROGEN OXIDE

======== Disposal Considerations =============

Waste Disp

osal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE OR LOCAL REGULATIONS. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER, IF ALLOWED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, FOLLOW L ABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly o

r implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.