

EASTMAN KODAK COMPANY -- 174 9902 FLEXICOLOR STABILIZER & REPLENISHER, PART B --
6750-00-539-9540

===== Product Identification =====

Product ID:174 9902 FLEXICOLOR STABILIZER & REPLENISHER, PART B

MSDS Date:05/31/1995

FSC:6750

NIIN:00-539-9540

MSDS Number: CBSZX

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Inf

o Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/

Information on Ingredients =====

Ingred Name:ORGANO SILICONE

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL:EXPECTED TO BE LOW HAZARD FOR RECOMMENDED HANDLING. EYE:CAUSES IRRIT. SKIN:CAUSES IRRIT. INGEST:EXP

ECTED TO BE LOW INGESTION HAZARD.

Explanation of Carcinogenicity:PER MSDS:PART A,W CONTAIN FORMALDEHYDE [50-00-0] WHICH IS LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.

Effects of Overexposure:EYE/SKIN IRRIT.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHAL:SYMPTOMATIC MOVE TO FRESH AIR.SYMPTOMS PERSIST GET MED ATT. EYES:IMMED FLUSH W/PLENTY OF WATER FOR @LEAST 15 MINS.GET MED

ATTN. SKIN:IMMED REMOVE CONTAMIN CLOTH/SHOES.WASH W/SOAP/PLENTY OF WATER. SYMPTOMS PERSIST GET MED ATTN. INGEST:DRINK 1-2 GLASSES OF WATER.SEEK MED ATTN.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:243F,117C

Autoignition Temp:Autoignition Temp Text:NP

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE (CO2), DRY CHEMICAL, ALCOHOL FOAM.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTH.

Unusual Fire/Explosion Hazard:FIRE OR HIGH TEMPERATURES MAY CAUSE DECOMPOSITION.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB W/VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN CONTAINER FOR CHEMICAL WASTE.CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL CONTAMINATION.CAUTION:CONTAMINATED SURFACES MAY BE SLIPPERY.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage ==

=====

Handling and Storage Precautions:AVOID EYE/SKIN/CLOTH CONTACT.USE
W/ADEQUATE VENTI.KEEP FRM CONTACT W/OXIDIZING MATLS.KEEP AWAY FRM
HEAT.KEEP CNTNR CLSD.

Other Precautions:THIS MATL HAS NOT BEEN TESTED FOR ENVIRONMENTAL
EFFECTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.

Ventilation:USE GOOD GEN VENTI(10 AIR CHANGES/HR).MATCH VENTI RATES
W/CONDITIONS.USE PROCESS ENCLRS,LOC EXHAU VENTI,
OTHER (SUPPLE)

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS, GOGGLES.

Other Protective Equipment:EYEBATH, WASHING FACILITIES, SAFETY SHOWER.

Work Hygienic Practices:WASH CONTAMIN CLOTH BEF REUSE.DESTROY/CLEAN
WELL CONTAMIN SHOES.WASH THOROUGHLY AFT HNDLG.

Supplemental Safety and Health

VENTI:ENGINEER CNTRLS TO MAINTAIN AIRBORNE LEVELS 680F,>360C

Vapor Pres:NEGLIGIBLE

Vapor Density:N/AVAILABL

Spec Gravity:1.04

pH:N/AVAI

Viscosity:NP

Evaporation Rate &

Reference:NP

Solubility in Water:COMPLETE

Appearance and Odor:LIQUID, COLORLESS, ODORLESS.

Percent Volatiles by Volume:100

Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:HOWEVER MATL CAN DECOMPOSE ABOVE 360C
(680F).AVOID TEMPERATURES ABOVE 260C (500F).

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE,
OXIDES OF SILICON.

=====

==== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE/TREAT/DISPO MAY BE SUBJ TO
FED/STATE/LOC LAWS.CONTRACT W/LICENSED CHEM DISPO AGENCY.SEC 313
TITLE III SARA/40CFR372:FORMALDEHYDE,METHANOL (PARTS A,WORK SOLN).

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants thi
s information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.