

HENTZEN COATINGS INC -- SAND ZENTHANE, 686A P/N 08618TUA-GD -- 8010-01-234-2935
===== Product Identification =====

Product ID:SAND ZENTHANE, 686A P/N 08618TUA-GD

MSDS Date:08/31/1995

FSC:8010

NIIN:01-234-2935

MSDS Number: CBTWD

=== Responsible Party ===

Company Name:HENTZEN COATINGS INC

Address:6937 W MILL ROAD

City:MILWAUKEE

State:WI

ZIP:53218-1225

Country:US

Info Phone Num:414-353-4200

Emerge

ncy Phone Num:414-353-4200 800-424-9300(CHEMTREC)

Preparer's Name:JANE FREEMAN

CAGE:09225

=== Contractor Identification ===

Company Name:HENTZEN COATINGS INC

Address:6937 WEST MILL ROAD

Box:18749

City:MILWAUKEE

State:WI

ZIP:53218

Country:US

Phone:414-353-4200

CAGE:09225

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ISOAMYL KETONE SOLVENT

CAS:110-12-3

RTECS #:MP3850000

Fraction by Wt: 20.821%

Other REC Limits:NONE SPECIFIED

OSHA PEL:50 PPM

ACGIH TLV:50

PPM

Ingred Name:TITANIUM DIOXIDE PIGMENT

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 10-15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:10 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:SILICA PIGMENT (SARA 313)

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: 20-30%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.1 MG/M3

ACGIH TLV:0.1 MG/M3

Ingred Name:HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE (HDI)(EXACT PERCENTAGE IS A TRADE SECRET)

CAS:28182-81-2

RTECS #:HQ9170000

Fraction by Wt: 20-30%

Other REC

Limits:MFR.5MG.M3STEL1MG/M3

Ingred Name:AROMATIC HYDROCARBONS (MIXTURE OF C8'S TO C10'S)

CAS:64742-95-6

Fraction by Wt: 1.240%

Other REC Limits:100 PPM = MFR'S

Ingred Name:BUTYL ACETATE SOLVENT

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 1.240%

Other REC Limits:NONE SPECIFIED

OSHA PEL:150 PPM/STEL 200 PPM

ACGIH TLV:150 PPM/STEL 200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:HEXAMETHYLENE DIISOCYANATE MONOMER (SARA 313)

CAS:822-06-0

RTECS #:MO1740000

Fraction by Wt: 0.049%

Ot

her REC Limits:NONE SPECIFIED
OSHA PEL:0.005 PPM
ACGIH TLV:0.005 PPM
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:VM&P NAPHTHA SOLVENT
CAS:8030-30-6
RTECS #:DE3030000
Fraction by Wt: 5.615%
Other REC Limits:NONE SPECIFIED
OSHA PEL:300 PPM
ACGIH TLV:300 PPM

Ingred Name:XYLENE (SARA 313)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 4.776%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/STEL 150 PPM
ACGIH TLV:100 PPM/STEL 150 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VOC: 3.
494 LBS/GAL; 418.686 GRAMS/LITER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CHRONIC: OVEREXPO TO SOLVENTS CAUSE
PERMANENT BRAIN/NERVOUS SYSTEM/LIVER/KIDNEY DAMAGE. OVEREXPO TO
ISOCYANATE LEADS TO RESPIRATORY SENSITIZATION CHARACTERIZED BY
ALLERGIC DERMATITIS WHICH INC
LUDES RA SH, ITCHING, HIVES, SWELLING.
INGEST: IRRIT/CORROSIVE TO MOUTH/STOMAH TISSUE/DIGEST TRACT/SORE
THROAT**
Explanation of Carcinogenicity:BASED UPON LABORATORY ANIMAL DATA, IARC
HAS LISTED SILICA AS A "PROBABLE HUMAN CARCINOGEN."
Effects of Overexposure:SKIN/EYE/RESP TRACT IRRIT (NOSE/THROAT/LUNGS).
WATERING EYES/DRY THROAT/COUGHING/HEADACHE/TIGHT CHEST/BURNING
SENSATION. SOLVENTS EXPOSURE MAY CAUSE HEADACHE/DIZZINESS/NAUSEA.
SHORTNESS OF BREATH. EXP OSURE >LIMITS M

AY LEAD TO

BRONCHITIS/BRONCHIAL SPASM/PULMINARY EDEMA. CHEM/HYPERSENSITIVE
PNEUMONITIS W/FLU-LIKE SYMPTOM

Medical Cond Aggravated by Exposure:SKIN ALLERGIES AND EXEMA, ASTHMA &
OTHER RESPIRATORY AILMENTS, CHEMICAL SENSITIZATION.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. CONSULT
DR. EYES: FLUSH IMMED W/LUKE WARM RUNNING WATER 15 MINUTES, LIFTING
EYELIDS. GET MEDICAL ATTENTION. SKIN: REMO
VE CONTAM CLOTHES/WASH
BEFORE REUSE. USE SAFETY SHOWER AFTER REMOVINGCLOTHES. GET MEDICAL
AID. LESSER EXPOSURE, CONTACT DR IF IRRITATION DEVELOPS/PERSISTS.
INGESTION: CALL DR IMMED. DON'T INDUCE VOMITING.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:54.0F,12.2C
Autoignition Temp:Autoignition Temp Text:NA
Lower Limits:0.9
Upper Limits:8.2
Extinguishing Media:CO2, DRY CHEMICAL, FOAM, ALCOHOL FOAM.
Fire Fighting Procedures:FU
LL PROTECTIVE EQUIPMENT W/SCBA SHOULD BE
WORN. DURING A FIRE, IRRITATING & HIGHLY TOXIC GASES & SMOKE ARE
PRESENT FROM THE DECOMPOSITION/COMBUSTION PRODUCTS.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO EXTREME HEAT
MAY EXPLODE OR BURST WHEN CONTAMINATED W/H2O (CO2 RELEASED). DON'T
WELD, CUT, TORCH DRUMFULL/EMPTY MAY IGNITE/EXPLODE.

=====
Accidental Release Measures
=====

Spill Release Procedures:EVACUATE NON-ESSENTIAL PERSONNEL. REMOVE
IGNIT
SOURCES (FLAMES/HOT SURFACES/ELECTRICAL/STATIC/SPARKS). VENTILATE
AREA.AVOID BREATHING VAPORS. COVER W/INERT ABSORBENT.POUR
DECONTAMINANT/ALLOW TO REACT >10 MIN.COLLECT IN OPEN CNTNR/ADD
MORE DECONTAM***
Neutralizing Agent:3-8% CONCENTRAT AMMONIA/2% DETERGENT/90-95% H2O OR
TERGITOL TNN-10 20%/WATER 80%

=====
Handling and Storage
=====

Handling and Storage Precautions:DON'T STORE >120F OR