

AMERICAN ABRASIVE METALS CO -- NON-SKID DECK COATING EPOXO 2000 X -- 5610-00-006-1550
===== Product Identification =====

Product ID:NON-SKID DECK COATING EPOXO 2000 X

MSDS Date:10/29/1986

FSC:5610

NIIN:00-006-1550

Kit Part:Y

MSDS Number: CCBDG

=== Responsible Party ===

Company Name:AMERICAN ABRASIVE METALS CO

Address:460 COIT ST

City:IRVINGTON

State:NJ

ZIP:07111

Country:US

Info Phone Num:201-37

3-7060

Emergency Phone Num:201-373-7060

CAGE:88444

=== Contractor Identification ===

Company Name:AMERICAN SAFETY TECHNOLOGIES INC

Address:565 EAGLE ROCK AVE

Box:City:ROSELAND

State:NJ

ZIP:07068

Country:US

Phone:973-403-2600

CAGE:88444

===== Composition/Information on Ingredients =====

Ingred Name:BISPHENOL A-EPICHLOROHYDRIN COPOLYMER;(EPOXY RESINS)

CAS:25068-38-6

RTECS #:SL6475000

Fraction by Wt: 12%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:XYLENE (SARA 313) (CERCLA)

CAS:13

30-20-7
RTECS #:ZE2100000
Fraction by Wt: 10%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM; 150 STEL
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:2-PROPANOL, 1-METHOXY-; (PROPYLENE GLYCOL MONOMETHYL ETHER)
CAS:107-98-2
RTECS #:UB7700000
Fraction by Wt: 1%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM; 150 STEL

Ingred Name:SILICA, CRYSTALLINE - QUARTZ; (SILICON DIOXIDE,
CRYSTALLINE)
CAS:14808-60-7
RTECS #:VV7330000
Fraction by Wt: 20%
OSHA PEL:SEE TABLE Z-3
ACGIH TLV:0.1 MG/M3 RDUST

=====
=== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INHAL: DIZZINESS, UNCONSCIOUSNESS.
SKIN: IRRITATION, SENSITIZATION. EYE: IRRITATION, EYE DAMAGE.
Explanation of Carcinogenicity:SILICA, CRYSTALLINE-QUARTZ: IARC MONO,
SUPP. VOL 7, PG 341, 1987: GROUP 2A. NTP 7TH ANNUAL REPORTS ON
CARCINS,
(SUPDAT)
Effects of Overexposure:AS PER HEALTH HAZARDS ABOVE.
Medical Cond Aggravated by Exposure:RESPIRATORY DISEASES, SKIN
CONDITIONS, KIDNEY OR LIVER DISEASE.

=====
==== First Aid Measures =====

First Aid:EYE: FLUSH W/LGE AMTS OF WATER FOR AT LEAST 15 MINUTES. GET
MED ATTN. INHAL: FRESH AIR, OXYGEN, ARTF RESP. SKIN: WASH W/SOAP &
WATER. INGEST: DO NOT INDUCE VOMITING. CALL MD.

=====
==== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:81.0F,27.2C

Lower Limits:1%

Upper Limits:12%

Extinguishing Media:CHEMICAL FOAM OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard:VAPORS ARE HVR THAN AIR; MAY TRAVEL ALONG GROUND AND BE IGNITED BY FLAMES, SPARKS OR OTHER IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES (FLAMES,

FLARES, PILOT LIGHTS, ELECTRICAL SPARKS).

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:WARNING! IRRITANT: DO NOT GET INTO EYES. AVOID CONTACT W/SKIN & CLTHG. AVOID INHAL OF VAPS/MIST. USE W/ADEQ VENT.

Other Precautions:CAUTION: WHEN REMOVING OLD COATING BY SANDING OR SANDBLASTING, WEAR PROPER NIOSH/MSHA APPRVD DUST MASKS TO AVOID INHALATION OF SILICA DUST. AVOID EXTREME

HEAT - KEEP AWAY FROM

FLAME. DO NOT EXCEED 110 F IN STORAGE AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV'S ARE EXCEEDED, NIOSH/MSHA APPROVED SCBA.

Ventilation:LOCAL EXHAUST: SUFFICIENT TO MAINTAIN LEVEL. MECH: BELOW TLV.

Protective Gloves:RUBBER/BUNA N GLOVES.

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGS.

Other Protective Equipment:EMERGENCY EYEWASH & DELUGE SHOWER MEETING ANSI DESIGN CRITERIA. PROTECTIVE CLOTHING.

Work H

ygienic Practices:WASH THORO AFTER HANDLING & BEFORE EATING, DRINKING OR SMOKING. REMOVE CONTAMD CLOTHING AND WASH BEFORE RE-USE.

Supplemental Safety and Health

EXPLAN OF CARCINS: 1994: ANTICIPATED TO BE CARCINOGEN.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>240F,>116C

Vapor Pres:8 @ 20C

Vapor Density:3.7

Spec Gravity:2.1(H*20=1)

Evaporation Rate & Reference:0.7 (BUAC=1)

Solubility in Water:SLIGHT

Appearance and Odor:VISCOUS PASTE, MI

LD ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG ACID, ALKALIES, AMINES, OXIDIZING AGENTS.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: CO*2, CO & TOXIC FUMES WHEN BURNING.

===== Disposal Considerations =====

Waste Disposal Methods: ABSORB ON SAND, CLAY OR OTHER ABSORBANT MATERIAL AND SHOVEL INTO CONTAINERS. DISPOSE BY CONTROLLED BU

RNING OR

AUTHORIZED LANDFILL. DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.