

EAGLE-PICHER INDUSTRIES INC -- CAREFREE RECHARGABLE BATTERY -- 6140-01-152-3995

=====
Product Identification
=====

Product ID:CAREFREE RECHARGABLE BATTERY
MSDS Date:03/12/1991
FSC:6140
NIIN:01-152-3995
MSDS Number: CCBGL
=== Responsible Party ===
Company Name:EAGLE-PICHER INDUSTRIES INC
Address:BETHEL ROAD
Box:130
City:SENECA
State:MO
ZIP:64865
Country:US
Info Phone Num:417-776-2256
Emergency P
hone Num:417-776-2256
CAGE:0B3X4
=== Contractor Identification ===
Company Name:EAGLE-PICHER INDUSTRIES INC
Address:14212 BETHEL ROAD
Box:130
City:SENECA
State:MO
ZIP:64865
Country:US
Phone:417-776-2256
CAGE:0B3X4

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD (SARA 313) (CERCLA)
CAS:7439-92-1
RTECS #:OF7525000
Fraction by Wt: 50%
OSHA PEL:SEE 1910.1025
ACGIH TLV:0.15MG/M3 DUST
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:LEAD; (LEAD OXIDES) (SARA 313)

(CERCLA)
CAS:7439-92-1
RTECS #:OF7525000
Fraction by Wt: 25%
OSHA PEL:SEE 1910.1025
ACGIH TLV:0.15MG/M3 DUST
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:SULFURIC ACID; (38% SULFURIC ACID, 1.28 S.G.) (SARA
302/313) (CERCLA)
CAS:7664-93-9
RTECS #:WS5600000
Fraction by Wt: 18%
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3/3 STEL
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Ent
ry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:SEVERE BURNS AND EYE DAMAGE FROM
SULFURIC ACID ELECTROLYTE. ILLNESS FROM SULFUR OXIDE FUMES. SIGNS &
SYMPS:IRRITATION AND ACID BURNS. PUNGENT ODOR AND RESPIRATORY
IRRITATION. CHRONIC:LEAD APPEARS ON N AVY OCCUPATIONAL CHEMICAL
REPRODUCTIVE HAZARDS LIST. SEEK CONSULTATION FROM APPROPRIATE
HEALTH (EFTS OF OVEREXP)
Explanation of Carcinogenicity:SUL
FURIC ACID:IARC MONOGRAPHS ON EVAL OF
CARCIN RISK OF CHEMS TO MAN, VOL 54, PG 41, 1992:GROUP 1.
ANIMAL:PULM IRRIT.
Effects of Overexposure:HLTH HAZS:PROFESSIONALS CONCERNING LATEST
HAZARD LIST INFORMATION AND SAFE HANDLING AND USE INFORMATION .
Medical Cond Aggravated by Exposure:NOT APPLICABLE.

=====
===== First Aid Measures =====

First Aid:EYES:IMMEDIATELY FLUSH W/POTABLE WATER FOR A MINIMUM OF 15
MINUTES, SEEK ASSISTANCE FROM MD . INHALATION:F

OR SULFUR OXIDE

FUMES, DISCONNECT BATTERIES, EVACUATE AND VENTILATE. SKIN:FLUSH AREAS CONTAMINATED BY SULFURIC ACID ELECTROLYTE WITH WATER. INGESTION:DRINK LARGE QUANTITIES OF WATER OR MILK, FOLLOWED BY MILK OF MAGNESIA, BEATEN EGGS OR VEGETABLE OIL.

===== Fire Fighting Measures =====

Extinguishing Media:WATER, FOAM, DRY.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . NOT APPLICABLE.

Unusual Fire/Explosion

Hazard:KEEP LIGHTED CIGARETTES, SPARKS AND FLAMES AWAY. EXPLOSION CAN RESULT FROM IMPROPER CHARGING AND IGNITION OF CHARGING GASES & IF CHARGED IN GAS TIGHT ENCLOSURES.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID CONTACT WITH SULFURIC ACID ELECTROLYTE FROM BATTERY. FLUSH WITH WATER.

Neutralizing Agent:NEUTRALIZE WITH SOLUTION OF BAKING SODA IN WATER.

===== Handling and Storage =====

Handling

and Storage Precautions:BATTERIES WITH RELEASED ELECTROLYTES SHALL BE SEALED IN POLYETHYLENE BAGS. KEEP BATTERIES AWAY FROM CHILDREN.

Other Precautions:DO NOT CRACK BATTERY CASES. DO NOT OVERCHARGE. DO NOT SHORT CIRCUIT BATTERY TERMINALS. KEEP LIGHTED CIGARETTES, SPARKS, AND FLAMES AWAY FROM CHARGING BATTERIES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

NOT APPLICABLE.

Ventilation:OTHER:NATURAL CONVECTION.

Protective Gloves:USE RUBBER GLOVES IF CASE IS CRACKED.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGLES .

Other Protective Equipment:ANSI APPROVED EMERGENCY EYE WASH AND DELUGE SHOWER . NOT APPLICABLE.

Work Hygienic Practices:NOT APPLICABLE.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:C3

Appearance and Odor:NOT APPLICABLE.

===== St

ability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

SOLVENTS MAY DISSOLVE BATTERY CASE MATERIAL.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: SEVERE OVERCHARGE AND OVERHEATING MAY CAUSE SULFUR OXIDE FUMES.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSAL MUST BE I/A/W FEDERAL, STATE & LOCAL REGULATIONS . DISPOSE WITH AUTOMOTIVE BATTERY SCRAP. DO NOT

INCINERATE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.