

AKRON PAINT AND VARNISH INC -- WALKWAY DARK GULL GRAY G-8130 -- 8010-00-641-0426

=====
Product Identification
=====

Product ID:WALKWAY DARK GULL GRAY G-8130
MSDS Date:04/10/1995
FSC:8010
NIIN:00-641-0426
MSDS Number: CCJWG
=== Responsible Party ===
Company Name:AKRON PAINT AND VARNISH INC
Address:1390 FIRESTONE PARKWAY
City:AKRON
State:OH
ZIP:44301-1624
Country:US
Info Phone Num:216-773-8911
Emer
gency Phone Num:216-773-8911
CAGE:70228

=== Contractor Identification ===
Company Name:AKRON PAINT AND VARNISH INC
Address:1390 FIRESTONE PARKWAY
City:AKRON
State:OH
ZIP:44301-1624
Country:US
Phone:216-773-8911
CAGE:70228

=====
Composition/Information on Ingredients
=====

Ingred Name:CRYSTALLINE SILICA (CHRONIC HEALTH EFFECTS POSSIBLE IF
INHALED AS A DUST).
CAS:14808-60-7
RTECS #:VV7330000
Fraction by Wt: 41.16%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.1 MP/F3
ACGIH TLV

:0.1 MP/F3

Ingred Name:VM&P NAPHTHA RULE 66 (VP = 15 @ 100F)

CAS:64742-89-8

Fraction by Wt: 29.33%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:VOC = 3.19

RTECS #:9999999VO

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chro

nic:EYES: CAN CAUSE

REDNESS,IRRIT,SWELLING,BLURRED VISION. SKIN:PROLONGED/REPEATED CONTACT CAN CAUSE MODERATE IRRIT, DEFATTING, DERMATITIS.

BREATHING:EXCESSIVE INHALATION OF VAPORS AND/OR SPRAY MIST CAN CAUSE RESPIRATORY IRRITATION,

DIZZINESS/WEAKNESS/FATIGUE/NAUSEA/HEADACHE/UNCONSCIOUSNESS.

Explanation of Carcinogenicity:LIMITED EVIDENCE OF CARCINOGENICITY TO HUMANS IARC CLASS 2A.

Effects of Overexposure:ASPHYXIATION. INGEST: GASTROINTESTINAL IRRITATION/NAUSEA/VOMIT

ING/DIARRHEA. ASPIRATION OF MATERIAL INTO

LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

===== First Aid Measures =====

First Aid:EYES:FLUSH W/LRG AMTS WATER 15 MIN.LIFT LIDS, GET IMMED MED AID.SKIN:WASH W/SOAP/WATER REMOVE CONTAM CLOTHES WASH BEFORE REUSE.CONSULT DR.IF IRRIT PERSISTS.INGEST:DON'T INDUCE VOMITING.CAN CAUSE CHEM PNEUMONITIS/CAN BE FATAL.GIVE 1-2 GLASSES WATER TO DILUTE.INHAL:GET FRESH AIR.IF TROUBLE BREATHING G

IVE OXYGEN.IF

BREATHING STOPS GIVE ARTIF RESP.KEEP WARM/QUIET.GET MED AID.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:52F0F,10.0C

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG. USE WATER FOR COOLING MATERIAL IN VICINITY OF FIRE.

Fire Fighting Procedures:USE SCBA W/A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE. WEAR PROTECTIVE CLOTHING

Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR, TRAVEL ALONG GROUND TO IGNITION SOURCE SOME DISTANCE FROM HANDLING POINT. IGNITION SOURCES:PILOT LIGHTS/SMOKING/HEATERS/ELECTRIC*

===== Accidental Release Measures =====

Spill Release Procedures:SMALL:ABSORB

W/RAGS/ABSORBENT/VERMICULITE/OTHER; TRANSFER TO HOOD.

LARGE:ELIMINATE IGNIT SOURCES. DIKE AREA-PREVENT SPREADING.

VENTILATE INDOOR AREA. PUMP LIQUID INTO SALVAGE TANK REMAINING LIQU

ID TAK EN UP W/SAND/ABSORB/OTHER. SHOVEL **

===== Handling and Storage =====

Handling and Storage Precautions:DON'T DROP CNTNRS.NO HEAT/SPARKS/OPEN FLAME.STORE LRG QTY IN BLDG COMPLY W/OSHA 1910.106.DONT PRESSURE TO EMPTY.NO BREATHE SAND DUST.READ MFG PRECAUTN

Other Precautions:*MOTORS/ELEC SWITCH SPARKS/STATIC DISCHARGE.NO TORCH-CUT EMPTY CNTNRS.VAPORS IN EMPTY CNTNR MAY EXPLODE.APPLIC TO HOT SURFACES-SPECIAL PRECAUS.DURING EMERG COND OVEREXP
OSE TO DECOMP

PRODS-HEALTH HAZAR D.SYMPTS NOT IMMED APPARENT.GET MED AID.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:UNRESTRICTED VENTILATION APPROVED

CHEMICAL/MECHANICAL FILTERS DESIGNED TO REMOVE COMBINATION OF PARTICULATES/VAPOR. IN CONFINED AREAS, APPROVED AIR LINE TYPE RESPIRATORS/HOODS.

Ventilation:SUFFICIENT VENT TO KEEP AIR

Spec Gravity:1.34934

Evaporation Rate & Reference:6.87 (N-BUTYL ACETATE)

Appearance and Odor:DAR

K GULL GRAY LIQUID
Percent Volatiles by Volume:50.7

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
AVOID CONTACT WITH STRONG OXIDIZERS (EG: NITRIC ACID).
Stability Condition to Avoid: KEEP AWAY FROM HEAT AND OPEN FLAME.
Hazardous Decomposition Products: MAY FORM CARBON MONOXIDE AND DIOXIDE,
VARIOUS HYDROCARBONS, ETC.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORD
ANCE W/LOCAL, STATE AND
FEDERAL REGULATIONS. **INTO CNTNRS. PREVENT RUN-OFF TO
SEWERS/BODIES OF WATER. NOTIFY PROPER AUTHORITIES AS REQUIRED BY
LOCAL, STATE AND FEDERAL REGULATIONS .

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability f
or its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.