

NILES CHEMICAL PAINT CO -- N-6515A DK. GRAY R=3. 6: COMP. B -- 8010-01-380-2359

=====
Product Identification
=====

Product ID:N-6515A DK. GRAY R=3. 6: COMP. B

MSDS Date:01/12/1996

FSC:8010

NIIN:01-380-2359

Kit Part:Y

MSDS Number: CCKLX

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-3377

Emergency Phone Num:219-236-5856

Preparer's Name:MIKE LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====
Composition/Information on Ingredients
=====

Ingred Name:EPOXY RESIN

CAS:25068-38-6

RTECS #:KC2100000

Fraction by Wt: 45.0%

Other REC Limits:NONE RECOMMENDED

Ingred Name:TALC

CAS:14807-96-6

RTECS #:MW2700000

Fra

ction by Wt: 34.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:PROPRIETARY INGREDIENTS (MFR STATES UNIDENTIFIED
INGREDIENTS NOT CONSIDERED HAZARDOUS UNDER FEDERAL HAZARD COMM
REGS)

Fraction by Wt: BALANCE
Other REC Limits:NONE RECOMMENDED

Ingred Name:#100 SOLVENT (VP = 4.4 @ 20C)
CAS:64742-95-6
Fraction by Wt: 18.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.
ACGIH TLV:50 PPM

Ingred Name:POLYAMIDE
Fraction by Wt: 1.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC = 2.08
LBS/GL
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE:SEVERE
IRRIT,LACRIMATION,REDNESS,BLURRED VISION. SKIN:REDNESS & IRRIT,
DEFATTING LEADING TO DERMATITIS. INHAL:NASAL & RESPIRATORY IRRIT.
CNS DEPRESSION (DIZZY,DROWSY,WEAK,FATIGUE,CONFUSION) NA
USEA ,
HEADACHE, VERTIGO, UNCONSCIOUSNESS, ASPHYXIATION. INGEST:GI IRRIT,
ABDOMINAL PAIN, NAUSEA, VOMITTING, DIARRA.
Effects of Overexposure:DUST MAY CAUSE PNUEMOCONIOSIS & PLEURAL
THICKENING.TARGET ORGANS: LUNGS.
Medical Cond Aggravated by Exposure:NONE KNOWN

===== First Aid Measures =====

First Aid:INHAL: MOVE TO FRESH AIR IMMED. IF BREATH STOPPED, GIVE ARTIF
RESP. GET MED AID ASAP. SKIN: IMMED FLUSH W/PLENTY WATER. IF MAT'L
PENETRAT

ES CLOTH, IMMEDIATELY REMOVE CONTAMINATED CLOTHING & FLUSH SKIN WITH WATER. GET MEDICAL AID. EYE: IMMEDIATELY FLUSH WITH WATER AT LEAST 15 MINUTES, LIFTING LIDS. GET MEDICAL AID IMMEDIATELY. INGEST: DRINK 1-2 GLASSES OF WATER, DO NOT INDUCE VOMITING. CALL DRUG/POISON CONTROL IMMEDIATELY. TREAT SYMPTOMATICALLY.

===== Fire Fighting Measures =====

Flash Point Method: TCC

Flash Point: 113F, 45C

Autoignition Temp: Autoignition Temp Text: NE

Lower Limits: 1.0

Upper Limits: 0.0

Extinguishing Media: DRY CHEMICAL, FOAM, CO2

Fire Fighting Procedures: WEAR SCBA WITH FULL FACEPIECE (POSITIVE PRESSURE MODE) & FULL PROTECTIVE CLOTHING. USE WATER TO COOL CLOSED CONTAINER TO PREVENT PRESSURE BUILDUP/AUTO IGNITION/EXPLOSION WITH HEAT.

Unusual Fire/Explosion Hazard: KEEP CONTAINER CLOSED. VAPOR HEAVY, TRAVEL ON GROUND TO IGNITION. KEEP FROM HEAT/IGNITION. CLOSED CONTAINER EXPLODES WITH HEAT. APPLICATION TO HOT SURFACES REQUIRE SPECIAL CAUTION. DECOMPOSITION PRODUCT-HEALTH HAZARD.

===== Accidental Release Measures =====

Spill Release Procedures: ELIMINATE

IGNITION SOURCES. MINIMIZE BREATHING

VAPOR/AVOID SKIN CONTACT. ABSORB WITH INERT MATERIAL (CLAY, SOIL, COMMERCIAL ABSORBENT). SMALL: SHOVEL RECLAIMED LIQUID/ABSORBENT INTO

RECOVERY/SALVAGE DRUMS. LARGE: DIKE. RECLAIM INTO RECOVERY/SALVAGE DRUMS OR TANK TRUCK.

===== Handling and Storage =====

Handling and Storage Precautions: AVOID STORAGE IN HIGH TEMPERATURE AREAS OR NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE. AVOID ROUGH HANDLING.

Other Precautions: CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTY. DO NOT WELD OR FLAME CUT ON EMPTY DRUMS. SHOCK FROM DROPPING MAY SPLIT CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: WEAR APPROPRIATE (TYPE TC-23C-75) FITTED HALF-MASK OR FULL FACEPIECE RESPIRATOR DURING/AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR LEVELS BELOW APPLICABLE LIMITS. FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS

FOR USE.
Ventilation:KEEP CONCEN