

SHELL OIL COMPANY -- ISOPROPYL ALCOHOL -- 6810-00-286-5435

=====
Product Identification
=====

Product ID:ISOPROPYL ALCOHOL

MSDS Date:11/04/1991

FSC:6810

NIIN:00-286-5435

MSDS Number: CCLQP

=== Responsible Party ===

Company Name:SHELL OIL COMPANY

Address:CORPORATE ENVIRONEMNTAL AFFAIRS

Box:4320

City:HOUSTON

State:TX

ZIP:77210

Country:US

Info Phone Num:713-241-2252

Emergency Phone Num:713-473-945

1

CAGE:SHELL

=== Contractor Identification ===

Company Name:HOC INDUSTRIES, INC

Address:3511 N. OHIO

Box:2609

City:WICHITA

State:KS

ZIP:67219

Country:US

Phone:316-838-4663

CAGE:0A9L8

Company Name:SHELL OIL COMPANY PRODUCT SAFETY AND COMPLIANCE

Address:P.O. BOX 4320

Box:4320

City:HOUSTON

State:TX

ZIP:77210

Phone:713-241-2252 /713-241-4819

CAGE:SHELL

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA 313)

CAS:67-63-0

RTECS #:NT8050000

Fractio

n by Wt: 100%
Other REC Limits:NONE SPECIFIED
OSHA PEL:400 PPM
ACGIH TLV:400 PPM/500STEL;9596

=====
Hazards Identification
=====

LD50 LC50 Mixture:ORAL LD50 (RAT) = 5840 MG/KG
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: OVEREXPOSURE MAY LEAD TO
CENTRAL NERVOUS SYSTEM DEPRESSION, LEADING TO HEADACHES AND
DIZZINESS. EYE: MAY LEAD TO IRRITATION AND WILL
INJURE EYE TISSUE
IF NOT REMOVED PROMPTLY. SKIN: MAY LEAD TO DERMATITIS. INGESTION:
MAY LEAD TO VOMITING. CHRONIC: PROLONGED SKIN CONTACT MAY CAUSE
DERMATITIS.
Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT
CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT
CARCINOGENS.
Effects of Overexposure:OVEREXPOSURE MAY LEAD TO DIZZINESS, HEADACHES,
DERMATITIS AND EYE IRRITATION. HIGH VAPOR CONCENTRATIONS ARE
ANESTHETIC AND MAY HAVE OTHE
R CENTRAL NERVOUS SYSTEM EFFECTS.
Medical Cond Aggravated by Exposure:PERSONS WITH SKIN, HEART,
RESPIRATORY, OR ANY OTHER MEDICAL CONDITION SHOULD USE CAUTION WHEN
HANDLING OR USING THIS PRODUCT.

=====
First Aid Measures
=====

First Aid:SKIN: IMMEDIATELY FLUSH WITH SOAP AND WATER. GET MEDICAL
ATTENTION IF NECESSARY. INHALATION: IMMEDIATELY REMOVE VICTIUM TO
FRESH AIR. GIVE CPR IF BREATHING IS STOPPED. GET MEDICAL ATTENTION.
EYE: IMME DI
ATELY FLUSH WITH WATER FOR 15 MINUTES.GET MEDICAL
ATTENTION. INGESTION: GET PROMPT MEDICAL ATTENTION. DO NOT INDUCE
VOMITING. KEEP AT REST.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:=11.7C, 53.F
Lower Limits:2.0
Upper Limits:12.0
Extinguishing Media:WATER FOG, "ALCOHOL" FOAM, DRY CHEMICAL OR CO2.
Fire Fighting Procedures:CLEAR FIRE AREA OF UNPROTECTED PERSONNEL. DO
NOT ENTER CONFINED AREA W/OUT FULL BUNKER GEAR AND NIOSH

SCBA. COOL

FIRE EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRESSURE BUILDUP WHICH CAN CAUSE RUPTURE. COOL WITH WATER.

===== Accidental Release Measures =====

Spill Release Procedures:MINOR: ABSORB MATERIAL WITH CLAY, VERMICULITE, OR SIMILAR ABSORBENT MATERIAL. PLACE IN DISPOSAL CONTAINERS. MAJOR: DIKE & CONTAIN SPILL. ELIMINATE SOURCES OF IGNITION. SHUT OFF LEAKS. REMOVE LIQUID BY VACUUM OR ABSORBENT. FLUSH RESIDUE WITHWATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:USE ONLY IN WELL VENTILATED WORK AREA. KEEP CONTAINERS CLOSED WHEN NOT IN USE. FLAMMABLE LIQUID; EMPTY CONTAINERS CAN CONTAIN LIQUID/VAPOR RESIDUE.

Other Precautions:DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXOPSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. EXPLOSION HAZARD. EMPTY DRUMS SHOULD BE C COMPLETELY DRAINED, BUNGED & DISPOSED OF.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR. AIR-SUPPLIED OR FILTERING TYPE WITH ORGANIC VAPOR CARTRIDGES ARE RECOMMENDED.

Ventilation:LOCAL AND MECHANICAL EXHAUST RECOMMENDED. AVOID OPEN ELECTRICAL SOURCES NEAR PRODUCT VAPOR A REAS.

Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD

Other Protective Equipment:SAFETY SHOES, EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT. WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK AREA.

Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:="

82.2C, 180.F

Melt/Freeze Pt:=-88.3C, -127.F

Vapor Pres:33

Vapor Density:2.1

Spec Gravity:0.79

Evaporation Rate & Reference:1.4 N-BUTYL ACETATE

Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS,MOBIL LIQUID,MILD ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, ALUMINUM EQUIPMENT FOR STORAGE AND HANDLING.

Stability Condition to Avoid:HEAT, SPARKS, FLAME AND CON

TACT WITH

STRONG OXIDIZING AGENTS. KEEP TEMPS. BELOW 120F AND AWAY FROM
ALUMINUM PRODUCTS.

Hazardous Decomposition Products:CARBON MONOXIDE AND UNIDENTIFIED
ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ALL WASTE IN ACCORDANCE WITH LOCAL,
STATE AND FEDERAL REGULATIONS. INCINERATION IS RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies):

Th

is information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.