

US BUREAU OF MINES, HELIUM OPNS -- HELIUM -- 6830-00-660-0027

=====  
Product Identification  
=====

Product ID:HELIUM

MSDS Date:07/14/1993

FSC:6830

NIIN:00-660-0027

MSDS Number: CCMJD

=== Responsible Party ===

Company Name:US BUREAU OF MINES, HELIUM OPNS

Address:1100 S FILLMORE ST

City:AMARILLO

State:TX

ZIP:79101-4318

Country:US

Info Phone Num:806-376-2638

Emergency Phone Num:806-376-2638

CAGE:0JB

D1

=== Contractor Identification ===

Company Name:US BUREAU OF MINES, HELIUM OPNS

Address:1100 S FILLMORE ST

Box:City:AMARILLO

State:TX

ZIP:79101-4318

Country:US

Phone:806-376-2638

CAGE:0JBD1

=====  
Composition/Information on Ingredients  
=====

Ingred Name:HELIUM

CAS:7440-59-7

RTECS #:MH6520000

Fraction by Wt: >99%

Other REC Limits:NONE RECOMMENDED

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:NOT GIVEN

Routes of Entry: Inhalation:YES

Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NON-TOXIC. SIMPLE ASPHYXIANT. IN

CLOSED AREAS NON-FLAMMABLE GAS CAN DISPLACE OXYGEN. IF ATMOSPHERIC OXYGEN CONTENT DROPS BELOW 18% ASPHYXIATION CAN OCCUR. CONTACT WITH LIQUID OR COLD GAS PRODUCED CAN CAUSE FREEZE BURNS.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS

Effects of Overexposure:SYMPTOMS CAN INCLUDE FROSTBITE, PANTING, GASPING, FAST PULSE, CLUMSINESS, BLUISH FINGERNAILS AND/OR LIPS, CONFUSION, DIZZINESS, FATIGUE, NAUSEA, VOMITING, COLLAPSE AND CONVULSIONS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:INHALATION- (CAUTION! RESCUERS MUST SEE TO THEIR OWN SAFETY. USE SELF-CONTAINED BREATHING EQUIPMENT TO ENTER AREAS OF LOW OX

YGEN.) REMOVE VICTIM TO FRESH AIR. QUICKLY RESTORE OR SUPPORT BREATHING AS NEEDED. GIVE OXYGEN IF AVAILABLE. GET MEDICAL ATTENTION FOR VICTIM. SKIN/EYES-PROMPTLY FLUSH AREA WITH LUKEWARM WATER. DO NOT APPLY HEAT. APPLY LOOSE, DRY, STERILE DRESSING. GET MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:USE EXTINGUISHERS SUITED TO SURROUNDING FIRE.

Fir

e Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL TANKS AND CONTAINERS EXPOSED TO FIRE WITH WATER.

Unusual Fire/Explosion Hazard:DEWARS MAY BURST WHEN HEATED.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:CLEAR PEOPLE FORM AREA UNTIL A SAFE OXYGEN LEVEL CAN BE ASSURED. NOTIFY SAFETY PERSONNEL IMMEDIATELY. EMERGENCY WORKERS NEED SELF-CONTAINED BREATHING APPARATUS. PAINT

SOAP SOLUTION AROUND SUSPECTED LEAK TO SEE IF BUBBLES FORM, INDICATING A LEAK.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions: STORE IN A COOL, DRY, WELL-VENTILATED AREA WITH LOW RISK OF FIRE AND AWAY FROM COMBUSTIBLE OR CORROSIVE CHEMICALS.

Other Precautions: PROTECT CONTAINERS FROM PHYSICAL DAMAGE AND FROM HEAT OVER 125F. COVER VALVE WITH CAP WHEN NOT IN USE. PROTECT COMPRESSED

MPRESSED

GAS CYLINDERS AGAINST FALLING, BUMPING OR SUDDEN BLOWS. WEAR SAFETY SHOES WHEN HANDLING COMPRESSED GAS CYLINDERS.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection: PROVIDE AIR-SUPPLIED OR SELF-CONTAINED BREATHING EQUIPMENT FOR WORKERS IN EMERGENCY OR NON-ROUTINE SITUATIONS WHERE OXYGEN LEVEL IS UNSAFE. USE A SAFETY LINE AND A STAND-BY WORKER WHEN A WORKER WITH A RESPIRATOR MUST ENTER AN EMERGENCY AREA

Ventilation: MAINTAIN A

AT LEAST 19% OXYGEN IN AIR.

Protective Gloves: NONE NORMALLY REQUIRED.

Eye Protection: NONE NORMALLY REQUIRED.

Other Protective Equipment: SAFETY SHOES ARE RECOMMENDED FOR HANDLING GAS CYLINDERS.

Work Hygienic Practices: WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

CHECK FOR LEAKS IN COMPRESSED GAS EQUIPMENT BEFORE USE IN CONFINED SPACES.

=====  
===== Physical/Chemical Properties =====

=====

HCC: G3

Boiling Pt: B.P. Text: -452F, -269C

Melt/Freeze Pt: M.P/F.P Text: -458F, -272C

Decomp Temp: Decomp Text: NOT GIVEN

Vapor Pres: NOT GIVEN

Vapor Density: 0.138

Spec Gravity: NOT GIVEN

Evaporation Rate & Reference: GAS

Solubility in Water: NOT GIVEN

Appearance and Odor: COLORLESS, ODORLESS CRYOGENIC LIQUID

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

CARBON STEEL

Stability Condition to Avoid: MOISTURE

Hazardous Decomposition Pr

Products:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:MOVE LEAKING CYLINDER OUTDOORS OR TO AN EXHAUST HOOD WITH GOOD FORCED VENTILATION. ALLOW GAS TO VENT AT A MODERATE RATE. TAG CYLINDER AS DEFECTIVE AND MARK DEFECT. WHEN EMPTY CLOSE VALVE AND RETURN TO SUPPLIER. FOLLOW ALL STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.