

GC THORSEN -- RED X CORON A DOPE, 10-5002 -- 8040-00-779-2863

=====
Product Identification
=====

Product ID:RED X CORON A DOPE, 10-5002
MSDS Date:08/02/1993
FSC:8040
NIIN:00-779-2863
MSDS Number: CCSTP
=== Responsible Party ===
Company Name:GC THORSEN
Address:1801 MORGAN ST
City:ROCKFORD
State:IL
ZIP:61105-1209
Country:US
Info Phone Num:815-968-9661
Emergency Phone Num:800-424-9300(CHEMTREC)
Prep
arer's Name:M WINSEL
CAGE:EO177
=== Contractor Identification ===
Company Name:GC THORSEN
Address:1801 MORGAN STREET
Box:City:ROCKFORD
State:IL
ZIP:61105
Country:US
Phone:815-968-9661
CAGE:72653
Company Name:GC THORSEN
Address:1801 MORGAN STREET
Box:1209
City:ROCKFORD
State:IL
ZIP:61105-1209
Country:US
Phone:815-968-9661
CAGE:EO177

=====
Composition/Information on Ingredients
=====

Ingred Name:LIGROINE; (VM&P NAPHTHA)
CAS:8032-32-4
RTECS #:OI6180000
Fraction by Wt: 34%
OSHA P

EL:300 PPM
ACGIH TLV:300 PPM

Ingred Name:XYLENE (SARA 313) (CERCLA)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 15%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150STEL
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA 313)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 1.5%
OSHA PEL:400 PPM
ACGIH TLV:400 PPM/500STEL

Ingred Name:IRON (III) OXIDE; (POLYESTER RESIN/IRON OXIDE)
CAS:1309-37-1
RTECS #:NO7400000
Fraction by Wt: 49%
OSHA PEL:10 MG/M3 (FE)
ACGIH TLV:5MG(FE)/M3FUM
E

Ingred Name:VOLATILE ORGANIC COMPOUND:505 GMS/L
RTECS #:9999999VO
OSHA PEL:N/K
ACGIH TLV:N/K

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INFLAMMATION OF MUCOUS MEMBRANES AND
RESPIRATORY TRACT, DERMATITIS, BREATHING DIFFICULTY, LOSS OF
APPETITE, NAUSEA, VOMITING, HEADA

CHE, DIZZINESS, UNCOORDINATION,
NARCOSIS, PARTIAL PARALYSIS. (PERSONS WITH DISEASE OF THE LIVER,
KIDNEYS, BLOOD OR NERVOUS SYSTEM).

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:PERSONS WITH DISEASE OF THE LIVER,
KIDNEYS, BLOOD OR NERVOUS SYSTEM.

=====
===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER FOR AT LEAST 15 MINUTES-CONSULT
PHYSICIAN. SKIN:WASH WITH SOAP AND WATER. INHALATION:FRESH AIR,
OXYGEN, ARTIFICIAL RESPIRATION. INGESTION:DO NOT INDUCE
VOMITING-GASTRIC LAVAGE-CONSULT PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:OC

Flash Point:50.0F,10.0C

Lower Limits:2%

Upper Limits:12%

Extinguishing Media:CO₂, CHEMICAL FOAM, DRY CHEMICAL.

Fire Fighting Procedures:WEAR NIOSH APPROVED SCBA & FULL PROTECTIVE
EQUIPMENT . WATER MAY BE INEFFECTIVE EXCEPT FOR COOLING CONTAINERS.

Unusual

Fire/Explosion Hazard:DUE TO FLASH POINT-CONTAINERS MAY EXPLODE
UNDER HIGH HEAT OR FIRE CONDITIONS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA (AVOID BREATHING VAPORS). PICK
UP WITH AN INERT ABSORBENT MATERIAL. STORE IN SEALED METAL
CONTAINERS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM HEAT OR IGNITION SOURCES.

Other Precautions:PROVIDE GOOD VENTILATION.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED SCBA.

Ventilation:LOCAL EXHAUST. MECHANICAL AS REQUIRED TO MEET TLV'S.

Protective Gloves:RUBBER GLOVES.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGLES .

Other Protective Equipment:ANSI APPROVED EMERGENCY EYE WASH AND DELUGE
SHOWER . RUBBER APRON AS REQUIRED.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental

Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:230F,110C

Vapor Density:4.0

Spec Gravity:1.0

Solubility in Water: