View NSN Online: https://aerobasegroup.co.il/nsn/7930-01-412-1017

MAINTEX INC. -- LIME GO (HEAVY DUTY PHOSPHORIC) -- 7930-01-412-1017

Product ID:LIME GO (HEAVY DUTY PHOSPHORIC) MSDS Date:09/08/1995 FSC:7930 NIIN:01-412-1017 **MSDS Number: CDHLB** === Responsible Party === Company Name: MAINTEX INC. Address:13300 NELSON AVE. City:CITY OF INDUSTRY State:CA ZIP:91746 Country:US Info Phone Num:818-961-1988 Emergency Phone Num:800-255 -3924 Preparer's Name: ALI ABYANE CAGE:NO277 === Contractor Identification === **Company Name: MAINTEX INC** Address:13300 NELSON AVE Box:City:CITY OF INDUSTRY State:CA ZIP:91746 Country:US Phone:818-961-1988 CAGE:0AWE2 Company Name: MAINTEX INC. Address:3614 EL MONTE AVE Box:City:EL MONTE State:CA ZIP:91731 Phone:213-283-7380 CAGE:NO277

Ingred Name:PHOSPHORIC ACID (SARA 313) (CERCLA) CAS:7664-38-2 RTECS #:TB6300000 Fraction by Wt: 25-30% Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT EST. ACGIH TLV:1 MG/M3 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:ETHYLENE GLYCOL (SARA 313) (CERCLA) CAS:107-21-1 RTECS #:KW2975000 Fraction by Wt: 1-4% Other REC Limits:NONE RECOMMENDED ACGIH TLV:C 50 PPM,VAPOR; 9495 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: IRRIT/POSSIBLE BURNS DEPENDING ON LENGTH CONTACT. SKIN: CHRONIC: MAY CAUSE IRRIT/POSSIBLE BURNS. INHAL: IRRIT/BURNS W/EXTENDED CONTACT. BREATHING HIGH CONCENTRATIONS VAPOR MISTS/SPRAY COMPOUND MA Y CAUSE IRRIT. INGESTION: MAY CAUSE BURNS TO MOUTH. IRRITATES THROAT/ESSOPHAGUS/DIGESTIVE TRACT. MAY RESULT IN NAUSEA/* Effects of Overexposure:*VOMITING. CHRONIC: MODERATELY TOXIC BY INGESTION/REPEATED INHALATION. CAUSES BURNS TO EXPOSED TIS SUE

W/CHRONIC CONTACT.

First Aid:EYES: IMMEDIATELY FLUSH W/PLENTY OF WATER >15 MINUTES. CALL DR. SKIN: WASH W/SOAP & WATER. WASH CONTAMINATED CLOTHES BEFORE REUSE. INHALATION: MOVE TO FRESH AIR. IF TROUBLE BREATHING GIVE OXYGEN. CALL DR. INGESTION: GIVE PLENTY OF WATER. DON'T INDUCE VOMITING. CALL DR.

Flash Point Method:SCC Flash Point :>212F,>100C Extinguishing Media:WATER SPRAY, FOAM, CO2, DRY CHEMICAL. Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR POS PRESSURE SCBA W/FULL FACEPIECE.

Spill Release Procedures:LARGE (>55 GL): WEAR RUBBER BOOTS, GLOVES, APPROPRIATE RESPIRATOR/PROTECTIVE CLOTHING. SHUT OFF LEAK SOURCE IF SAFE. DIKE/CONTAIN SPILL. SMALL: MOP UP & RINSE AREA.

Н

andling and Storage Precautions:STORE IN ORIGINAL POLYETHYLENE
CONTAINERS IN COOL DRY AREA AWAY FROM BLEACH/OTHER CHEMICALS.
CAUTION: CORROSIVE. CONTAINS PHOSPHORIC ACID. WILL BURN.
Other Precautions:KEEP OUT OF REACH OF CHILDREN. DON'T GET IN EYES, ON
SKIN OR CLOTHING. DO NOT TAKE INTERNALLY AVOID BREATHING MISTS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NOT REQUIRED IF PROPERLY DILUTED. Ventilation:MECHANICAL LOCAL EXHAUST AT POIN T OF CONTAMINANT RELEASE. Protective Gloves:RUBBER DECREASES SKIN DRYNESS/IRRITATION Eye Protection:CHEM GLASSES ADVISED ESPEC W/CONCENTRATE Other Protective Equipment:EYEWASH, PROTECTIVE CLOTHING Supplemental Safety and Health IT IS IMPORTANT TO DETERMINE WHETHER EXPOSURE IS TO CONCENTRATE OR

DILUTE PRODUCT. GENERALLY EXPOSURE TO DILUTED PRODUCT RESULTS IN SUBSTANTIALLY LESS RISK OF INJURY THAN DESCRIBED IN HEALTH HAZARDS.

=====

Boiling Pt:B.P. Text:>212F,>100C Melt/Freeze Pt:M.P/F.P Text: