

EASTMAN KODAK COMPANY -- 103 8660 PRE-BLEACH & REPLENISH,PROCESS E-6
AR,CONCENTRATE -- 6750-01-341-6134

===== Product Identification =====

Product ID:103 8660 PRE-BLEACH & REPLENISH,PROCESS E-6 AR,CONCENTRATE

MSDS Date:07/31/1996

FSC:6750

NIIN:01-341-6134

MSDS Number: CDJTT

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Co

untry:US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====

Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 80 - 85%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

Ingred Name:STABILIZING AGENT

Fraction by Wt: 10 - 15%

Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM SULFITE

CAS:10117-38-1

RTECS #:WT3530000

Fraction by Wt: 1 - 5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHYLENEDIAMINE-TETRAACETIC ACID (EDTA) (CERCLA)

CAS:60-00-4

RTECS

#:AH4025000

Fraction by Wt: 1 - 5%

Other REC Limits:NONE RECOMMENDED

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA 313) (CERCLA)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:S, 200 PPM

ACGIH TLV:S,200PPM/250STEL; 96

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:1-THIOGLYCEROL

CAS:96-27-5

RTECS #:TY8140000

Fraction by Wt: 212F,>100C

Vapor Pres:18 @ 68F

Vapor Density:0.6

Spec Gravity:1.20

pH:6.1

Solubi

lity in Water:COMPLETE
Appearance and Odor:COLORLESS LIQUID - ODORLESS
Percent Volatiles by Volume:80- 85

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG ACIDS, STRONG BASES
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
SULFUR DIOXIDE, FORMALDEHYDE

===== Disposal Considerations =====

Waste Disposal Methods:DIS
CHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT
TO FEDERAL, STATE OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNT
OF WATER.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek compe
tent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.