

ASPECT, INC. -- QUIKEE ASP-3 -- 6840-01-411-9963

=====
Product Identification
=====

Product ID:QUIKEE ASP-3

MSDS Date:10/15/1991

FSC:6840

NIIN:01-411-9963

MSDS Number: CFDKM

=== Responsible Party ===

Company Name:ASPECT, INC.

Address:57 EISENHOWER LANE SOUTH

City:LOMBARD,

State:IL

ZIP:60148-5409

Country:US

Info Phone Num:800-331-8009

Emergency Phone Num:708-627-9600 800-424-9300 (CHEMTREC

CAGE:05

BH0

=== Contractor Identification ===

Company Name:ASPECT, INC.

Address:57 EISENHOWER LANE SOUTH

Box:City:LOMBARD,

State:IL

ZIP:60148-5409

Country:US

Phone:800-331-8009

CAGE:05BH0

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 94.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM

=====
Hazards Identification
=====

LD50 LC50 Mixture:T

LV 1000 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: IRRITATION, REDNESS, TEARING.

SKIN: IRRITATION, DEFATTING, DERMATITIS. INHAL: IRRITATION,
DIZZINESS, WEAKNESS, NAUSEA, HEADACHE.

=====
===== First Aid Measures =====

First Aid:EYE: IRRIGATE W/WATER. SKIN: WASH W/SOAP & WATER. INHAL: GET
FRESH AIR. GIVE OXYGEN IF BREATHING IS DIFFICULT. IF BREAT
HING HAS
STOPPED, GIVE ARTIF RESP. KEEP WARM/QUIET, GET IMMED MED AID.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:80.0F,26.7C

Lower Limits:3.3

Upper Limits:19.0

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM OR WATER
FOG.

Fire Fighting Procedures:DILUTE W/25 VOLUMES OF WATER. WEAR FULL FACE
BREATHING APARATUS IN POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:PRODUCT IS AN OSHA CLASS 1B FLAMMABLE

LIQUID. KEEP AWAY FROM IGNITS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE PROTECTIVE EQUIPMENT TO GUARD AGAINST
LIQUID CONTACT & INHALATION. SMALL SPILL: ABSORB. EVAPORATE
FLAMMABLE ALCOHOL IN EXPLOSION PROOF EXHAUST HOOD, BURN DRY PAPER.
LARGE SPILL: ELIMINATE IGNITS. EVAC AREA. USE NONSPARKING TOOLS.
ABSORB.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN CL

EAN, COOL, VENTILATED AREA

AWAY FROM IGNITS & OXIDIZING AGENTS. MATERIAL IS FLAMMABLE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR.

Ventilation:MECHANICAL (GENERAL) &/OR LOCAL EXHAUST.

Protective Gloves:NATURAL RUBBER, NEOPRENE.

Eye Protection:CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:IMPERVIOUS CLOTHING & BOOTS.

Supplemental Safety and Health

NK

=====
===== Physical/Chemical P

roperties =====

Boiling Pt:B.P. Text:173 TO 174F

Vapor Pres:44.6

Spec Gravity:0.815

Evaporation Rate & Reference:1.7

Solubility in Water:COMPLETE.

Appearance and Odor:CLEAR, COLORLESS LIQUID, W/ALCOHOL ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:CO, CO2.

===== Disposal Considerations =====

=====

Waste Disposal Methods:SMALL SPILL: AFTER LIQUID EVAPORATION DISPOSE IN ACCORDANCE W/APPLICABLE REGULATIONS. LARGE SPILL: DESTROY LIQUID BY INCINERATION. DISPOSE OF ABSORBENT IN LANDFILL ACCORDING TO LOCAL/STATE/FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants that this information is accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.