

F & L COMPANY, INC. -- TECTYL 517, MIL-C-6218A TYPE #2, (11OZ. AEROSOL). -- 8030-01-134-6513

=====
Product Identification
=====

Product ID:TECTYL 517, MIL-C-6218A TYPE #2, (11OZ. AEROSOL).

MSDS Date:09/02/1995

FSC:8030

NIIN:01-134-6513

MSDS Number: CFJTR

=== Responsible Party ===

Company Name:F & L COMPANY, INC.

Address:1537 EAST DEL AMO BOULEVARD

City:CARSON

State:CA

ZIP:90746

Country:US

CAGE:JO

940

=== Contractor Identification ===

Company Name:F & L COMPANY

Address:1537 E DEL AMO BLVD

Box:City:CARSON

State:CA

ZIP:90746

Country:US

Phone:310-603-2200

CAGE:0KWT9

Company Name:F & L COMPANY, INC.

Address:1537 E. DEL AMO BLVD

Box:City:CARSON

State:CA

ZIP:90746

Country:US

CAGE:JO940

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC HYDROCARBON (STODDARD TYPE)

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 40-55%

Other REC Limits:350 MG/M3/STEL 1800

OSHA PEL:100 PPM
ACGIH TLV:100 PPM

Ingred Name:PETROLEUM DISTILLATE
CAS:64742-53-6
RTECS #:PY8036000
Fraction by Wt: 1-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3/STEL 10 MG/3

Ingred Name:PROPANE/ISOBUTANE PROPELLANT
CAS:68476-86-8
Fraction by Wt: 20.0%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:1000 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogeni

city:NTP:NO IARC:NO OSHA:YES

Health Hazards Acute and Chronic:EYE: IRRITATION, REDNESS, TEARING,
BLURRED VISION. SKIN: IRRITATION, DEFATTING DERMATITIS. INGEST: GI
IRRITATION, NAUSEA, VOMIT, DIARRHEA, CHEMICAL PNEUMONITIS. INHAL:
IRRITATION, CNS EFFECTS, DIZZINE SS, WEAKNESS, FATIGUE, NAUSEA,
HEADACHE, UNCONSCIOUSNESS, DEATH.

Explanation of Carcinogenicity:CONTAINS N-NITROSODIMETHYLAMINE
[62-75-9] WHICH IS LISTED BY NTP AND IARC AND REGULATED BY OSHA AS
A CARCINOGEN.

===== First Aid Measures =====

First Aid:SKIN: WASH THOROUGHLY W/SOAP & WATER. REMOVE CONTAM CLOTHES.
WASH BEFORE REUSE. EYE: FLUSH W/LARGE AMOUNTS OF WATER, LIFT LIDS.
GET MED AID. INGEST: DONT INDUCE VOMIT. KEEP PERSON WARM/QUIET. GET
MED AID. INHAL: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT,
GIVE OXYGEN. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION.
KEEP WARM/QUIET, GET MED AID.

===== Fire Fighting Mea

sures =====

Flash Point Method:COC

Flash Point:>100F,>38C

Lower Limits:1.0

Extinguishing Media:FOAM, CO2, DRY CHEMICAL.

Fire Fighting Procedures:USE SCBA W/FULL FACE PIECE IN PRESSURE DEMAND
MODE & PROTECTIVE CLOTHING. TREAT AS OIL FIRE. WATER/FOAM MAY CAUSE
VIOLENT/DANGEROUS FROTHING. CNTNR MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP PROMPTLY. SURFACES MAY BE SLIPPERY.
TREAT AS OIL SPILL. SMAL

L SPILL: ABSORB. LARGE SPILL: DIKE. CALL

DISPOSAL COMPANY. ALWAYS PACKAGE IN DOT APPROVED CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:CONTAINER RETAINS RESIDUE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR.

Ventilation:SUFFICIENT MECHANICAL (GENERAL) &/OR LOCAL EXHAUST.

Protective Gloves:NITRILE, RUBBER.

Eye Protection:CHEMICAL

SPLASH GOGGLES.

Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.

APRON, CHEMICAL SUIT & CHEMICAL GOGGLES.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>330F,>166C

Vapor Pres:52.0

Vapor Density:>1.0

Spec Gravity: