

NILES CHEMICAL PAINT CO -- N5881A 383 GREEN H2O CARC, #34094 -- 8010-01-426-5498

=====  
Product Identification  
=====

Product ID:N5881A 383 GREEN H2O CARC, #34094

MSDS Date:02/11/1997

FSC:8010

NIIN:01-426-5498

Kit Part:Y

MSDS Number: CFNJV

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-68

3-3377

Emergency Phone Num:219-236-5856

Preparer's Name:MICHAEL LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====  
Composition/Information on Ingredients  
=====

Ingred Name:DIATOMACEOUS SILICA

CAS:68855-54-9

Fraction by Wt: 18.0%

Other REC Limits:NONE RECOMMENDED

ACGIH TLV:0.08 MG/M3

Ingred Name:WATERBOURNE POLYEURET

HANE DISPERSION(VP 0.29@20C)  
CAS:6069-50-5  
Fraction by Wt: 16.0%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:1-METHYLPYRROLIDONE (VP=0.5@20C)  
CAS:872-50-4  
RTECS #:UY5790000  
Fraction by Wt: 4.0%  
Other REC Limits:NONE RECOMMENDED  
ACGIH TLV:100 PPM

Ingred Name:WAX DISPERSION (VP = 17.5@20C)  
CAS:63231-60-7  
Fraction by Wt: 2.0%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:CHROMIUM OXIDE  
CAS:1308-38-9  
RTECS #:GB6475000  
Fraction by Wt: 10.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.5 MG/M3  
AC  
GIH TLV:0.5 MG/M3

Ingred Name:ALUMINUM MAGNESIUM SILICATE  
CAS:12174-11-7  
Fraction by Wt: 1.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:15 MG/M3  
ACGIH TLV:10 MG/M3

Ingred Name:CALCIUM CARBONATE  
CAS:471-34-1  
RTECS #:FF9335000  
Fraction by Wt: 15 MIN. LIFT LIDS. GET IMMED MED AID. NO CONTACTS.  
INGEST: 1-2 GLASSES WATER. DON'T INDUCE VOMITING. CALL DR/POISON  
CONTROL IMMEDIATELY. TREAT SYMPTOMS.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:250F,121C

Lower Limits:0.8

Upper Limits:15.0

Extinguishing Media:DRY CHEMICAL, FOAM, CO2.

Fire Fighting Procedures:USE SCBA W/FULL FACE PIECE IN POSITIVE PRESSURE MODE/PROTECTIVE CLOTHES. USE WATER TO COOL CLOSED CONTAINERS. PREVENT PRESSURE BUILD-UP/AUTOIGNIT/EXPLOSION.

Unusual Fire/Explosion Hazard:KEEP CONTAINER TIGHTLY CLOSED. KEEP FROM IGNITS. APPLIC TO HOT SURFACE REQUIRES SPECIAL PRECAUTIONS. DECOMP PRODUCTS HAZARDOUS.

===== Accidental Release Me  
asures =====

Spill Release Procedures:REMOVE IGNITS. AVOID VAPOR BREATHING/SKIN CONTACT. ABSORB/SHOVEL INTO DRUMS AND DISPOSE. DIKE.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE IN HIGH HEAT/NEAR IGNITS. KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID ROUGH HANDLING.

Other Precautions:CONTAINERS HAZARDOUS WHEN EMPTY. DON'T WELD/FLAME CUT ON EMPTY DRUM. SHOCK FROM DROPPING MAY SPLIT CONTAINER.

=====

==== Exposure Controls/Personal Protection =====

Respiratory Protection:PROPERLY FITTED HALF-MASK OR FULL FACEPIECE RESPIRATOR, NIOSH/MSHA APPROVED.

Ventilation:SUFFICIENT.

Protective Gloves:CHEMICAL RESISTANT (NITRILE/VITON)

Eye Protection:CHEM GOGGLES/SAFETY GLASSES/FACE SHIELD.

Work Hygienic Practices:WASH HANDS BEFORE EATING/SMOKING/USING RESTROOM. REMOVE CONTAM CLOTHES TO AVOID FLAMMABILITY HAZARD. WASH BEFORE REUSE.

Supplemental Safety and Health  
MORE INFORMATION ON  
FILE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212 TO 398F

Decomp Temp:Decomp Text:NOT EST.

Vapor Density:>AIR

Spec Gravity:1.423

pH:NA

Viscosity:85 #4FC

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:YES

Appearance and Odor:LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:53.73

Corrosion Rate:MINIMAL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OX

IDENTIFYING/REDUCING AGENTS.

Stability Condition to Avoid:HIGH TEMPERATURES

Hazardous Decomposition Products:CARBON MONOXIDE &/OR CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:ACCORDING TO FEDERAL, STATE, LOCAL REGS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or

implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.