View NSN Online: https://aerobasegroup.co.il/nsn/6850-01-439-6250 RICOH CORP -- TONER TYPE 450, 889463 ______ MSDS Safety Information _____ FSC: 6850 NIIN: 01-439-6250 MSDS Date: 07/14/1995 MSDS Num: CFTCW Product ID: TONER TYPE 450, 889463 MFN: 01 Responsible Party Cage: RICOH Name: RICOH CORP Address: 5 DEDRICK PLACE City: WEST CALDWELL NJ 07006 Info P hone Number: 201-882-2000;800-336-6737 Emergency Phone Number: 800-336-6737 Proprietary Ind: Y Published: Y ______ Contractor Summary ______ Cage: 2Z665 Name: RICOH CO LTD Address: 5 DEDRICK PL City: CALDWELL NJ 07006-6304 Phone: 973-882-2000 / 800-336-6737 Cage: RICOH Name: RICOH CORP Address: 5 DEDRICK PLACE City: WEST CALDWELL NJ 07006 Phone: 201-882-2000 _____ ========= Item Description Information Item Name: TONER, INDIRECT ELECTROSTATIC PROCESSING _____ Ingredients ______

Name: *** PROPRIETARY ***

Health Hazards Data

LD50 LC50 Mixture: NONE SPECIFIE

D BY MANUFACTURER.

Route Of Entry Inds - Inhalation: YES

Skin: YES Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: YES OSHA: NO

Effects of Exposure: ACUTE: EYES: MAY CAUSE TEMPORARY EYE DISCOMFORT. SKIN:

NON-IRRITANT. INHALATION: GASPING. INGESTION: GREATER THAN 5 G/KG BODYWEIGHT. CHRONIC: PROLONGED INHALATION OF EXCESSIVE DUST MAY CAUSE LUNG DAMA GE THAT IS ATTRIBUTED TO "LUNG OVERLOADING", A GENERIC RESPONSE TO EXCESSIVE AMOUNTS OF ANY DUST (EFTS OF OVEREXP)

Explanation Of Carcinog

enicity: CARBON BLACK: IARC MONOGRAPHS ON EVAL OF CARCIN

RISK OF CHEMS TO MAN, VOL 65, PG 24-27, 1995: GROUP 2B (ANIMAL: LUNG).

Signs And Symptions Of Overexposure: HEALTH HAZARDS: RETAINED IN LUNGS FORM PROLONGED INTERVAL. USE OF PRODUCT AS INTENDED DOES NOT RESULT IN INHALATION

OF EXCESSIVE DUST.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYE: TRY TO REMOVE WITH EYE DROPS OR FLUSH WITH WATER FOR AT LEAST 15 MINUTES. IF UNSUCCESSFUL, GET MEDICAL ATTE

NTION. SKIN: WASH THOROUGHLY

WITH SOAP AND WATER. INHALATION: REMOVE FROM EXPOSURE. INGE STION: DILUTE STOMACH CONTENTS WITH SEVERAL GLASSES OF WATER.

Handling and Disposal

Spill Release Procedures: SWEEP UP USING APPRVD TONER VACUUM CLEANER WITH 0.5 MICRON FILTER OR SMALLER SUCH AS ATRIX AAA TONER VACUUM (RICOH EDP CODE 342MIU). USE OF VACUUM CLEANER NOT RATED FOR TONER PARTIC

ULATE COULD BE POTN

TL FIRE HAZ & amp; /OR RSLT IN PERSONAL INJURY. (SUPDAT)

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: USED TONER SHOULD BE DISP OF IN AN ENVIRONMENTALLY SAFE MANNER & Mann

Handling And Storage Precautions: STORE IN COOL, DRY PLACE. CLEANSE SKIN THOROUGHL

Y AFTER CONTACT, BEFORE BREAKS AND MEALS, AND AT END OF WORK PERIODS. KEEP OUT OF REACH OF CHILDREN.

Other Precautions: DO NOT HANDLE IN AREAS WHERE WIND BLOWS. FLYING POWDER MAY ENTER EYES. MINIMIZE INHALATION OF DUST.

Fire and Explosion Hazard Information

Extinguishing Media: FOAM, WATER SPRAY (FOG), DRY CHEMICALS OR CARBON DIOXIDE

MAY BE SUITABLE.

Fire Fighting Procedures: US

E NIOSH APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT (FP N). Unusual Fire/Explosion Hazard: AIRBORNE DISPERSAL OF MOST FINELY DIVIDED ORGANIC POWDERS SUCH AS TONER MAY FORM AN EXPLOSIVE MIXTURE. DO NOT INCINERATE LOOSE OR SPILLED TONER. _____ **Control Measures** -----Respiratory Protection: NONE REQUIRED UNDER NORMAL CONDITIONS OF USE. USE NIOSH APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE O F CONCERN (FP N). Ventilation: MECHANICAL (GENERAL): ADEQUATE VENTILATION. Protective Gloves: IMPERVIOUS GLOVES (FP N). Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES (FP N). Other Protective Equipment: ANSI APPROVED EYE WASH & DELUGE SHOWER (FP N). Work Hygienic Practices: MINIMIZE BREATHING DUST. CLEANSE SKIN THOROUGHLY AFTER CONTACT, BEFORE BREAKS AND MEALS. Supplemental Safety and Health: SPILL PROCEDURE: REMOVE RESIDUE WITH SOAP AND WATER. -----Physical/Chemical Properties _____ Spec Gravity: 1.2 Solubility in Water: NEGLIGIBLE; Appearance and Odor: BLACK POWDER WITH SLIGHT PLASTIC ODOR. ______ Reactivity Data ______ Stability Indicator: YES Materials To Avoid: NONE. Hazardous Decomposition Products: CARBON MONOXIDE AND OTHER DECOMPOSITION PRODUCTS IN CASE OF INCOMPLETE COMBU STION. Hazardous Polymerization Indicator: NO Conditions To Avoid Polymerization: NOT RELEVANT. _____

Toxicological Information

Ecological Information

MSDS Transport Information

========
Regulatory Information
Other Information
Transportation Information
Responsible Party Cage: RICOH Trans ID NO: 136807 Product ID: TONER TYPE 450, 8894 63 MSDS Prepared Date: 07/14/1995 Review Date: 01/08/1998 MFN: 1 Multiple KIT Number: 0 Review IND: Y
Detail DOT Information
DOT PSN Code: ZZZ DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
Detail IMO Information
IMO PSN Code: ZZZ IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION
Detail IATA Information
IATA PSN Code: ZZZ IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
Detail AFI Information
AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORT

ATION

HAZCOM Label

Product ID: TONER TYPE 450, 889463

Cage: RICOH Assigned IND: Y

Company Name: RICOH CORP Street: 5 DEDRICK PLACE City: WEST CALDWELL NJ

Zipcode: 07006

Health Emergency Phone: 800-336-6737

Label Required IND: Y

Date Of Label Review: 12/02/1997

Status Code: C

Label Date: 12/02/1997 Origination Code: G Chronic Hazard IND: Y Eye Protection IND: YES Skin Protection IND: Y

ES

Signal Word: CAUTION

Respiratory Protection IND: YES

Health Hazard: Slight Contact Hazard: Slight Fire Hazard: Slight Reactivity Hazard: None

Hazard And Precautions: COMBUSTIBLE. ACUTE: EYES: MAY CAUSE TEMPORARY EYE DISCOMFORT. INHALATION: GASPING. INGESTION: GREATER THAN 5 G/KG BODYWEIGHT. CHRONIC: CANCER HAZARD. CONTAINS CARBON BLACK, WHICH IS LISTED AS AN ANIMA L LUNG CARCINOGEN (FP N). PROLONGED INHALATION OF EXCESSIVE DUST MAY CAUSE LUNG DAMAGE THAT IS ATTRIBUTED TO "LUNG OVERLOA"

DING". CANCER HAZARD. CONTAINS

CARBON BLACK, WHICH IS LISTED AS AN ANIMAL LUNG CARCINOGEN (FP N).

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person o

r persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding De partment of Defense or other government situation.