View NSN Online: https://aerobasegroup.com/nsn/8010-00-081-0809

DEL PAINT CORP. -- TT-E-529G OLIVE DRAB #24084 -- 8010-00-081-0809

Product ID:TT-E-529G OLIVE DRAB #24084 MSDS Date:08/05/1997 FSC:8010 NIIN:00-081-0809 **MSDS Number: CFWTB** === Responsible Party === Company Name: DEL PAINT CORP. Address:3105 E. RENO City:OKLAHOMA CITY State:OK ZIP:73117 Country:US Info Phone Num:405-672-1431/FAX 405-672-0804 **Emergency Phone Num:80** 0-424-9300 24 HRS Preparer's Name: ONEY FLEMING CAGE: JO954 === Contractor Identification === Company Name: DEL PAINT CORP. Address:3105 E. RENO City:OKLAHOMA CITY State:OK ZIP:73117 Country:US Phone:405-672-1431/FAX 405-672-0804 CAGE:JO954 Company Name: DEL PAINT MFG Address:3105 EAST RENO Box:City:OKLAHOMA CITY State:OK ZIP:73117 Country:US Phone:405-672-1431 CAGE:39934

Ingred Name: MEDIUM ALIPHATIC SOLVENT NAPHTHA CAS: 64742-88-

7 Fraction by Wt: 32.0% Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-HAZARDOUS INGREDIENTS Fraction by Wt: 68.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Ingred Name:VOC = 2.84 LBS/GL RTECS #:9999999VO Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO O SHA:NO Health Hazards Acute and Chronic:EYE: REDNESS, PAIN. SKIN: REDNESS.

INHAL: LABORED BREATHING, DULLNESS, DROWSINESS. INGEST: ABDOMINAL PAIN, NAUSEA. CHRONIC: EYE: IRRITATION, REDNESS, TEARING, BLURRED VISION. SKIN: IRRITATION, DEFATTI NG, DERMATITIS. INHAL: NASAL/RESPIRATORY IRRIT, DIZZINESS, NAUSEA, HEADACHE. INGEST: GI IRRITATION, NAUSEA, VOMITING.

Medical Cond Aggravated by Exposure: RESPIRATORY SYSTEM DISEASES.

First Aid:EYE: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINUTES, LIFT LIDS, GET MED AID. SKIN: REMOVE CONTAM CLOTHES, WASH BEFORE REUSE. WASH SKIN W/SOAP & WATER. INHAL: REMOVE TO FRESH AIR. GIVE OXYGEN IF NEEDED. GET MED AID. INGEST: KEEP WARM/QUIET. GET MED AID. DONT INDUCE VOMIT.

Flash Point Method:TCC Flash Point:100F,38C Autoignition Temp:Autoignition Temp Text:540F Lower Limits:1.0 Upper Limi ts:6.0 Extinguishing Media:CO2, DRY CHEMICAL, FOAM. Fire Fighting Procedures: USE SCBA & FULL PROTECTIVE GEAR. USE WATER SPRAY TO COOL CONTAINERS. (PREVENT PRESSURE BUILDUP/AUTOIGNITION/EXPLOSION). Unusual Fire/Explosion Hazard:WATER MAY SPREAD FIRE. VAPORS >AIR, MAY TRAVEL TO IGNITION SOURCE & FLASH BACK. Spill Release Procedures: VENT AREA. COVER W/INERT ABSORBENT. SHOVEL W/NONSPARKING TOOLS INTO CONTAINER. REM OVE TO SAFE AREA & SEAL. Handling and Storage Precautions: STORE IN CLEAN, DRY AREA. KEEP AWAY FROM IGNITION SOURCES. Other Precautions: KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM CHILDREN. GROUND EQUIPMENT TO REDUCE STATIC ELECTRICITY HAZARD. USE NONSPARKING TOOLS. Respiratory Protection: USE A RESPIRATOR W/APPROPRIATE CARTRIDGES (NIOSH APPR OVED). Ventilation:LOCAL EXHAUST. Protective Gloves: CHEMICAL RESISTANT. Eye Protection: SAFETY GLASSES W/SIDE SHIELDS. Other Protective Equipment: EYEWASH STATION, SAFETY SHOWER & IMPERVIOUS CLOTHING. Supplemental Safety and Health NK HCC:F4 Boiling Pt:B.P. Text:305 TO 396F Melt/Freeze Pt:M.P/F.P Text:NA Decomp Temp:Decomp Text:752F,400C Vapor Pres:2.58 Vapor Density:>AIR Spec Gravity:1.08 pH:NA Viscosity:65-72 KU Evaporati

on Rate & amp; Reference: