

LIFE INDUSTRIES CORPORATION -- LIFE CHALK TYPE P-2 PART BLACK PART A --
8030-00-682-6745

=====
Product Identification
=====

Product ID:LIFE CHALK TYPE P-2 PART BLACK PART A

MSDS Date:01/23/1997

FSC:8030

NIIN:00-682-6745

Kit Part:Y

MSDS Number: CFWYF

=== Responsible Party ===

Company Name:LIFE INDUSTRIES CORPORATION

Address:2081 BRIDGEVIEW DRIVE

City:NORTH CHARLESTON

State:SC

ZIP:29405

Country:U

S

Info Phone Num:800-262-8200

Emergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name:JAMES J. ANDERSON

CAGE:OFJC8

=== Contractor Identification ===

Company Name:LIFE INDUSTRIES

Address:205 SWEET HOLLOW RD

Box:City:OLD BETHPAGE

State:NY

ZIP:11804

Country:US

Phone:516-454-0055

CAGE:OFJC8

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA 313) (CERCLA)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 5.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:20

0 PPM
ACGIH TLV:200 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE OVEREXPOSURE: ABDOMINAL
DISCOMFORT OR PAIN, NAUSEA, VOMIT, WEAKNESS. CHRONIC: TYPICAL
SYMPTOMS OF HEAVY METAL POISONING.

=====
First Aid Measures
=====

First Aid:INHA
L: GET FRESH AIR. EYES: WASH W/WATER FOR 15 MINUTES, GET
MED AID. SKIN: WASH W/SOAP & WATER. INGEST: INDUCE VOMIT, GET MED
AID.

=====
Fire Fighting Measures
=====

Flash Point:175F,79C
Extinguishing Media:FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures:USE SCBA.
Unusual Fire/Explosion Hazard:EMISSIONS OF TOXIC VAPORS.

=====
Accidental Release Measures
=====

Spill Release Procedures:CONTAIN SPILL. SOAK UP & REMOVE PRODUCT
W/ABSORBENT MATERIAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE SCBA.
Ventilation:LOCAL EXHAUST ADEQUATE.
Protective Gloves:NONPOROUS, CHEMICAL RESISTANT.
Eye Protection:SAFETY GOGGLES.
Supplemental Safety and Health
NK

=====
Physical/Chemical Properties
=====

Spec Gravity:1.56
A

Appearance and Odor:DARK BROWN, HIGHLY VISCOUS LIQUID.
Percent Volatiles by Volume:5.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NK
Stability Condition to Avoid:ACIDS & REDUCERS.

===== Disposal Considerations =====

Waste Disposal Methods:FOLLOW LOCAL, STATE & FEDERAL REGULATIONS. DO
NOT INCINERATE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.