View NSN Online: https://aerobasegroup.co.il/nsn/8010-01-333-9815

DURANT PAINT -- TT-E-2784A -- 8010-01-333-9815

Product ID:TT-E-2784A MSDS Date:09/15/1997

FSC:8010

NIIN:01-333-9815

MSDS Number: CFXDT
=== Responsible Party ===
Company Name: DURANT PAINT

Address:960 BROADWAY

City:REVERE State:MA ZIP:02051 Country:US

Info Phone Num:617-289-1400

Emergency Phone Num:617-289-1400

CAGE:NO367

=== Contractor Identification ===

Compan

y Name:DURANT PAINT Address:950 BROADWAY

Box:City:REVERE

State:MA ZIP:02051 Country:US

Phone:617-289-1400

CAGE:NO367

Company Name: DURANT PAINTS INC

Address:112 RAILROAD ST

Box:City:REVERE

State:MA

ZIP:02151-4007

Country:US

Phone:781-289-8415

CAGE:3F338

======= Composition/Information on Ingredients ========

Ingred Name: GLYCOL ETHER (VAPOR PRESSURE 25%)

CAS:111-77-3

RTECS #:KL6125000 Fraction by Wt: 7.20%

Other REC Limits: NONE RECOMMENDED

Ingred Name: GLYCOL ETHER (VAPOR PRESSURE 0

|                        | by Wt: 1.30%<br>C Limits:NONE RECOMMENDED   |
|------------------------|---|
| RTECS #                | ame:VOC = 1.46 G/L, NON-EXEMPT SOLVENT PER ADJUSTED GALLON.<br>#:999999VO<br>C Limits:NONE RECOMMENDED  |
| ======                 | ======== Hazards Identification ===============   |
| Reports of Health Ha   | f Entry: Inhalation:YES Skin:YES Ingestion:YES of Carcinogenicity:NTP:NO IARC:NO OSHA:NO azards Acute and Chronic:EYE: IRRITATION. SKIN: IRRITATION. : IRRITATING TO NOSE/THROAT. INGEST:TOXIC. |
| cts of Ov              | erexposure:INHAL: HEADACHE, NAUSEA, VOMITING, DROWSINESS. Cond Aggravated by Exposure:HEART CONDITIONS, ASTHMA.   |
| ======                 | ======================================  |
| W/SO/                  | EYE: FLUSH W/WATER FOR 15 MINUTES, GET MED AID. SKIN: WASH<br>AP & WATER. REMOVE CONTAIM CLOTHES. INHAL: GET FRESH AIR. OXGEN<br>EDED. INGEST: GIVE TWO GLASSES OF WATER. INDUCE VOMIT.         |
| ======                 | ======== Fire Fighting Measures ===============   |
| Extinguis<br>Fire Figh | int:NONFLAMMBLE shing Media:CO2, FOAM. ting Procedures:USE FULL PROTECTIVE GEAR. Fire/Explosion Hazard:COOL CONTAINERS W/WATER STEAM IN EVENT OF  |
| ======                 | ======= Accidental Release Measures ============  |
| Spill Rele             | ease Procedures:DIKE & CONTAIN. SOAK UP RESIDUE W/ABSORBENT<br>RIAL.  |
| ======                 | ========= Handling and Storage ================   |
|                        | and Storage Precautions:STORE IN A COOL, DRY PLACE. PROTECT FREEZING.   |
| =====                  | ===== Exposur   |

.1%) CAS:770-35-4

| Respiratory Protection:REQUIRED. Ventilation:REQUIRED. Protective Gloves:REQUIRED. Eye Protection:REQUIRED. Other Protective Equipment:APRON. Work Hygienic Practices:WASH AFTER HANDLING. Supplemental Safety and Health NK   |
|--|
| ======== Physical/Chemical Properties =========  |
| Boiling Pt:B.P. Text:212F,156C<br>Vapor Density:>AIR<br>Evaporation Rate & Description of the state of |
| == ===================================   |
| Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIALS. Stability Condition to Avoid:HEAT, SPARKS & OPEN FLAME. Hazardous Decomposition Products:CARBON MONOXIDE & UNIDENTIFIED ORGANIC COMPOUNDS.   |
| ======= Disposal Considerations ==========   |
| Waste Disposal Methods:DISPOSE OF IN RECKA APPROVED FACILITY.  |
| Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.  |

e Controls/Personal Protection ========