

PRESTONE PRODUCTS CORPORATION -- RE4MFTH-55 BE SERIES REINHIBITOR FOR MIL-A-46153,  
PART 1 -- 6850-01-397-1960

===== Product Identification =====

Product ID:RE4MFTH-55 BE SERIES REINHIBITOR FOR MIL-A-46153, PART 1

MSDS Date:05/01/1995

FSC:6850

NIIN:01-397-1960

MSDS Number: CFYSP

=== Responsible Party ===

Company Name:PRESTONE PRODUCTS CORPORATION

Address:83 WOOSTER HEIGHTS ROAD

City:DANBURY

Stat

e:CT

ZIP:06810-1925

Country:US

Info Phone Num:203-731-3686

Emergency Phone Num:800-424-9300(CHEMTREC)

CAGE:EO340

=== Contractor Identification ===

Company Name:FINISH THOMPSON INC

Address:921 GREENGARDEN RD

Box:City:ERIE

State:PA

ZIP:16501-1591

Country:US

Phone:814-455-4478/800-942-5969

CAGE:30255

Company Name:PRESTONE PRODUCTS CORPORATION

Address:55 FEDERAL ROAD

City:DANBURY

State:CT

ZIP:06810

Country:US

Phone:203-830-7865

CAGE:EO340

Company Name:PRESTONE PRODUCTS CORPORATION

Box:UNKNOW

CAGE:PR

ESP

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHYLENE GLYCOL (SARA 313) (CERCLA) CONTAINS INGRED #2.  
CAS:107-21-1  
RTECS #:KW2975000  
Fraction by Wt: 15-25%  
Other REC Limits:NONE RECOMMENDED  
ACGIH TLV:C STEL39PPM,A4,VAP96  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:DIETHYLENE GLYCOL IN INGRED #1.  
CAS:111-46-6  
RTECS #:ID5950000  
Fraction by Wt: 0-8%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM HYDROXIDE (CERCLA)  
CAS:1310-58-3  
RTECS #:TT2100000  
  
Fraction by Wt: 15-25%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:C 2 MG/M3  
ACGIH TLV:C 2 MG/M3; 9596  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:SODIUM HYDROXIDE (CERCLA)  
CAS:1310-73-2  
RTECS #:WB4900000  
Fraction by Wt: 5-10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:2 MG/M3  
ACGIH TLV:C 2 MG/M3; 9596  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:SODIUM TOLYLTRIAZOLE  
CAS:64665-57-2  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:BENZOTRIAZOLE  
CAS:95-14-7

RTECS #:DM1225000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM SILICATE  
CAS:1344-09-8  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 25-60%  
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:N

O OSHA:NO

Health Hazards Acute and Chronic:INGEST:MAY RESULT IN IMMEDIATE/SEVERE BURNS TO LIPS/TONGUE/ORAL MUCOSA/ESOPHAGUS W/POSSIBLE GI HEMORRHAGE/PERFORATION.CNS EFFECTS.CARDIAC FAILURE,PULM EDEMA.SEVERE KIDNEY DMG W/LG VOL OF ETHYLENE GLYCOL -FATAL.SKIN ABSORPTION:NO EVIDENCE OF ADVERSE EFFECTS FROM AVAIL INFO.INHAL:EXT LUNG IRRIT,DMG/DESTRUCTION OF LUNG (SUPP)

Explanation of Carcinogenicity:PER MSDS:NONE OF INGREDIENTS IS LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN BY OSHA/NTP/IARC.

Effects of Overexposure:INGEST:DROOLING,DIFFICULTY W/SWALLOWING,BREATH,SPEAKING,CHEST PAIN,NAUSEA,VOMIT,DIZZINESS,MALaise,BLUR VISION,IRRITABILITY,LUMBAR PAIN,OLIGURIA,UREMIA,IRREGULAR EYE MOVEMENTS,CONVULSIONS,COMA.WEAK FACIAL MUSCLES,DIMINISHED HEARING,DIFFICULTY W/SWALLOW,LIVER INJURY.INHAL:HORSENESS,DIFFICULT BREATH,RESPIRATORY DISTRESS,DIZZINESS,NYSTAGMUS.SKIN SENSITIZATION,DERM.

Medical Conditions Aggravated by Exposure:MAY AGGRAVATE EXISTING KIDNEY DISEASE.

===== First Aid Measures =====

=====

First Aid:INGEST:DONT INDUCE VOMIT.RINSE MOUTH.DRINK GLASSFUL OF MILK/H2O.GET IMMED MED ATTN;EMERG ADVICE N/AVAI TAKE TO EMERG MED FACI.SKIN:REMOVE CONTAM CLOTH/SHOE.IMMED WASH W/SOAP/COPIOUS AMTS OF H2O.IRRIT/ RED DVLP/PERS GET MED ATTN.INHAL:SYMPT MOVE TO FRESH AIR.BREATH DIFF GIVE OXY;STOP BREATH ART RESP.GET IMMED MED ATTN.EYE:IMMED FLUSH W/LOTS OF H2O 15MINS MIN.IRRIT,PAIN,ETC GET MED ATTN.(OTHER PRECA)

===== Fire Fighting Measures =====

Flash Point:NONE THRU BOILIN  
Autoignition Temp:Autoignition Temp Text:N/DETR  
Lower Limits:N/DETERMINED  
Upper Limits:N/DETERMINED  
Extinguishing Media:APPLY ALCOHOL TYP OR ALL-PURPOSE FOAMS BY MFG'S RECOMMENDED TECHNIQUES FOR LG FIRES.SM FIRES USE H2O FOG,CO2,DRY CHEM.  
Fire Fighting Procedures:COOL FIRE EXPO CNTNRS/STRUCTURES W/H2O.WEAR POSITIVE PRESSURE SELF-CONTAIN BREATH APPARATUS & FULL PROT CLOTH.DONT SPRAY POOL FIRES DIRECTLY.SOLID STREAM(SUPPL)  
Unusual Fire  
/Explosion Hazard:NONE EXPECTED.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPILL FRM MIX W/OTHER MATL.WEAR SPLASHPROOF CHEM GOG/RUBB/NEOPRENE GLOVES.CONTAIN W/RING OF NONCOMBUST ABSORBANT MATL(SPEEDYDRY,VERMICULITE).DIL W/EQUAL ATM OF H2O.POUR MORE ABSORBENT.COLLECT INT O CNTNR.REPORT AS REQUIRE BY CERCLA/LOCAUTHORITIE  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:USE ONLY W/ADEQU VENTI.AVOID BREATH VAP/MIST FRM CHEMS.KEPE TIGHTLY CLSD.DONT STORE IN OPN/UNLABEL CNTNR.STORE IN COOL DRY AREA AWAY FROM INCOMPAT.  
Other Precautions:DONT MIX CHEM DIRECTLY W/OTHER CHEM.USE ONLY AS DIRECTED.NOTE TO DR:INGEST INDUCTION OF EMESIS SHOULD BE AVOIDED-FURTHER CAUSTIC INJURY TO ESOPHAGUS MAY OCCUR.NO SPEC ANTIDOTE FOR ALKALINE CORR INGEST .ETHANOL ANTIDOTAL FOR ETHYLENE GLYCOL.

===== Expo

sure Controls/Personal Protection =====

Respiratory Protection:NONE NEEDED UNDER NORMAL USE  
CONDITIONS.OPERATIONS WHERE TLV EXCEEDED NIOSH/MSHA APPROV ORG VAP  
RESP W/DUST/MIST PRE-FILT OR SUPP AIR RESP RECOMMENDED.EPMT SELECT  
DEPENDS ON CONTAM TYP/CONCEN SELECT I AW 29CFR1910.134/GOOD INDUST  
HGY PRAC.

Ventilation:GEN VENTI SHOULD BE ADEQUATE FOR NORMAL USE.MTL HEAT/MISTED  
& TLV EXCEEDED FORCED VENTI(LOC EXHUAST)MAY BE NEEDED.

Protective Gloves:CHEM RESIST-NEOPRENE,P  
VC COATED

Eye Protection:SPLASH PROOF CHEM SAF GOGG,FCHSIELD

Other Protective Equipment:DONT WEAR CONTACT LENSES.PROT  
CLOTH-APRON,COVERALL,BOOTS-PREVENT SKIN CONTACT.SUITABLE WASH/EYE  
FLUSH FACI IN WORKAREA.

Work Hygienic Practices:CONT CLOTH SHOULD BE IMMED REMOVE;LAUNDER BEF  
REUSE.WEAR PPE WHEN HNDLG.PREVENT EYE/SKIN/CLOTH CONTACT.WASH WELL  
AFT HND

Supplemental Safety and Health

FIREFIGHT:OF H2O/FOAM DIRECTED INTO HOT BURN LIQ CAN CAUSE FROTH.

HEALTH:TISSUE,PNEUITIS/PULM ED

EMA.HI VAP(FRM HEAT MATL IN

ENCLSD/POOR VENTI AREA)NAU,VOMIT,HEAD,DIZZ,IRREG EYE

MOVEMENTS.SKIN:SEVERE I RRRIT &/OR CHEM BURNS RESULTS IN TISSUE

DESTRUCT.EYE:RAPID,SEVERE IRRIT &/OR CHEM BURNS RESULTS IN TISSUE

DESTRUCT,BLIND.

===== Physical/Chemical Properties =====

HCC:B1

Boiling Pt:=107.8C, 226.F

Melt/Freeze Pt:=-28.9C, -20.F

Vapor Pres:N/DETERMIN

Vapor Density:N/DETERMIN

Spec Gravity:10.5-11.3 DENS

pH:14.0

Viscosity:N/DETERMINED

Evaporation Rate &

amp; Reference:N/DETERMINED

Solubility in Water:100%, COMPLETE

Appearance and Odor:ORANGE-YELLOW COLOR

Percent Volatiles by Volume:N/DETR

Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID STRONG ACIDS,STRONG OXIDIZING AGENTS,MATLS REACTIVE W/HYDROXYL  
COMPOUNDS.

Stability Condition to Avoid:NONE KNOWN

Hazardous Decomposition Products:COMBUSTION PRODUCTS MAY INCLUDE CARBON  
MONOXIDE & CARBON DIOXIDE.

===

===== Disposal Considerations =====

Waste Disposal Methods:WASTE MATL RCRA HAZ WASTE-CORRO.DISPO IAW ALL  
LOC/STATE/FED REGS.EMTPY CNTNR RETAIN PROD RESIDUE & MAY BE  
DANGEROUS.DONT REUSE EMTPY CNTNRS.IMMED REPLACE CNTNR LID & DISPO  
PROPERLY.FOLLOW ALL RECOMMEN DED PRECAUT IN HNDLG EMPTY  
CNTNRS.SARA,CERCLA CHEM

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.