

GLYPTAL INC -- 1201, GLYPTAL, AIR DRY ENAMAL. -- 7010-01-201-1385

=====
Product Identification
=====

Product ID:1201, GLYPTAL, AIR DRY ENAMAL.

MSDS Date:01/25/1991

FSC:7010

NIIN:01-201-1385

MSDS Number: CGLFQ

=== Responsible Party ===

Company Name:GLYPTAL INC

Address:305 EASTERN AVE

City:CHELSEA

State:MA

ZIP:02150-3344

Country:US

Info Phone Num:617-884-6918

Emergency Phone Num:617-884-6918

CAGE:653

13

=== Contractor Identification ===

Company Name:A-Z PACKAGING COMPANY (614-444-8441)

Box:UNKNOW

CAGE:AZPAC

Company Name:GLYPTAL INC

Address:305 EASTERN AVE

Box:NONE

City:CHELSEA

State:MA

ZIP:02150-3344

Country:US

Phone:617-884-6918

CAGE:65313

Company Name:J.G.B. ENTERPRISES

Address:115 METROPOLITAN DR

Box:209

City:LIVERPOOL

State:NY

ZIP:13088

Country:US

Phone:315-451-2770

CAGE:61125

Company Name:MILTOPE CORP. (334-284=8665)

Box:UNKNOW

CAGE:54418

=====
Composition/Information on Ingre

dients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 34.3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL;9495

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:VN&P NAPHTHA, (VARNISH MAKERS & PAINTER NAPHTHA)

CAS:8030-30-6

Fraction by Wt: 5.6%

Other REC Limits:300 PPM

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:STODDARD SOLVENT

CAS:64741-41-9

Fraction by Wt: 8.2%

Other REC Limits:5

00 PPM TLV

Ingred Name:IRON OXIDE

CAS:1309-37-1

RTECS #:NO7400000

Fraction by Wt: 8.2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 MG/M3 (FE)

ACGIH TLV:5MG(FE)/M3FUME,B2;95

Ingred Name:HYDRATED MAGNESIUM SILICATE

CAS:14807-96-6

RTECS #:MW2700001

Fraction by Wt: 17.0%

Other REC Limits:20 PPM TLV

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3

Ingred Name:ALKYD RESIN (NON-HAZARDOUS)

Fraction by Wt: 34.7%

Other REC Limits:NONE RECOMMENDED

Ingred Name:VOLATILE ORGANIC COMPOUNDS, VOC (LESS WATER): 3.98

LBS/GALLON.
RTECS #:9999999VO

=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: SKIN AND EYE CONTACT:
IRRITATION. CHRONIC: XYLENE CAUSES ANEMIA, LIVER ABNORMALITIES,
LIVER & EYE DAMAGE IN LABORATORY ANIMALS. REPORTS HAVE ASSOCIATED
PROLONGED AND REPEATED OCCU
PATIONAL OVERE XPOSURE WITH PERMANENT
BRAIN AND CNS DAMAGE.
Explanation of Carcinogenicity:NONE OF THE COMPONENTS OF THIS PRODUCT
ARE REPORTED CARCINOGENS.
Effects of Overexposure:HEADACHE, NAUSEA, DIZZINESS, CONFUSION,
IRRITABILITY.
Medical Cond Aggravated by Exposure:RESPIRATORY DIFFICULTIES,
PREEXISTING SKIN SENSITIZATION, PRE-EXISTING LIVER AND/OR KIDNEY
DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

=====
===== First Aid Measures =====
=====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL
ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREA
WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.
INHALATION: M OVE TO FRESH AIR. ADMINISTER CPR OR OXYGEN AS NEEDED
TO RESTORE BREATHING. GET MEDICAL ATTENTION. INGESTION: GET
IMMEDIATE MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:PMCC
Flash Point:72.0F,22.2C

Lower Limits:1.0

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. USE WATER TO COOL
CLOSED CONTAINERS EXPOSED TO HEAT. FIREFIGHTING PERSONNEL SHOULD
WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:PRESSURE MAY BUILD UP IN CLOSED
CONTAINERS THAT ARE EXPOSED TO HEAT. SOLVENT VAPORS ARE HEAVIER
THAN AIR AND MAY TRAVEL TO IGNITION SOURCE AND FLASH BACK.

=====
===== Accidental Release Measures

=====
Spill Release Procedures:PROVIDE ADEQUATE VENTILATION. REMOVE IGNITION SOURCES. ABSORB AND DISPOSE USING NON-SPARKING TOOLS. WATER SPRAY MAY BE USED. CONTAIN RUN-OFF, COVER WITH ABBSORBENT MATERIAL AND PLACE IN CONTAINERS FOR DISPOSAL.FLUSH AREA WITH WATER TO REMOVE RESIDUE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage

Handling and Storage Precautions:STORE IN COOL DRY PLACE AWAY FROM HEAT, SPARKS, OPEN FLAME. KEEP CONTAINERS CLOSED AND UPRIGHT TO PREVENT LEAKAGE. OUTSIDE/DETACHED STORAGE PREFERRED.

Other Precautions:INSIDE STORAGE SHOULD BE A FLAMMABLE LIQUID STORAGE CABINET. GROUND METAL CONTAINERS WHEN TRANSFERRING MATERIAL FROM ONE CONTAINER TO ANOTHER. DO NOT REUSE CONTAINER FOR ANY PURPOSE.

=====
Exposure Controls/Personal Protection

Respiratory Protection:OUTDOOR/OPEN AREAS USE BUREAU OF MINES APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE OVERSPRAY.INDOORS, WHERE VENTILATION IS INADEQUATE,USE BUREAU OF MINES APPROVED CHEMICAL-MECHANICAL RESPIRATOR DESIGNED TO REMOVE PARTICULATES AND VAPOR.

Ventilation:NONE SPECIFIED BY MANUFACTURER.

Protective Gloves:RECOMMENDED IF SKIN CONTACT IS LIKELY.

Eye Protection:CHEMICAL SPLASH GOGGLES RECOMMENDED.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING OR SAFETY EQUIPMENT AS NEEDED TO AVOID CONTACT.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health
NONE

=====
Physical/Chemical Properties

HCC:F2

Boiling Pt:B.P. Text:250F,121C

Vapor Pres:5.79 MMHG

Vapor Density:>1

Spec Gravity:1.19

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NEGLIGIBLE

Appearance and Odor:RED LIQUID WITH PAINT ODOR.

Percent Volatiles by Volume:56.3

=====
Stability and Reactivity Data

=====

Stability Indicator/Materials to Avoid: YES

STRONG ACIDS AND BASES.

Stability Condition to Avoid: NONE KNOWN.

Hazardous Decomposition Products: NORMAL PRODUCTS OF INCOMPLETE
COMBUSTION.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS. DISPOSE OF USING AN APPROVED INCINERATION
PROCESS, IF PERMITTED.

Disclaime

r (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.