View NSN Online: https://aerobasegroup.com/nsn/8030-01-154-9252

Product ID: INORGANIC DICHROMATE SOLUTION PR1422B-1/2 MSDS Date:12/19/1996 FSC:8030 NIIN:01-154-9252 MSDS Number: CGXPM === Responsible Party === Company Name:COURTAULDS Address:5430 SAN FERNANDO ROAD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Info Phone Num:818-240-2060 Emergen cy Phone Num:800-228-5635/ 818-240-2060 CAGE:83574 === Contractor Identification === Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY Address:5430 SAN FERNANDO RD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Phone:818-240-2060 CAGE:83574

Ingred Name:CALCIUM DICHROMATE CAS:14307-33-6 RTECS #:HX7630000 Fraction by Wt: 20.0% Other REC Limits:NONE RECOMMENDED ACGIH TLV:0.05 MG/M3

Ingred Name:DIMETHYL

ACETAMIDE (VP = 2.0) CAS:127-19-5 RTECS #:AB7700000 Fraction by Wt: 40.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 PPM ACGIH TLV:10 PPM Ingred Name:CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 Fraction by Wt: 200F.>93C Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG. Fire Fighting Procedures: USE COMPLETE PERSONAL PROTECTION. Spill Release Procedures: DIKE & COVER SPILL W/NON-OXIDIZABLE ABSORBENT. SCO OP INTO CONTAINER. SPRINKLE W/SODIUM THIOSULFATE ON RESIDUE. WORK INTO RESIDUE. SCOOP IN DISPOSAL CONTAINER. CLEAN AREA W/WATER. Respiratory Protection: WHEN APPLYING IN CIRCUMSTANCES LIKELY TO PRODUCE AIRBORNE LEVELS OF HAZARDOUS INGREDIENTS IN EXCESS OF TLV, USE ORGANIC VAPOR CARTRIDGE OR AIR SUPPLIED RESPIRATOR. Ventilation: GENERAL VENTILATION TO MAINTAIN VAPORS BELOW PEL. Protective Gloves:NITRILE, BUTYL OR NATU RAL RUBBER Eye Protection: CHEMICAL GOGGLES OR FACE SHIELD Other Protective Equipment: SKIN AREAS SUBJECT TO SPLASH SHOULD BE PROTECTED WITH NITRILE, BUTYL OR NATURAL RUBBER, POLYURETHANE APRON **OR COVERALLS** Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING OR BEFORE SMOKING OR EATING. Supplemental Safety and Health NK

Boiling Pt:B.P. Text:212 TO 520F Vapor Density:>AIR Spec Gravity:1.377 Evaporation Rate & amp; Reference:NA Appearance and Odor:BLACK PASTE Percent Volatiles by Volume:82.0

Stability Indicator/Materials to Avoid:YES EASILY OXIDIZED MATERIAL. Hazardous Decomposition Products:OXIDES OF CARBON & NITROGEN, CHROMIUM COMPOUNDS.

Waste Disposal Methods: IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS. EPA D-007 HAZARDOUS WASTE.

Disclaimer (provide

d with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.