

HY-KLAS PAINTS, INC. -- LATEX WOOD OR MASONRY GRAY #36176 -- 8010-01-396-6785

=====  
Product Identification  
=====

Product ID:LATEX WOOD OR MASONRY GRAY #36176

MSDS Date:07/02/1990

FSC:8010

NIIN:01-396-6785

MSDS Number: CGXVM

=== Responsible Party ===

Company Name:HY-KLAS PAINTS, INC.

Box:3607

City:LOUISVILLE

State:KY

ZIP:40201-3607

Country:US

Info Phone Num:502-634-9406

Emergency Phone Num:502-6

34-9406, 502-589-8222 POISON

CAGE:KO343

=== Contractor Identification ===

Company Name:HY-KLAS PAINTS INC

Box:3607

City:LOUISVILLE

State:KY

ZIP:40201-3607

Country:US

Phone:502-634-9406

CAGE:0HN95

Company Name:HY-KLAS PAINTS, INC

Box:10205

City:LOUISVILLE

State:KY

ZIP:40210

Phone:(502) 634-9406

CAGE:KO343

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 24.0%

Other REC Limits:NONE RECOMMENDED

OSHA

PEL:10 MG/M3  
ACGIH TLV:10 MG/M3

Ingred Name:NEPHELINE SYENITE  
CAS:37244-96-5  
Fraction by Wt: 25.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:10 MG/M3

Ingred Name:MUSCOVITE MICA  
CAS:12003-26-2  
Fraction by Wt: 2.5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:3 MG/M3  
ACGIH TLV:3 MG/M3

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 41.0%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:BICYCLIC OXAZOLIDINES  
CAS:56709-13-8  
Fraction by Wt: 0.12%  
Other REC Limits:NONE RECOMMENDED

I  
ngred Name:2,2,4-TRIMETHYL-1,3 PENTANEDIOL MONOISOBUTYRATE  
CAS:25265-77-4  
Fraction by Wt: 1.0%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:TETRA CHLOROISOPHTHALONITRILE  
CAS:1897-45-8  
Fraction by Wt: 0.6%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHYLENE GLYCOL (SARA 313) (CERCLA)  
CAS:107-21-1  
RTECS #:KW2975000  
Fraction by Wt: 1.0%  
Other REC Limits:NONE RECOMMENDED  
ACGIH TLV:50 PPM  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:AMMONIA (SARA 302/313) (CERCLA)  
CAS:7664-41-7  
RTECS #:BO0875

000  
Fraction by Wt: 0.2%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:50 PPM  
ACGIH TLV:25 PPM  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:FORMALDEHYDE (SARA 3023/313) (CERCLA)  
CAS:50-00-0  
RTECS #:LP8925000  
Fraction by Wt: 0.02%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:2 PPM  
ACGIH TLV:0.3 PPM  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP  
:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE: IRRIT. SKIN: IRRIT. INHAL:  
HEADACHE, NAUSEA, IRRIT TO NOSE/THROAT/LUNGS, LIVER/KIDNEY/CNS  
DAMAGE.  
Medical Cond Aggravated by Exposure:NA

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER. SKIN: FLUSH W/WATER. INHAL: REMOVE TO  
FRESH AIR. INGEST: DRINK 1-2 GLASSES OF WATER. DONT INDUCE VOMIT.  
CALL DR.

===== Fire Fighting Measures =====

E  
xtinguishing Media:NA  
Fire Fighting Procedures:CLOSED CONTAINERS MAY EXPLODE IN EXTREME HEAT.  
Unusual Fire/Explosion Hazard:NA

===== Accidental Release Measures =====

Spill Release Procedures:DIKE AND CONTAIN SPILL W/INERT MATERIAL (SAND,  
EARTH). TRANSFER LIQUID TO CONTAINER FOR RECOVERY/DISPOSAL & SOLID  
DIKING MATERIAL TO SEPARATE CONTAINER FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:K

EEP FROM FREEZING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NA  
Ventilation:MECHANICAL LOCAL EXHAUST  
Protective Gloves:IMPERVIOUS  
Eye Protection:SPLASH GOGGLES  
Work Hygienic Practices:WASH BEFORE EATING.  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C  
Vapor Density:>AIR  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:55-57

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
NA  
Stability Condition to Avoid:NA  
Hazardous Decomposition Products:NA

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE AND  
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The  
United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.