

N/P -- DOW CORNING 200 FLUID 350 CST -- 9150-00-851-4257

Product ID:DOW CORNING 200 FLUID 350 CST

MSDS Date:01/01/1987

FSC:9150

NIIN:00-851-4257

MSDS Number: CHHPN

=== Responsible Party ===

CAGE:71984

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
===== Composition/Information on Ingredients =====
=====

Ingred Name:NON HAZARDOUS INGREDIENTS

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE CONTACT MAY TEMPORARY DISCOMFORT.

SKIN CONTACT; NO ADVERSE EFFECTS EXPECTED. INGESTING SMALL AMOUNTS DURING NORMAL OPERATIONS SHOULD NOT CAUSE INJURY.

INHALATION; NO

ADVERSE EFFECTS LIKELY TO OCCUR DURING SHORT EXPOSURE (8 HRS OR LESS).

Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%

WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.

Effects of Overexposure:EYES-TEMPORARY DISCOMFORT. SKIN-NONE NOTED.

INGESTED-NONE NOTED. INHALATION-NONE NOTED.

Medical Cond Aggravated by Exposure:THIS PRODUCT, AS WITH ANY CHEMICAL

MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN PEOPLE. WE (DOW) DO NOT KNOW OF ANY CON

DITIONS THAT MIGHT BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

=====
First Aid Measures
=====

First Aid:EYES-FLUSH WITH WATER. SKIN-WIPE OFF AND FLUSH WITH WATER. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. INHALED-NO PROBLEM. INGESTED-NO PROBLEM.

=====
Fire Fighting Measures
=====

Flash Point:600F,316C; OC

=====
Accidental Release Measures
=====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:USE REASONABLE CARE AND CAUTION.
Other Precautions:THIS PRODUCT IS SENSITIVE TO CONTAMINATION AT HIGHER TEMPERATURES. IF THIS PRODUCT BECOMES WITH STRONG ACIDS, BASES OR SOME METALLIC COMPOUNDS, OXIDIZERS, THE FLASH POINT & VISCOSITY MAY CHANGE & SHOULD BE DETERMINED.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE NORMALLY REQUIRED.
Ventilation:USE GENERAL DILUTION VENTILATION.SEE SUPPLEMENTAL DATA.
Protective Gloves:WASHING AT MEALTIME IS SUFFICIENT.
Eye Protection:SAFETY GLASSES AT A MINIMUM
Other Protective Equipment:PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.
Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING.
Supplemental Safety an

d Health

TRACES OF FORMALDEHYDE, A CARCINOGEN, MAY BE FORMED WHEN THIS PRODUCT IS HEATED ABOVE 300F/149C; PROVIDE ADEQUATE VENTILATION.

===== Physical/Chemical Properties =====

Viscosity: 350 CST

===== Stability and Reactivity Data =====

Hazardous Decomposition Products: SILICON DIOXIDE, CARBON DIOXIDE, CARBON MONOXIDE AND TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. CONTACT DOW CORNING IF THERE ARE ANY DISPOSAL QUESTIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.