View NSN Online: https://aerobasegroup.co.il/nsn/6750-01-353-9738

EASTMAN KODAK COMPANY -- 197 3247 RAPID FIXER -- 6750-01-353-9738

========= Product Identification ============

Product ID:197 3247 RAPID FIXER

MSDS Date:01/14/1998

FSC:6750

NIIN:01-353-9738

MSDS Number: CHHVM === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

Info Phone Num:716-477-3194

Emergency Phone Num:716-722-5151

CAGE:1 9139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD Box:City:ROCHESTER

State:NY

ZIP:14650-3129 Country:US

Phone:800-828-6203

CAGE:5K871

====== Composition/Information on Ingredients ========

Ingred Name:WATER

CAS:7732-18-5 RTECS #:Z C0110000

Fraction by Wt: 40-45%

Other REC Limits: NONE RECOMMENDED

Ingred Name: AMMONIUM THIOSULFATE

CAS:7783-18-8 RTECS #:XN6465000

Fraction by Wt: 40-45%

Other REC Limits: NONE RECOMMENDED

Ingred Name: SODIUM ACETATE

CAS:127-09-3

RTECS #:AJ4300010 Fraction by Wt: 5-10%

Other REC Limits: NONE RECOMMENDED

Ingred Name:BORIC ACID

CAS:10043-35-3 RTECS #:ED4550000 Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 MG BORATES/M3 ACGIH TLV:5 MG BORATES/M3

Ingred Name: AMMONIUM SULFITE (C

ERCLA)

CAS:10196-04-0 Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: ACETIC ACID (CERCLA)

CAS:64-19-7

RTECS #:AF1225000 Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 PPM

ACGIH TLV:10 PPM/15 STEL; 9596

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: SODIUM BISULFITE (SASA III) (CERCLA)

CAS:7631-90-5

RTECS #:VZ2000000 Fraction by Wt: < 1%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3; 9596 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

======== Hazards Identification =============

LD50 LC50 Mixture:ORAL LD50 (RAT): > 2540 MG/KG Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EXPECTED TO BE A LOW INHALATION HAZARD FOR RECOMMENDED HANDLING. MAY LIBERATE SULFUR DIOXIDE WHICH IS IRRITATING TO RESPIRATORY TRACT. MAY CAUSE TRANSIENT EYE IRRITATION. MAY BE AB

- SORBED IN TOXIC AMOU NTS THROUGH DAMAGED OR ABRADED SKIN. MAY CAUSE SKIN SENSITIZATION. MAY BE HARMFUL IF SWALLOWED.
- Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.
- Effects of Overexposure:RESPIRATORY TRACT IRRITATION,DIFFICULT BREATHING,EYE IRRITATION,SKIN SENSITIZATION,WHEEZING,CHEST TIGHTNESS,STOMACH UPSET,HIVES,FAINTNESS,WEAKNESS,DIARRHEA. BASED ON REPEATED-DOSE
- INGESTION STUDIES IN ANIMALS, MAY CAUSE ADVERSE REPRODUCTIVE AND DEVELOPMENTAL EFFECTS. HOWEVER, DOSES MUCH HIGHER THAN NORMAL EXPOSURE.
- Medical Cond Aggravated by Exposure:SOME ASTHMATICS OR HYPERSENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING, WHEEZING, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS, DIARRHEA.

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL ATTEN

TION IF SYMPTOMS PERSIST. EYES: WASH OUT IMMEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: ONLY INDUCE VOMITING AT ADVICE OF MEDICAL PERSONNEL. CALL PHYSICIAN OR POISON CONTROL ASAP. NEVER GIVE ANYTHING BY MOUTH IF UNCONSCIOUS.

========== Fire Fighting Measures ============

Flash Point:NONFLAMMABLE Lower Limits:NOT GIVEN Upper Limits:NOT GIVEN Extinguish ing Media: NONFLAMMABLE. USE EXTINGUISHING MEDIA SUITABLE FOR SURROUNDING FIRE. Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS. Unusual Fire/Explosion Hazard: NONE SPECIFIED BY MANUFACTURER. ======== Accidental Release Measures ============== Spill Release Procedures:FLUSH TO SEWER IF ALLOWABLE WITH LARGE AMOUNTS OF WATER. OTHERWISE, ABSORB SPILL WITH VER MICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE TO REMOVE RESIDUA L CONTAMINATION. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER. ============ Handling and Storage =========================== Handling and Storage Precautions: AVOID BREATHING MIST OR VAPOR. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. USE WITH ADEQUATE VENTILATION. KEEP FROM CONTACT WITH OXIDIZING MATERIALS. Other Precautions: KEEP CONTAINER TIGHTLY CLOSED. KE **EP AWAY FROM** INCOMPATIBLE SUBSTANCES. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: NONE SHOULD BE NEEDED. A FULL-FACE POSITIVE-PRESSURE AIR-SUPPLIED RESPIRATOR MUST BE WORN IF HAZARDOUS DECOMPOSITION PRODUCTS ARE LIKELY TO BE RELEASED OR HAVE BEEN RELEASED. Ventilation: GOOD GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS. Protective Gloves: IMPERVIOUS Eye Protection: SAFETY GLA SSES W/SIDE SHIELDS OR GOGGLES Other Protective Equipment: CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE. Work Hygienic Practices: WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. Supplemental Safety and Health REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. ========= Physical/Chemical Properties ===========

HCC:N1

Boiling Pt:B.P. Text:>2

12F,>100C
Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN
Decomp Temp:Decomp Text:NOT GIVEN
Vapor Pres:18

Vapor Pres:18 Vapor Density:0.6 Spec Gravity:1.32

pH:5.0

Viscosity:NOT GIVEN

Evaporation Rate & Evaporation R

Solubility in Water: COMPLETE

Appearance and Odor:LIGHT YELLOW LIQUID, SLIGHT SULFUR DIOXIDE, ACETIC ACID ODOR

Percent Volatiles by Volume:40-45%

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES BASES, SODIUM HYPOCHLORITE (BLEACH), STRONG OXIDIZING AGENTS, STRONG ACIDS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE,
OXIDES OF NITROGEN, SULFUR DIOXIDE, AMMONIA, CHLORAMINE.

======= Disposal Considerations ===========

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL LAWS. MAY REQUIRE NEUTRALIZATION IF PH < 2.0 OR PH > 12.5. DISPOSE OF IN ACCORDANCE WITH A LL APPLICABLE

FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the sui tability of this information to their particular situation.