ESGARD, INC. -- PL-5 HYDROCARBON COMPLEX -- 8030-01-396-5754

Product ID:PL-5 HYDROCARBON COMPLEX MSDS Date:09/20/1994 FSC:8030 NIIN:01-396-5754 **MSDS Number: CHKLD** === Responsible Party === Company Name:ESGARD, INC. Address: PO DRAWER 2698 City:LAFAYETTE, State:LA ZIP:70502 Country:US Info Phone Num:318-234-6327 Emergency Phone Num:800-888-2511 CAGE:ESGAR === Co ntractor Identification === **Company Name: ESGARD INC** Address:515 DEBONNAIRE RD Box:City:SCOTT State:LA ZIP:70583 Country:US Phone:318-234-6327 CAGE:0N1W9 Company Name: ESGARD, INC. Address: PO DRAWER 2698 Box:2698 City:LAFAYETTE State:LA ZIP:70502 Country:US Phone:318-234-6327 CAGE:ESGAR

Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 2.08% Other REC Limits:TWA 500 PPM OSHA PEL:100 PPM ACGIH TLV:100 PPM

Ingred Name:VOC = 0.16 LBS/GL RTECS #:9999999VO Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: IRRITATION. SKIN: IRRITATION. INHAL: IRRITATION, NARCOTIC, ANESTHETIC. INGEST: GI DISTRESS, IRRITATION, NAUSEA. CHRONIC: LIVER/KIDNEY DAMAGE

Effects of Overexposure:INHAL: IRRITATION OF RESPIRATORY TRACT, NS DEPRESSION, HEADACHE, DIZZY, STAGGERING, CONFUSION, UNCONSCIOUSNESS, COMA. Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS.

First Aid:EYE: FLUSH W/WATER 15 MINUTES, GET MED AID. SKIN: WASH W/SOAP & WATER 15 MINUTES, GET MED AID. INGEST: DONT INDUCE VOMIT, GET IMMED MED AID. INHAL: REMOVE TO FRESH AIR, ARTIF RESP. GIVE OXYGEN

IF DIFF BREATHING. GET IMMED MED AID.

Flash Point Method:PMCC Flash Point:205F,96C Lower Limits:0.9 Upper Limits:7.0 Extinguishing Media:DRY POWDER, CARBON DIOXIDE, EATER FOG OR SPRAY. Fire Fighting Procedures:APPROACH FIRE FROM UPWIND. AVOID SMOKE, FUMES, MIST/VAPORS DOWNWIND, PROTECTIVE CLOTHES, SCBA. Unusual Fire/Explosion Hazard:PRODUCT WILL FLOAT & MAY IGNITE ON WATER. IF STORED IN DRUMS, CONTAINERS MAY RUPTU

RE, COOL W/WATER. EVAC
PERSONNEL FROM AREA.

======================================
Spill Release Procedures:SM SPILL: ABSORBENT MEDIA. STORE AS NON-HAZARDOUS OIL WASTE. LG SPILLS: CONTAIN W/DIKES. PICK UP W/VACUUM TRUCK. HANDLE AS NON-HAZARDOUS OIL WASTE.
======================================
Handling and Storage Precautions:STORE IN COOL, VENTILATED AREA AWAY FROM IGNIT SOURCES, OXIDIZERS OR MATERIALS W/YELLOW DOT LA BEL.
Other Precautions: CLEAN LEAKS/SPILLS IMMED TO PREVENT WATER/SOIL CONTAMINATION.
======================================
Respiratory Protection:NOT NORMALLY NEEDED. Ventilation:LOCAL EXHAUST AND MECHANICAL VENT. Protective Gloves:CHEMICAL RESISTANT Eye Protection:CHEMICAL GOGGLES/FULL FACE SHIELD. Other Protective Equipment:BOOTS, APRONS, DRENCH SHOWER, EYEWASH STATION. Work Hygienic Practices:AVOID CONTACT W/SKIN/EYES/CLOTHES. WASH HANDS BEFORE EATI NG/DRINKING/SMOKING. REMOVE CONTAM CLOTHES. WASH BEFORE REUSE.
Supplemental Safety and Health NK
======================================
Boiling Pt:B.P. Text:>300F,>149C Melt/Freeze Pt:M.P/F.P Text:NA Vapor Pres:4 Spec Gravity:0.91 (H20 +1) pH: 8-9

Evaporation Rate & amp; Reference: BUAC -1