View NSN Online: https://aerobasegroup.co.il/nsn/6850-01-434-7708

Product ID:S-20 SILICONE OIL, FG2-5962

MSDS Date:03/01/1993

FSC:6850

NIIN:01-434-7708

MSDS Number: CHPJY === Responsible Party ===

Company Name: CANON USA INC Address: ONE CANON PLAZA

City:LAKE SUCCESS

State:NY ZIP:11042 Country:US

Info Phone Num:516-328-5600

Emergency Phone Num:800-424-9300 (CHEMT

REC)

Preparer's Name: JOSEPH PALMERI

CAGE:1BA63

=== Contractor Identification ===
Company Name: CANON USA INC

Address:ONE CANON PLZ Box:City:NEW HYDE PARK

State:NY ZIP:11042 Country:US

Phone:516-328-5000; 5600

CAGE:08YZ7

Company Name: CANON USA INC Address: ONE CANON PLAZA Box: City: LAKE SUCCESS

State:NY ZIP:11042 Country:US

Phone:516-328-5600

CAGE:1BA63

====== Composition/Information on Ingredients ========

Ingred Name:POLY (DIMETHYLSILOXANE); (SILICONE)

CAS:63148-62-9 RTECS #:JJ6484 500

Fraction by Wt: 100%

OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name:SUP DAT: (INCL CARPETING) CLEANED COMMERCIALLY. PETRO DISTILS MAY BE USED, EXCEPT ON PLASTIC/VINYL SURFACES. (ING 3) RTECS #:9999992Z

Ingred Name:ING 2: DISPOSE OF ABSORBENT MATERIAL IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE, AND LOCAL REQUIREMENTS.

RTECS #:9999999ZZ

============= Hazards Identification ===============

LD50 LC50 Mixture:LD50 (ORAL RAT): > 5 G/KG.

Routes of Entry: Inhalation:YES Ski

n:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: SKIN: MAY CAUSE SLIGHT

IRRITATION, BUT NO SIGNIFICANT EFFECT. EYES: MAY CAUSE SLIGHT IRRITATION. CHRONIC: NO KNOWN CHRONIC HEALTH EFFECTS, BUT UNNECESSARY EXPOSURE TO ANY CHEMICAL SHOULD BE AVO IDED.

Explanation of Carcinogenicity: NOT RELEVANT.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:THIS PRODUCT, AS WITH ANY CHEMICAL, MAY ENHAN

CE ALLERGIC CONDITIONS ON CERTAIN PEOPLE.

First Aid:INHALATION: NO FIRST AID SHOULD BE REQUIRED. REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE OXYGEN OR ARTIFICIAL RESPIRATION). EYES: OPEN EYE AND FLUSH WITH FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. SKIN:SINGLE PROLONGED EXPOSURE CAUSES NO KNOWN ADVERSE EFFECT; WIPE AND FLUSH WITH WATER. INGESTION: NO FIRST AID SHOULD BE REQUIRED. CALL MD IMMEDIATELY.

Flash Point:610F,321C

Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM, CARBON DIOXIDE. Fire Fighting Procedures:WEAR NIOSH APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard:NONE.

======== Accidental Release Measures ===========

Spill Release Procedures: USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL.

Neutralizing Agent:NO

NE SPECIFIED BY MANUFACTURER.
=========== Handling and Storage =============
Handling and Storage Precautions: USE REASONABLE CARE AND CAUTION. STORE IN A COOL AREA. KEEP AWAY FROM HEAT AND FLAME. DO NOT LAY CONTAINER ON ITS SIDE.
Other Precautions:AT ELEVATED TEMPERATURES THIS PRODUCT IS SENSITIVE TO CONTAMINATION. IF THIS PRODUCT BECOMES CONTAMINATED W/STRONG ACIDS, BASES/SOME METALLIC COMPOUNDS & OXIDIZING AGENTS, FLASH POINT VISCOSITY MAY CH ANGE & S HOULD BE REDETERMINED. (SUP DAT)
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NO RESPIRATORY PROTECTION REQUIRED. USE NIOSH APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN. Ventilation:NONE SPECIFIED BY MANUFACTURER. Protective Gloves:IMPERVIOUS GLOVES. Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES. Other Protective Equipment:EMERGENCY EYEWASH AND DELUGE SHOWER MEETING ANSI DESIGN CRITERIA. Work Hygienic Practices:WASHING AT M EALTIME AND END OF SHIFT IS ADEQUATE.
Supplemental Safety and Health OTHER PREC: NOTE: THIS OIL IS VERY SLIPPERY & MAY PRESENT SKIDDING/SLIPPING HAZARD. FOLLOWING SPILL/LEAK, USE ABSORB MATL TO CONTAIN & COLLECT EXCESSIVE OIL FOR SALVAGE/DISP. THORO CLEAN FLOOR/OTHER C ONTAM SURFACE (SUCH AS LADDER) & DO NOTLEAVE ANY TRACES OF OIL. USE ALL-PURPOSE ALKALINE CLEANER/HAVE SURFACE (ING 2)
========= Physical/Chemical Properties ==========
Vapor Pres: