

S C JOHNSON & SON INC -- 4435 SHINE-UP POTPOURRI-AEROSOL -- 7930-01-056-9929

=====  
Product Identification  
=====

Product ID:4435 SHINE-UP POTPOURRI-AEROSOL

MSDS Date:02/22/1996

FSC:7930

NIIN:01-056-9929

Status Code:A

MSDS Number: CJBGS

=== Responsible Party ===

Company Name:S C JOHNSON & SON INC

Address:1525 HOWE ST

City:RACINE

State:WI

ZIP:53403-5011

Country:US

Info Phone Num:800-725-6737/800-228

-5635

Emergency Phone Num:800-851-7145/414-631-2777

CAGE:0U826

=== Contractor Identification ===

Company Name:S C JOHNSON & SON INC/PROF WAX DIV

Address:1525 HOWE ST

City:RACINE

State:WI

ZIP:53403

Country:US

Phone:800-725-6737/414-886-1480 INTNL#

CAGE:0U826

Company Name:SC JOHNSON AND SON INC

Address:1525 HOWE ST

Box:City:RACINE

State:WI

ZIP:53403-2236

Country:US

Phone:800-725-6737

CAGE:32204

=====  
Composition/Information on Ingredients  
=====

Ingred Name:BUTANE, N-BUTANE \*98

-2\*

CAS:106-97-8  
RTECS #:EJ4200000  
Fraction by Wt: 1-5%  
Other REC Limits:800 PPM  
OSHA PEL:800 PPM  
ACGIH TLV:1900 MG/CUM

Ingred Name:PROPANE (DIMETHYLMETHANE) \*98-2\*

CAS:74-98-6  
RTECS #:TX2275000  
Fraction by Wt: 1-5%  
Other REC Limits:1800 MG/CUM  
OSHA PEL:1000 PPM  
ACGIH TLV:SIMPLE ASPHYXIAN

Ingred Name:ISOBUTANE, 2-METHYLPROPANE

CAS:75-28-5  
RTECS #:TZ4300000  
Fraction by Wt: 1-5%  
Other REC Limits:1000 PPM  
OSHA PEL:1800 MG/CUM  
ACGIH TLV:1000 PPM

Ingred Name:DIMETHYL POLYSILOXANE (MONOMER: DIMETHYL SILOXANE),

SILICONE FLUID, DOW CORNING 200, POLYMETHYLSILOXANE \*98-2\*  
CAS:63148-62-9  
RTECS #:JT6484500  
Fraction by Wt: 5-10%

Ingred Name:WATER

CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 70-90%

Ingred Name:VOLATILE ORGANIC CONTENT: 1.78 LBS/GAL; THEORETICAL  
RTECS #:9999999VO

Ingred Name:ISOPARAFFINIC HYDROCARBON SOLVENT

CAS:68920-06-9  
Fraction by Wt: 5-10%

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50(RATS): >5000 MG/KG

Routes of

Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES: MILD IRRITANT. SKIN:  
PROLONGED/REPEATED CONTACT MAY CAUSE MILD IRRITATION. INHALATION:  
IRRITATION TO NOSE, THROAT & RESPIRATORY TRACT. INGESTION:  
ASPIRATION INTO THE LUNGS MAY CAUSE SEVERE EFFECTS. INTENTIONAL  
MISUSE BY DELIBERATELY CONCENTRATING/INHALING THE CONTENTS CAN BE  
HARMFUL/FATAL.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH IMMEDIATELY W/WATER FOR 20 MINS. SKIN: WASH  
W/WATER & SOAP. INHALATION: REMOVE TO FRESH AIR. INGESTION:  
IMMEDIATELY DRINK 1-2 GLASSES OF WATER/MILK. DON'T INDUCE VOMITING.  
OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====  
===== Fire Fighting Measures =====

Flash Point:120F, FREEZING

=====  
===== Disposal Considerations =====

=====

Waste Disposal Methods:RECYCLE EMPTY AEROSOL CAN TO NEAREST STEEL  
RECYCLING CENTER. USE UP PACKAGE/GIVE TO SOMEONE WHO CAN. DON'T  
PUNCTURE/INCINERATE. DISPOSE OF IAW/LOCAL, STATE & FEDERAL  
REGULATIONS. UN1950 LTD.QTY AEROSOL.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.