

PACKAGING SERVICES -- P-D-680 TYPE II -- 6850-00-110-4498

===== Product Identification =====

Product ID:P-D-680 TYPE II
MSDS Date:11/17/1998
FSC:6850
NIIN:00-110-4498
Status Code:A
MSDS Number: CJCLR
=== Responsible Party ===
Company Name:PACKAGING SERVICES
Address:4702 SHANK RD
City:PEARLAND
State:TX
ZIP:77588
Country:US
Emergency Phone Num:OUT OF BUSINESS
Preparer's Name:DSCR-BBA(LEVIEN)
CAGE:9
V846

=== Contractor Identification ===
Company Name:PACKAGING SERVICES INC
Address:472 SHANK RD
Box:875
City:PEARLAND
State:TX
ZIP:77581
Country:US
Phone:713-485-1457
CAGE:9V846

===== Composition/Information on Ingredients =====

Ingred Name:STODDARD SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9596

===== Hazards Identification =====

Routes of Entry: Inhala

tion:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHALATION- IRRITATION, CNS EFFECTS. EYES- IRRITATION. SKIN- IRRITATION, SKIN DAMAGE. INGESTION- IRRITATION OF DIGESTIVE TRACT, CNS EFFECTS. CHRONIC: PAINTER'S SYNDROME (BRAIN & NERVOUS SYSTEM DAMAGE).

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYE:REDNESS, BURNING SENSATION. SKIN:REDNESS, DRYING, CRACKING. INHALED:IRRITATION OF RESPIRATORY TRACT,

DIZZINESS, HEADACHE, FATIGUE, DROWSINESS. INGESTED: NAUSEA, VOMITING, DIARRHEA, CNS EFFECTS SIMILAR TO INHALATION.

Medical Cond Aggravated by Exposure:NONE REPORTED. PEOPLE WITH PRE-EXISTING SKIN OR RESPIRATORY DISORDERS MAY BE MORE SUSCEPTABLE TO THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP & WATER. INHALED:REMOVE FROM

EXPOSURE. GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED. GET MEDICAL ATTENTION. INGESTED:DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. IF SYMPTOMS PERSIST,GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:138F,59C

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM, HALON, OR WATER SPRAY

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. USE

WATER TO COOL FIRE EXPOSED CONTAINERS,BEING CAREFUL NOT TO SPREAD FIRE WITH WATER.

Unusual Fire/Explosion Hazard:MATERIAL WILL NOT IGNITE READILY,BUT CAN BE IGNITED BY FLAME AND WILL BURN EASILY ONCE IGNITED. VAPORS ARE HEAVIER THAN AIR AND MAY ACCUMULATE IN LOW AREAS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. ABSORB WITH INERT MATERIAL. STORE IN CLOSED CONTAINER FOR DISPOSAL.

Ne

utralizing Agent:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE TIGHTLY CLOSED IN A COOL, DRY, WELL VENTILATED AREA FREE FROM IGNITION SOURCES. PROPERLY BOND AND GROUND CONTAINERS DURING TRANSFER OPERATIONS.

Other Precautions:"EMPTY" DRUMS MAY CONTAIN SUFFICIENT RESIDUE OR VAPOR TO BE EXPLOSION HAZARD. DO NOT CUT, WELD, GRIND ON "EMPTY" CONTAINERS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH ORGANIC VAPOR RESPIRATOR OR SUPPLIED AIR RESPIRATOR IF EXPOSED ABOVE TLV(PEL).

Ventilation:USE ADEQUATE MECHANICAL VENTILATION. USE EXPLOSION PROOF EQUIPMENT.

Protective Gloves:NITRILE

Eye Protection:SAFETY GLASSES AND/OR SPLASH GOGGLES

Other Protective Equipment:IMPERVIOUS CLOTHING (IF NEEDED TO PREVENT PROLONGED/REPEATED CONTACT). EYE WASH/SAFETY SHOWER.

Work Hygienic Practices:USE NORMAL CHEMICAL HYGIENE PROCEDURES. DO NOT EAT, DRINK, OR SMOKE UNTIL WASHING HANDS.

Supplemental Safety and Health
NONE

=====
===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:370F,188C

Vapor Pres: