View NSN Online: https://aerobasegroup.com/nsn/8040-01-017-7380

SUREGUARD INC. -- CAN-TEX NO. 99 CONDUIT SOLVENT CEMENT -- 5975-01-017-7380

Product ID:CAN-TEX NO. 99 CONDUIT SOLVENT CEMENT

MSDS Date:06/15/1988

FSC:5975

NIIN:01-017-7380

Status Code:A

MSDS Number: CJDDL === Responsible Party ===

Company Name: SUREGUARD INC.

Address:514 BISHOP AVE.

City:RICHARDSON

State:TX ZIP:75081

Emergency Phone Num:(214) 234-2481

CAGE:SUREG

=== Contractor Identification === Company Name: CANTEX CORP

Address: ROTTERDAM INDUSTRIAL PK BLDG NO 1

Box:City:SCHENECTADY

State:NY ZIP:12306 Country:US

Phone:800-833-6146

CAGE:5K616

Company Name: DIXIE ELECTRIC SUPPLY CORP

Address: 1901 N HAMILTON STREET

Box:6522

City:RICHMOND

State:VA

ZIP:23230-4101 Country:US

Contract Num:SP040098AAC941016

CAGE:2E492

Company Name: SUREGUARD INC.

Address:514 BISHOP AVE.

City:RICHARDSON

State:TX ZIP:75081

Phone: (214) 234-2481

CAGE:SUREG

====== Composition/

| Information on Ingredients | ======== |
|----------------------------|--------------------|
| Ingred Name:TETRAHYDF | ROFURAN (SARA III) |

CAS:109-99-9

RTECS #:LU5950000

Other REC Limits:NONE SPECIFIED OSHA PEL:200 PPM/250 STEL

ACGIH TLV:200 PPM/250STEL;9192

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Other REC Limits:NONE SPECIFIED OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: CYCLOHEXANONE (S

ARA III)

CAS:108-94-1

RTECS #:GW1050000

Other REC Limits: NONE SPECIFIED

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

========== Hazards Identification ===============

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRITATION, INFLAMMATION,

CONJUNCTIVITIS. SKIN: DRYNESS, DEFATTING, IRRITATION. INHALATION:

NASAL AND RESPIRATO

RY TRACT IRRITATION, HEADACHE, NAUSEA, DRY

THROAT, DIZZINESS. INGESTION: CENTRAL NERVOUS SYSTEM DEPRESSION.

Explanation of Carcinogenicity: NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:EXPOSURE TO HIGH VAPOR CONCENTRATIONS MAY CAUSE NAUSEA, DIZZINESS, HEADACHES, NARCOSIS OR LACK OF COORDINATION.

First Aid:EYES: IMMEDIATELY FLUSH WITH LARGE AMOUNTS O

| INHALATION: MOVE TO FRESH AIR. LIMIT PHYSICAL ACTIVITY. | | | |
|--|--|--|--|
| ====================================== | | | |
| Flash Point Method:TCC Flash Point:=-14.4C, 6.F Lower Limits:2 Upper Limits:11.8 Extinguishing Media:WATER SPRAY, DRY CHEMICAL OR CARBON DIOXIDE FOAM. Fire Fighting Procedures:HANDLE AS A VERY FLAMMABLE LIQUID. RED LABEL. Unusual Fire/Explosion Hazard:EVACUATE AFFECTED AREA, STAY UPWIND AND AVOID SMOKE AND FUMES. USE WATER SPRAY TO COOL CONTAINERS, VAP ORS ARE HEAVIER THAN AIR. | | | |
| ======== Accidental Release Measures ========== | | | |
| Spill Release Procedures:SHUT OFF LEAK IF POSSIBLE WITHOUT INJURY. SHUT OFF OR REMOVE IGNITION SOURCES. ABSORB SPILL WITH INERT MATERIAL. | | | |
| ====================================== | | | |
| Handling and Storage Precautions:DO NOT STORE ABOV3 120F. HANDLE AS AN EXTREMELY FLAMMABLE LIQUID. Other Precautions:STORE MATERIAL IN ORIGINAL CONTAINERS IN A COOL, DRY, SH ELTERED AREA. EMPTY CONTAINERS ARE A FIRE HAZARD. DISPOSE OF PROPERLY. | | | |
| ====== Exposure Controls/Personal Protection ======== | | | |
| Respiratory Protection:PROVIDE GOOD VENTILATION IF USED INDOORS. Ventilation:EXPLOSION PROOF MOTOR REQUIRED. Protective Gloves:NOT NORMALLY REQUIRED. Eye Protection:NOT NORMALLY REQUIRED. Supplemental Safety and Health KEEP CONTAINER CLOSED WHEN NOT IN USE. TRANSFER ONLY TO APPROVED | | | |

CONTAINERS WITH COMPLETE AND APPROPRIATE LABELING. DO NOT TAKE

F WATER.

INTERNALLY. DO NOT PUNCTURE, DRAG, OR SLIDE CONTAINER. MATERIAL CANNOT B E MADE NON-POISONOUS.

| ========== | Physical/Chemical | Properties | ======================================= |
|------------|-------------------|------------|---|
|------------|-------------------|------------|---|

HCC:F2

Vapor Pres:82.5 @75F Vapor Density:2.5 (AIR=1

Spec Gravity:0.91

Solubility in Water: NOT MIISCIBLE

Appearance and Odor: MOBILE LIQUID PUNGENT ODOR

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

OXIDIZERS, PEROXIDES, OXYGEN, SODIUM HYDROXIDE.

Stability Condit

ion to Avoid: EXPOSURE TO LIGHT AND AIR.

Hazardous Decomposition Products: CARBON DIOXIDE, CARBON MONOXIDE, HYDROGEN CHLORIDE.

Conditions to Avoid Polymerization: UNSTABLE PEROXIDES MAY FORM ON LONG STANDING.

======= Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS FOR DISPOSAL OF FLAMMABLE ORGANIC COMPOUNDS.

Disclaimer (provided with this information by the compiling agencies): Thi

s information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.