

FARWEST PAINT MFG CO -- RED STENCIL PAINT 31136 -- 8010-00-285-4931

=====  
Product Identification  
=====

Product ID:RED STENCIL PAINT 31136

MSDS Date:03/01/1998

FSC:8010

NIIN:00-285-4931

Status Code:A

MSDS Number: CJGBW

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:TUKWILA

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-8844

Emergency P

hone Num:206-941-1619

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALIPHATIC HYDROCARBON

CAS:64742-89-8

Fraction by Wt: 13.46%

OSHA PEL:500 PPM

ACGIH TLV:300 PPM

Ingred Name:AROMATIC HYDROCARBONS

CAS:64742-95-6

Fraction by Wt: 17.64%

OSHA PEL:300 PPM

ACGIH TLV:300 PP

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:SKIN: PROLONGED/REPEATED CONTACT MAY CAUSE IRRITATION, SENSITIZATION, OR DEFATTING OF SKIN. INHAL: EXCESSIVE EXPOSURE TO VAPORS/SPRAY MISTS CAN PRODUCE HEADACHE, DIZZINESS, NAUSEA, & LOSS OF CONSCIOUS NESS. SOME REPORTS HAVE ASSOCIATED REPEATED/PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS W/ PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. EYES: IRRITANT.  
Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE WITH HANDLING INSTRUCTIONS.

=====  
First Aid Measures  
=====

First Aid:SKIN: PROMPTLY WASH W/ SOAP & WATER. REMOVE AND WASH ANY CONTAMINATED CLOTHING BEFORE REUSE. EYES: WASH W/ LARGE AMOUNTS OF WATER FOR 15 MINUTES AND SEEK MED ATTN. INGEST: DO NOT INDUCE VOMITING. KEEP WARM & QUIET, AND GET MED ATTN. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. SEEK MED ATTN. INHALATION: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS DEVELOP, SEEK MED ATTN AT ONCE.

=====  
Fire Fighting Measures  
=====

Flash Point:=10.C, 50.F  
Lower Limits:1.0  
Upper Limits:7.0  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG. ANY CLASS B EXTINGUISHING AGENT. WATER MAY BE UNSUITABLE AS EXTINGUISHING MEDIUM, BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL.  
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA OF UNPROTECTED PERSONEL. WEAR PROTECTIVE CLOTHING.  
Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE IN AIR & MAY BE IGNITED BY SPARKS, PILOT LIGHTS, ETC. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE SOURCES OF IGNITION AND VENTILATE ARE

A.

ADSORB ON INERT MATERIAL SUCH AS SAWDUST, VERMICULITE, OR SAND, AND PLACE MATERIAL IN CLOSED CONTAINER. LARGE SPILL: DIKE AREA TO PREVENT FROM ENTERING SEWER OR WATERWAY. WEAR PROTECTIVE EQUIPMENT DURING CLEAN UP.

Neutralizing Agent:NONE

=====  
===== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED/REPEATED INHALATION OF HEATED VAPORS/SPRAY MISTS. KEEP AWAY FROM HEAT/OPEN FLAME. MATERIAL MAY CAUSE SENSITIZATION

. DO NOT GET IN EYES, ON SKIN OR CLOTHING.

DO NOT ALLOW CONTAM CLOTHIN G TO CONTACT SKIN. DO NOT WELD ON FULL/EMPTY CONTAINERS.

Other Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE & PROPERLY LABELED.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:CANNISTER TYPE RESPIRATOR MUST BE WORN TO PREVENT INHALATION OF VAPORS/SPRAY MISTS WHEN TLV/PEL EXCEEDED.

Ventilation:GENERAL VENTILATION DURING NORMAL USE. LOCAL VENTILATION MAY BE

REQUIRED DURING CERTAIN OPERATIONS TO KEEP EXPOSURE LEVEL

1

VOC Pounds/Gallon:411

Viscosity:75 - 90KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:RED MEDIUM VISCOUS LIQUID W / MILD, SWEET AROMATIC ODOR

Percent Volatiles by Volume: